



1 Startup

The photo below shows the output voltage startup waveform after the application of 12V in. The 12V output was loaded to 0A. (5V/DIV, 5mS/DIV)




The photo below shows the output voltage startup waveform after the application of 12V in. The 12V output was loaded to 5A. (5V/DIV, 5mS/DIV)




2 Efficiency


The converter efficiency is shown below for $V_{in} = 12V$ and $V_{out} = 12V$.



The converter efficiency is shown below for $V_{in} = 16V$ and $V_{out} = 12V$.




The converter efficiency is shown below for $V_{in} = 6V$ and $V_{out} = 12V$.



3 Output Ripple Voltage

The 12V output ripple voltage (AC coupled) is shown in the figure below. The image was taken with the output loaded to 5A. The input voltage is set to 6V. (200mV/DIV, 2uS/DIV)



The 12V output ripple voltage (AC coupled) is shown in the figure below. The image was taken with the output loaded to 5A. The input voltage is set to 16V. (200mV/DIV, 2uS/DIV)



The 12V output ripple voltage (AC coupled) is shown in the figure below. The image was taken with the output loaded to 5A. The input voltage is set to 12V. (200mV/DIV, 2uS/DIV)




The 12V output ripple voltage (AC coupled) is shown in the figure below. The image was taken with the output loaded to 1A. The input voltage is set to 12V. (50mV/DIV, 2uS/DIV)




4 Load Transients

The photo below shows the 12V output voltage (ac coupled) when the load current is stepped between 1A and 5A. $V_{in} = 12V$.
(500mV/DIV, 2A/DIV, 1mS/DIV)




The photo below shows the 12V output voltage (ac coupled) when the load current is stepped between 3A and 5A. $V_{in} = 12V$.
(200mV/DIV, 2A/DIV, 1mS/DIV)




5 Switch Node Waveforms


The photo below shows the FET switching voltage (TP2) for an input voltage of 6V and a 5A load. (10V/DIV, 2uS/DIV)




The photo below shows the FET switching voltage (TP2) for an input voltage of 16V and a 5A load. (10V/DIV, 2uS/DIV)



The photo below shows the FET switching voltage (TP2) for an input voltage of 6V and a 0.32A load. The converter is operating in DCM. (10V/DIV, 2uS/DIV)



The photo below shows the FET switching voltage (TP2) for an input voltage of 16V and a 1.05A load. The converter is operating in DCM. (10V/DIV, 2uS/DIV)




6 Loop Gain

The plot below shows the loop gain with the input voltage set to 12V and the output set to 5A.

Loop Gain ($V_{in} = 12V$)

BW: 3.78KHz

PM: 46 degrees




The plot below shows the loop gain with the input voltage set to 12V and the output set to 1A.

Loop Gain ($V_{in} = 12V$)

BW: 4.35KHz

PM: 47 degrees




The plot below shows the loop gain with the input voltage set to 6V and 16V and the output set to 5A.

Loop Gain (Vin = 6V)
 Loop Gain (Vin = 16V)

BW: 495Hz
 BW: 5.37KHz

PM: 95 degrees
 PM: 54 degrees




The plot below shows the loop gain with the input voltage set to 6V and 16V and the output set to 1A.

Loop Gain (Vin = 6V)
 Loop Gain (Vin = 16V)


BW: 2.31KHz
 BW: 3.79KHz

PM: 70 degrees
 PM: 64 degrees




7 Photo

The photo below shows the PMP10886 REVA assy.



8 Thermal Image

A thermal image is shown below operating at 12V input and 12V@5A output (room temp, no airflow).



IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (<https://www.ti.com/legal/termsofsale.html>) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2021, Texas Instruments Incorporated