

Application Report

MSP430 + DRV83xx Selection Guide for Power Tools



1 Introduction

To effectively spin a Brushless-DC motor in cordless power tools, an appropriate microcontroller (MCU) must be selected to provide a trapezoidal control algorithm, communicate to the gate driver to configure settings and diagnose faults, and consume minimal power to improve battery life. In addition, when using more complex control techniques such as sensorless control, the MCU must be able to calculate real-time motor phase voltages and currents to accurately detect rotor position and measure Back-EMF crossings.

Table 1-1. MCU + DRV Selection Table Including Required Evaluation Tools and Designs

Application	ABS MAX (V)	MCU	Gate Driver	Required Evaluation Tools and Designs			Sensored or Sensorless Trapezoidal Control Included?
				MCU Evaluation Board	Gate Driver Evaluation Module	Software/GUI/ Design Files	
Power Tool	40	MSP430 General Purpose MCUs ranging from 0.5kB up to 64kB	DRV8304x 40-V max 3-phase smart gate driver with current shunt amplifiers	MSP430F5529 MCU Launchpad ⁽¹⁾	BOOSTXL-DRV8304H	DRV8304 Software + GUI	Both
	65		DRV8320S 65-V max 3-phase smart gate driver with SPI interface		BOOSTXL-DRV8320S	DRV832x Software + GUI	
			DRV8320H 65-V max 3-phase smart gate driver with Hardware interface		BOOSTXL-DRV8320H		
			DRV8323RS 65-V max 3-phase smart gate driver with buck regulator, current shunt amplifiers, and SPI interface		BOOSTXL-DRV8323RS		

Table 1-1. MCU + DRV Selection Table Including Required Evaluation Tools and Designs (continued)

Application	ABS MAX (V)	MCU	Gate Driver	Required Evaluation Tools and Designs			Sensored or Sensorless Trapezoidal Control Included?
				MCU Evaluation Board	Gate Driver Evaluation Module	Software/GUI/Design Files	
Power Tool (cont)	65 (cont)	MSP430 General Purpose MCUs ranging from 0.5kB up to 64kB (cont)	DRV8323RH 65-V max 3-phase smart gate driver with buck regulator, current shunt amplifiers, and Hardware interface	MSP430F5529 MCU Launchpad ⁽¹⁾ (cont)	BOOSTXL-DRV8323RH	DRV832x Software + GUI (cont)	Both (cont)
Vacuum/blower/fan			DRV8320x 65-V max 3-phase smart gate driver	TIDA-010031			Sensorless
Garden tool/Lawn mower	102		DRV8350R 102-V max 3-phase smart gate driver with buck regulator	TIDA-010056			Sensored

1. MSP430FR2355 MCU Launchpad solution to be released October 2020 as replacement for MSP430F5529 Launchpad.

2 Description

For evaluation purposes, [MSP430FR2355](#) FRAM-based MCUs and [MSP430F5529](#) Flash-based are two general purpose MCUs well-suited for motor control applications such as power tools, vacuum cleaners, and garden tools. The MSP430FR2355 MCU integrates 32KB FRAM, 12-bit ADCs, universal asynchronous receiver/transmitter (UART)/serial peripheral interface (SPI)/inter-integrated circuit (I2C), and four 16-bit timers in a 48-pin LQFP package, and the MSP430F5529 MCU includes 128KB Flash, 12-bit ADCs, UART/SPI/I2C, USB, and four 16-bit timers in an 80-pin LQFP package. These peripherals on both MCUs are capable of providing 6 PWM control signals to the gate driver inputs, SPI to communicate to the gate driver, ADCs for optional motor phase current and phase voltage from the gate driver from the gate driver, and UART or USB compatibility for GUI interface.

Both MCUs are recommended to use with the [DRV8304x](#), [DRV832x](#), and [DRV835x](#) 3-phase Smart Gate Driver devices from Texas Instruments. These gate drivers are ideal for Brushless-DC motors in power tool applications, blowers, fans, garden tools, and lawn mowers because they optimize external MOSFET gate switching and power stage design while providing optional integrated Current Shunt Amplifiers for sensed or sensorless control.

To expedite the evaluation process, Texas Instruments provides the [BOOSTXL-DRV8304H](#), [BOOSTXL-DRV8320S](#), [BOOSTXL-DRV8320H](#), [BOOSTXL-DRV8323RS](#), and [BOOSTXL-DRV8323RH](#) Evaluation Modules to interface with the [MSP-EXP430F5529LP](#) and [MSP-EXP430FR2355](#) Launchpad Development Kits. Each EVM includes a “Software Files” folder on their product page that includes firmware examples and a GUI. The firmware includes sensed and sensorless projects to use with the BOOSTXL-DRV8304x or BOOSTXL-DRV832x EVM GUIs.

In addition, Texas Instruments provides two reference designs, [TIDA-010031](#) and [TIDA-010056](#), which demonstrate high-speed, high-power, and/or high-efficiency solutions for Brushless-DC motor drives. TIDA-010031 uses a high-speed sensorless trapezoidal to spin motors up to speeds of 180,000 RPM, and TIDA-010056 demonstrates a >99% efficient power stage in a small PCB form factor optimized for driving a three-phase BLDC motor in cordless power tools. Both designs utilize the MSP430FR2355 FRAM-based MCU as a cost-effective, smart microcontroller to meet the various end equipment system needs.

No matter the design challenges, Texas Instruments provides solutions to help you through the evaluation process and suit your power tool needs. The breadth of the MSP430 MCU portfolio, as well as the wide offerings of gate driver solutions, allows for the design and development of different classes of power tools from cordless hand-held tools to more robust garden tools.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (www.ti.com/legal/termsofsale.html) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2020, Texas Instruments Incorporated