

CSD25483F4 20V P 沟道 FemtoFET™ MOSFET

1 特性


- 超低导通电阻
- 超低 Q_g 和 Q_{gd}
- 高漏极工作电流
- 超小封装尺寸 (0402 外壳尺寸)
 - $1.0\text{mm} \times 0.6\text{mm}$
- 超薄型封装
 - 最大高度: 0.36mm
- 集成型 ESD 保护二极管
 - 额定值 $> 4\text{kV}$ HBM
 - 额定值 $> 2\text{kV}$ CDM
- 无铅且无卤素
- 符合 RoHS

2 应用

- 针对负载开关应用进行了优化
- 针对通用开关应用进行了优化
- 电池应用
- 手持式和移动类应用

3 说明

此 $210\text{m}\Omega$ 、 20V P 沟道 FemtoFET™ MOSFET 经过设计和优化, 能够最大限度地减小在许多手持式和移动应用中占用的空间。这项技术能够在替代标准小信号 MOSFET 的同时将封装尺寸减小至少 60%。



典型器件尺寸

产品概要

$T_A = 25^\circ\text{C}$		典型值	单位
V_{DS}	漏源电压	-20	V
Q_g	栅极电荷总量 (-4.5V)	959	pC
Q_{gd}	栅极电荷 (栅漏极)	161	pC
$R_{DS(on)}$	漏源导通电阻	$V_{GS} = -1.8\text{V}$	530 $\text{m}\Omega$
		$V_{GS} = -2.5\text{V}$	338 $\text{m}\Omega$
		$V_{GS} = -4.5\text{V}$	210 $\text{m}\Omega$
$V_{GS(th)}$	阈值电压	-0.95	V

订购信息⁽¹⁾


器件	数量	介质	封装	配送
CSD25483F4	3000	7 英寸卷带	Femto (0402)	卷带包装
CSD25483F4T	250		$1.0\text{mm} \times 0.6\text{mm}$ 基板栅格阵列 (LGA)	

(1) 如需了解所有可用封装, 请参阅数据表末尾的可订购产品附录。

绝对最大额定值

$T_A = 25^\circ\text{C}$		值	单位
V_{DS}	漏源电压	-20	V
V_{GS}	栅源电压	-12	V
I_D	持续漏极电流 ⁽¹⁾	-1.6	A
I_{DM}	脉冲漏极电流 ⁽²⁾	-6.5	A
I_G	持续栅极钳位电流	-35	mA
	脉冲栅极钳位电流 ⁽²⁾	-350	
P_D	功率耗散 ⁽¹⁾	500	mW
$V_{(ESD)}$	人体放电模型 (HBM)	4	kV
	充电器件模型 (CDM)	2	kV
T_J 、 T_{stg}	运行结温和贮存温度范围	-55 至 150	$^\circ\text{C}$

- (1) $R_{\theta JA} = 85^\circ\text{C/W}$ (0.06 英寸 (1.52mm) 厚 FR4 PCB 上 1 平方英寸 (6.45cm²) 2oz. (0.071mm) 厚的铜焊盘上的典型值)。
- (2) 脉冲持续时间 $\leq 300 \mu\text{s}$, 占空比 $\leq 2\%$



顶视图



Table of Contents

1 特性.....	1	6.1 Trademarks.....	6
2 应用.....	1	6.2 Electrostatic Discharge Caution.....	6
3 说明.....	1	6.3 术语表.....	6
4 Revision History.....	2	7 Mechanical Data.....	7
5 Specifications.....	3	7.1 Mechanical Dimensions.....	7
5.1 Electrical Characteristics.....	3	7.2 Recommended Minimum PCB Layout.....	8
5.2 Thermal Information.....	3	7.3 Recommended Stencil Pattern.....	8
5.3 Typical MOSFET Characteristics.....	4	7.4 CSD25483F4 Embossed Carrier Tape Dimensions....	9
6 Device and Documentation Support.....	6		

4 Revision History

注：以前版本的页码可能与当前版本的页码不同

Changes from Revision E (October 2021) to Revision F (January 2022)	Page
• 将特性中的最大高度从“0.35mm”更改为“0.36mm”	1
• 将典型器件尺寸的高度尺寸从“0.35mm”更改为“0.36mm”	1
• Changed maximum height dimension from "0.35 mm" to "0.36 mm" in <i>Mechanical Dimensions</i>	7
Changes from Revision D (October 2014) to Revision E (October 2021)	Page
• 更新了整个文档中的表格、图和交叉参考的编号格式.....	1
• Added footnote with link to support document.....	8
Changes from Revision C (July 2014) to Revision D (October 2014)	Page
• Corrected timing V_{DS} to read - 10 V	3
Changes from Revision B (February 2014) to Revision C (July 2014)	Page
• Corrected capacitance units to read pF in 图 5-5	4
Changes from Revision A (December 2013) to Revision B (February 2014)	Page
• 更新了特性中的“无铅且无卤素”	1
• 添加了 I_G 参数.....	1
• Lowered I_{DSS} limit.....	3
• Lowered I_{GSS} limit.....	3
Changes from Revision * (October 2013) to Revision A (December 2013)	Page
• 更正了电阻值的拼写错误.....	1

5 Specifications

5.1 Electrical Characteristics

(T_A = 25°C unless otherwise stated)

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
STATIC CHARACTERISTICS						
BV _{DSS}	Drain-to-Source Voltage	V _{GS} = 0 V, I _{DS} = - 250 μ A	- 20			V
I _{DSS}	Drain-to-Source Leakage Current	V _{GS} = 0 V, V _{DS} = - 16 V	- 100			nA
I _{GSS}	Gate-to-Source Leakage Current	V _{DS} = 0 V, V _{GS} = - 12 V	- 50			nA
V _{GS(th)}	Gate-to-Source Threshold Voltage	V _{DS} = V _{GS} , I _{DS} = - 250 μ A	- 0.70	- 0.95	- 1.2	V
R _{DS(on)}	Drain-to-Source On-Resistance	V _{GS} = - 1.8 V, I _{DS} = - 0.1 A		530	1070	mΩ
		V _{GS} = - 2.5 V, I _{DS} = - 0.5 A		338	390	mΩ
		V _{GS} = - 4.5 V, I _{DS} = - 0.5 A		210	245	mΩ
		V _{GS} = - 8 V, I _{DS} = - 0.5 A		175	205	mΩ
g _{fs}	Transconductance	V _{DS} = - 10 V, I _{DS} = - 0.5 A		1.4		S
DYNAMIC CHARACTERISTICS						
C _{iss}	Input Capacitance	V _{GS} = 0 V, V _{DS} = - 10 V, f = 1 MHz		198		pF
C _{oss}	Output Capacitance			82		pF
C _{rss}	Reverse Transfer Capacitance			5.8		pF
R _G	Series Gate Resistance			20		Ω
Q _g	Gate Charge Total (4.5 V)	V _{DS} = - 10 V, I _{DS} = - 0.5 A		959		pC
Q _{gd}	Gate Charge Gate-to-Drain			160		pC
Q _{gs}	Gate Charge Gate-to-Source			252		pC
Q _{g(th)}	Gate Charge at V _{th}			122		pC
Q _{oss}	Output Charge	V _{DS} = - 10 V, V _{GS} = 0 V		1081		pC
t _{d(on)}	Turn On Delay Time	V _{DS} = - 10 V, V _{GS} = - 4.5 V, I _{DS} = - 0.5 A, R _G = 2 Ω		4.3		ns
t _r	Rise Time			3.7		ns
t _{d(off)}	Turn Off Delay Time			17.4		ns
t _f	Fall Time			7		ns
DIODE CHARACTERISTICS						
V _{SD}	Diode Forward Voltage	I _{SD} = - 0.5 A, V _{GS} = 0 V	- 0.75			V
Q _{rr}	Reverse Recovery Charge	V _{DS} = - 10 V, I _F = - 0.5 A, di/dt = 100 A/ μ s	1060			pC
t _{rr}	Reverse Recovery Time		7.5			ns

5.2 Thermal Information






(T_A = 25°C unless otherwise stated)

THERMAL METRIC		TYPICAL VALUES	UNIT
R _{θJA}	Junction-to-Ambient Thermal Resistance ⁽¹⁾	85	°C/W
	Junction-to-Ambient Thermal Resistance ⁽²⁾	245	

- (1) Device mounted on FR4 material with 1-inch² (6.45 cm²), 2-oz. (0.071-mm thick) Cu.
 (2) Device mounted on FR4 material with minimum Cu mounting area.

5.3 Typical MOSFET Characteristics

($T_A = 25^\circ\text{C}$ unless otherwise stated)



5.3 Typical MOSFET Characteristics (continued)

($T_A = 25^\circ\text{C}$ unless otherwise stated)




图 5-6. Threshold Voltage vs Temperature




图 5-7. On-State Resistance vs Gate-to-Source Voltage




图 5-8. Normalized On-State Resistance vs Temperature




图 5-9. Typical Diode Forward Voltage




图 5-10. Maximum Safe Operating Area




图 5-11. Maximum Drain Current vs Temperature

6 Device and Documentation Support

6.1 Trademarks

FemtoFET™ is a trademark of Texas Instruments.

所有商标均为其各自所有者的财产。

6.2 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

6.3 术语表


TI 术语表

本术语表列出并解释了术语、首字母缩略词和定义。

7 Mechanical Data

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

7.1 Mechanical Dimensions




- A. All linear dimensions are in millimeters (dimensions and tolerancing per AME T14.5M-1994).
- B. This drawing is subject to change without notice.
- C. This package is a PB-free solder land design.

Pin Configuration


Position	Designation
Pin 1	Gate
Pin 2	Source
Pin 3	Drain

7.2 Recommended Minimum PCB Layout





- A. All dimensions are in millimeters.
- B. For more information, see [FemtoFET Surface Mount Guide](#) (SLRA003D).

7.3 Recommended Stencil Pattern



- A. All dimensions are in millimeters.

7.4 CSD25483F4 Embossed Carrier Tape Dimensions



- A. Pin 1 is oriented in the top-right quadrant of the tape enclosure (quadrant 2), closest to the carrier tape sprocket holes.

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead finish/ Ball material (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
CSD25483F4	ACTIVE	PICOSTAR	YJC	3	3000	RoHS & Green	NIAU	Level-1-260C-UNLIM	-55 to 150	DR	Samples
CSD25483F4T	ACTIVE	PICOSTAR	YJC	3	250	RoHS & Green	NIAU	Level-1-260C-UNLIM	-55 to 150	DR	Samples

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBsolete: TI has discontinued the production of the device.

⁽²⁾ **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

Green: TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

⁽³⁾ MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

⁽⁴⁾ There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.


⁽⁵⁾ Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

⁽⁶⁾ Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer:The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


TAPE AND REEL INFORMATION



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
CSD25483F4	PICOSTAR	YJC	3	3000	180.0	8.4	0.7	1.1	0.46	4.0	8.0	Q2
CSD25483F4T	PICOSTAR	YJC	3	250	180.0	8.4	0.7	1.1	0.46	4.0	8.0	Q2

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
CSD25483F4	PICOSTAR	YJC	3	3000	182.0	182.0	20.0
CSD25483F4T	PICOSTAR	YJC	3	250	182.0	182.0	20.0

重要声明和免责声明

TI“按原样”提供技术和可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证没有瑕疵且不做任何明示或暗示的担保，包括但不限于对适销性、某特定用途方面的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任：(1) 针对您的应用选择合适的 TI 产品，(2) 设计、验证并测试您的应用，(3) 确保您的应用满足相应标准以及任何其他功能安全、信息安全、监管或其他要求。

这些资源如有变更，恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的应用。严禁对这些资源进行其他复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。您应全额赔偿因在这些资源的使用中对 TI 及其代表造成的任何索赔、损害、成本、损失和债务，TI 对此概不负责。

TI 提供的产品受 [TI 的销售条款](#) 或 [ti.com](#) 上其他适用条款/TI 产品随附的其他适用条款的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。

TI 反对并拒绝您可能提出的任何其他或不同的条款。

邮寄地址：Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2024，德州仪器 (TI) 公司