
TPS22998 5.5V、10A、导通电阻为 4mΩ 的负载开关

1 特性

- 输入电压范围 (V_{IN})：0.2 V 至 5.5V
- 偏置电压范围：2.2 V 至 5.5V
- 最大持续电流：10A
- 导通电阻 (R_{ON})：4mΩ（典型值）
- 带三态引脚的可调压摆率
- 快速输出放电 (QOD)：50Ω
- 热关断
- 低功耗：
  - 导通状态 (I_Q)：15μA（典型值）
  - 关闭状态 (I_{SD})：3μA（典型值）

2 应用

- 固态硬盘
- PC 和笔记本电脑
- 工业 PC
- 光学模块



TPS22998 方框图

3 说明

TPS22998 是一款单通道负载开关，具有可配置上升时间，从而可更大限度地降低浪涌电流。此器件包含一个可在 0.2V 至 5.5V 输入电压范围内运行的 N 沟道 MOSFET，并且支持 10A 的最大连续电流。


开关可由一个打开和关闭输入 (ON) 控制，此输入可与低压控制信号 (V_{IH} = 0.9V) 直接连接。TPS22998 在开关关闭时具有固定快速输出放电，将输出下拉至接地。

TPS22998 采用 10 引脚 WQFN 封装 (RYZ)（1.5mm × 2mm，间距为 0.5mm）并可在自然通风条件下的 –40°C 至+105°C 温度范围运行。

器件信息

器件型号	封装(1)	封装尺寸（标称值）
TPS22998	WQFN (10)	1.5mm × 2.0mm

(1) 要了解所有可用封装，请参见产品说明书末尾的可订购产品附录。



TPS22998 典型应用

本文档旨在为方便起见，提供有关 TI 产品中文版本的信息，以确认产品的概要。有关适用的官方英文版本的最新信息，请访问 www.ti.com，其内容始终优先。TI 不保证翻译的准确性和有效性。在实际设计之前，请务必参考最新版本的英文版本。

Table of Contents

1 特性 1
2 应用 1
3 说明 1
4 Revision History 2
5 Pin Configuration and Functions 3
6 Specifications 4
6.1 Absolute Maximum Ratings 4
6.2 ESD Ratings 4
6.3 Recommended Operating Conditions 4
6.4 Thermal Information 4
6.5 Electrical Characteristics (VBIAS = 5 V) 5
6.6 Electrical Characteristics (VBIAS = 3.3 V) 5
6.7 Electrical Characteristics (VBIAS = 2.2 V) 6
6.8 Switching Characteristics (VBIAS = 2.2 V to 5 V) 7
6.9 Timing Diagram 8
6.10 Typical Characteristics 9
7 Detailed Description 11
7.1 Overview 11
7.2 Functional Block Diagram 11
7.3 Feature Description 11
7.4 Device Functional Modes 12
8 Application and Implementation 13
8.1 Application Information 13
8.2 Typical Application 13
9 Power Supply Recommendations 15
10 Layout 15
10.1 Layout Guidelines 15
10.2 Layout Example 15
11 Device and Documentation Support 16
11.1 接收文档更新通知 16
11.2 支持资源 16
11.3 Trademarks 16
11.4 Electrostatic Discharge Caution 16
11.5 术语表 16
12 Mechanical, Packaging, and Orderable Information 17

4 Revision History

注：以前版本的页码可能与当前版本的页码不同

Changes from Revision * (October 2021) to Revision A (December 2021)	Page
• 将数据表状态从“预告信息”更改为“量产数据”	1

Copyright © 2022 Texas Instruments Incorporated

5 Pin Configuration and Functions




图 5-1. TPS22998 RYZ Package, 10-Pin WQFN (Top View)

表 5-1. Pin Functions

PIN		I/O(1)	DESCRIPTION
NAME	NO.		
VBIAS	1	I	Device bias supply
VIN	2, 3, 4	I	Switch input
GND	5	G	Device ground
VOUT	6, 7, 8	O	Switch output
CT	9	I	Slew rate control – can be pulled up, left floating, or tie to ground
ON	10	I	Enable pin

(1) I = Input, O = Output, I/O = Input or Output, G = Ground, P = Power.

Copyright © 2022 Texas Instruments Incorporated

6 Specifications

6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)(1)

		MIN	MAX	UNIT
V_{IN}	Input Voltage	–0.3	6	V
V_{BIAS}	Bias Voltage	–0.3	6	V
V_{ON}, VCT	Control Pin Voltage	–0.3	6	V
I_{MAX}	Maximum Current		10	A
T_J	Junction temperature		Internally Limited	°C
T_{stg}	Storage temperature	–65	150	°C

(1) Operation outside the Absolute Maximum Ratings may cause permanent device damage. Absolute Maximum Ratings do not imply functional operation of the device at these or any other conditions beyond those listed under Recommended Operating Conditions. If used outside the Recommended Operating Conditions but within the Absolute Maximum Ratings, the device may not be fully functional, and this may affect device reliability, functionality, performance, and shorten the device lifetime.

6.2 ESD Ratings

			VALUE	UNIT
$V_{(ESD)}$	Electrostatic discharge	Human body model (HBM), per ANSI/ESDA/JEDEC JS-001(1)	±2000	V
		Charged device model (CDM), per ANSI/ESDA/JEDEC JS-002(2)	±1000	

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

6.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

		MIN	NOM	MAX	UNIT
V_{IN}	Input Voltage	0.2		5.5	V
V_{BIAS}	Bias Voltage	2.2		5.5	V
V_{CT}	Control Pin Voltage	0		5.5	V
T_A	Ambient Temperature	–40		105	°C

6.4 Thermal Information

THERMAL METRIC (1)		TPS22998 RYZ (WQFN) 10 PINS	UNIT
$R_{\theta JA}$	Junction-to-ambient thermal resistance	84.1	°C/W
$R_{\theta JC(top)}$	Junction-to-case (top) thermal resistance	77.5	°C/W
$R_{\theta JB}$	Junction-to-board thermal resistance	16.6	°C/W
Ψ_{JT}	Junction-to-top characterization parameter	4.0	°C/W
Y_{JB}	Junction-to-board characterization parameter	16.0	°C/W

(1) For more information about traditional and new thermal metrics, see the Semiconductor and IC Package Thermal Metrics application report.

Copyright © 2022 Texas Instruments Incorporated

6.5 Electrical Characteristics (VBIAS = 5 V)

Over operating free-air temperature range (unless otherwise noted). Typical values are at T_A = 25°C.

PARAMETER		TEST CONDITIONS	T_A	MIN	TYP	MAX	UNIT
Power Consumption							
$I_{SD,VBIAS}$	VBIAS Shutdown Current	ON = 0 V	25°C		3		uA
			– 40°C to 85°C			5	uA
			– 40°C to 105°C			6	uA
$I_{Q,VBIAS}$	VBIAS Quiescent Current	ON > V_{IH}	25°C		15		uA
			– 40°C to 85°C			20	uA
			– 40°C to 105°C			20	uA
$I_{SD,VIN}$	VIN Shutdown Current	ON = 0 V	25°C		0.1		uA
			– 40°C to 85°C			1	uA
			– 40°C to 105°C			2	uA
I_{ON}	ON pin leakage	ON = VBIAS	– 40°C to 105°C		0.1		uA
Performance							
R_{ON}	On-Resistance	VIN = 0.2 V to 5 V	25°C		4		mΩ
			– 40°C to 85°C			6	mΩ
			– 40°C to 105°C			7	mΩ
V_{IH}	Turn on threshold, rising		– 40°C to 105°C	0.765	0.9	1.035	V
V_{IL}	Turn off threshold, falling		– 40°C to 105°C	0.595	0.7	0.805	V
$V_{ON,HYST}$	ON pin hysteresis		– 40°C to 105°C		0.2		V
$t_{ON,DEGLITCH}$	On pin deglitch time		– 40°C to 105°C	2	5	7	us
R_{QOD}	QOD Resistance	VOUT = VIN	25°C		50		Ω
			– 40°C to 105°C	40		60	Ω
Protection							
TSD	Thermal Shutdown		-	130	150	180	°C
TSD_{HYS}	Thermal Shutdown Hysteresis		-		20		°C

6.6 Electrical Characteristics (VBIAS = 3.3 V)

Over operating free-air temperature range (unless otherwise noted). Typical values are at T_A = 25°C.

PARAMETER		TEST CONDITIONS	T_A	MIN	TYP	MAX	UNIT
Power Consumption							
$I_{SD,VBIAS}$	VBIAS Shutdown Current	ON = 0 V	25°C		3		uA
			– 40°C to 85°C			5	uA
			– 40°C to 105°C			5	uA
$I_{Q,VBIAS}$	VBIAS Quiescent Current	ON > V_{IH}	25°C		15		uA
			– 40°C to 85°C			20	uA
			– 40°C to 105°C			20	uA
$I_{SD,VIN}$	VIN Shutdown Current	ON = 0 V	25°C		0.1		uA
			– 40°C to 85°C			1	uA
			– 40°C to 105°C			3	uA
I_{ON}	ON pin leakage	ON = VBIAS	– 40°C to 105°C		0.1	1	uA
Performance							

6.6 Electrical Characteristics (VBIAS = 3.3 V) (continued)

Over operating free-air temperature range (unless otherwise noted). Typical values are at T_A = 25°C.

PARAMETER		TEST CONDITIONS	T_A	MIN	TYP	MAX	UNIT
R_{ON}	On-Resistance	VIN = 0.2 V to 3.3 V	25°C		4		mΩ
			–40°C to 85°C			7	mΩ
			–40°C to 105°C			7	mΩ
V_{IH}	ON pin turn on threshold, rising		–40°C to 105°C	0.765	0.9	1.035	V
V_{IL}	ON pin turn off threshold, falling		–40°C to 105°C	0.595	0.7	0.805	V
$V_{ON,HYST}$	ON pin hysteresis		–40°C to 105°C		0.2		V
$t_{ON,DEGLITCH}$	On pin deglitch time		–40°C to 105°C	2	5	6.5	us
R_{QOD}	QOD Resistance	VOUT = VIN	25°C		50		Ω
			–40°C to 105°C	40		60	Ω
Protection							
TSD	Thermal Shutdown		-	130	150	180	°C
TSD_{HYS}	Thermal Shutdown Hysteresis		-		20		°C

6.7 Electrical Characteristics (VBIAS = 2.2 V)

Over operating free-air temperature range (unless otherwise noted). Typical values are at T_A = 25°C.

PARAMETER		TEST CONDITIONS	T_A	MIN	TYP	MAX	UNIT
Power Consumption							
$I_{SD,VBIAS}$	VBIAS Shutdown Current	ON = 0 V	25°C		3		uA
			–40°C to 85°C			5	uA
			–40°C to 105°C			5	uA
$I_{Q,VBIAS}$	VBIAS Quiescent Current	ON > V_{IH}	25°C		15		uA
			–40°C to 85°C			20	uA
			–40°C to 105°C			20	uA
$I_{SD,VIN}$	VIN Shutdown Current	ON = 0 V	25°C		0.1		uA
			–40°C to 85°C			1	uA
			–40°C to 105°C			3	uA
I_{ON}	ON pin leakage	ON = VBIAS	–40°C to 105°C		0.1	1	uA
Performance							
R_{ON}	On-Resistance	VIN = 0.2 V to 2.2 V	25°C		4.3		mΩ
			–40°C to 85°C			7	mΩ
			–40°C to 105°C			7	mΩ
V_{IH}	ON pin turn on threshold, rising		–40°C to 105°C	0.765	0.9	1.035	V
V_{IL}	ON pin turn off threshold, falling		–40°C to 105°C	0.595	0.7	0.805	V
$V_{ON,HYST}$	ON pin hysteresis		–40°C to 105°C		0.2		V
$t_{ON,DEGLITCH}$	On pin deglitch time		–40°C to 105°C	2	4.5	6.5	us
R_{QOD}	QOD Resistance	VOUT = VIN	25°C		50		Ω
			–40°C to 105°C	40		60	Ω
Protection							
TSD	Thermal Shutdown		-	130	150	180	°C

Copyright © 2022 Texas Instruments Incorporated

Over operating free-air temperature range (unless otherwise noted). Typical values are at T_A = 25°C.

PARAMETER		TEST CONDITIONS	T_A	MIN	TYP	MAX	UNIT
TSD_{HYS}	Thermal Shutdown Hysteresis		-		20		°C

6.8 Switching Characteristics (VBIAS = 2.2 V to 5 V)

Over operating free-air temperature range (unless otherwise noted), CIN=47uF. Typical values are at T_A = 25°C, C_L = 0.1 μF, and a current load of 1mA.

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
VIN = 5 V						
t_{ON}	Turn ON time	CT = Open		250		us
t_{ON}	Turn ON time	CT = V_{BIAS}		1870		us
t_{ON}	Turn ON time	CT = GND		3728		us
t_{RISE}	Rise time	CT = Open		225		us
t_{RISE}	Rise time	CT = V_{BIAS}		1838		us
t_{RISE}	Rise time	CT = GND		3697		us
t_D	Delay time	CT = Open		26		us
t_D	Delay time	CT = V_{BIAS}		31		us
t_D	Delay time	CT = GND		31		us
t_{FALL}	Fall time	CT = Open		11		us
t_{OFF}	Turn OFF time	CT = Open		3		us
VIN = 3.3 V						
t_{ON}	Turn ON time	CT = Open		175		us
t_{ON}	Turn ON time	CT = V_{BIAS}		1261		us
t_{ON}	Turn ON time	CT = GND		3586		us
t_{RISE}	Rise time	CT = Open		150		us
t_{RISE}	Rise time	CT = V_{BIAS}		1232		us
t_{RISE}	Rise time	CT = GND		2478		us
t_D	Delay time	CT = Open		26		us
t_D	Delay time	CT = V_{BIAS}		29		us
t_D	Delay time	CT = GND		29		us
t_{FALL}	Fall time	CT = Open		11		us
t_{OFF}	Turn OFF time	CT = Open		3		us
VIN = 1.8 V						
t_{ON}	Turn ON time	CT = Open		102		us
t_{ON}	Turn ON time	CT = V_{BIAS}		664		us
t_{ON}	Turn ON time	CT = GND		1302		us
t_{RISE}	Rise time	CT = Open		75		us
t_{RISE}	Rise time	CT = V_{BIAS}		634		us
t_{RISE}	Rise time	CT = GND		1272		us
t_D	Delay time	CT = Open		27		us
t_D	Delay time	CT = V_{BIAS}		29		us
t_D	Delay time	CT = GND		30		us
t_{FALL}	Fall time	CT = Open		11		us
t_{OFF}	Turn OFF time	CT = Open		3		us
VIN = 0.6 V						
t_{ON}	Turn ON time	CT = Open		51		us
t_{ON}	Turn ON time	CT = V_{BIAS}		213		us

Copyright © 2022 Texas Instruments Incorporated

6.8 Switching Characteristics (VBIAS = 2.2 V to 5 V) (continued)

Over operating free-air temperature range (unless otherwise noted), CIN=47uF. Typical values are at T_A = 25°C, C_L = 0.1 μ F, and a current load of 1mA.

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
t_{ON}	Turn ON time	CT = GND		393		us
t_{RISE}	Rise time	CT = Open		23		us
t_{RISE}	Rise time	CT = V_{BIAS}		183		us
t_{RISE}	Rise time	CT = GND		365		us
t_D	Delay time	CT = Open		27		us
t_D	Delay time	CT = V_{BIAS}		29		us
t_D	Delay time	CT = GND		29		us
t_{FALL}	Fall time	CT = Open		10		us
t_{OFF}	Turn OFF time	CT = Open		4		us
VIN = 0.285 V						
t_{ON}	Turn ON time	CT = Open		37		us
t_{ON}	Turn ON time	CT = V_{BIAS}		96		us
t_{ON}	Turn ON time	CT = GND		158		us
t_{RISE}	Rise time	CT = Open		11		us
t_{RISE}	Rise time	CT = V_{BIAS}		66		us
t_{RISE}	Rise time	CT = GND		128		us
t_D	Delay time	CT = Open		27		us
t_D	Delay time	CT = V_{BIAS}		29		us
t_D	Delay time	CT = GND		30		us
t_{FALL}	Fall time	CT = Open		9		us
t_{OFF}	Turn OFF time	CT = Open		4		us

6.9 Timing Diagram





图 6-1. TPS22998 Timing Diagram


Copyright © 2022 Texas Instruments Incorporated

6.10 Typical Characteristics




VBIAS = 5 V VOUT = Open

图 6-2. Quiescent Current vs Input Voltage




VIN = VBIAS VOUT = Open

图 6-3. Quiescent Current vs Bias Voltage




VBIAS = 5 V VOUT = 0 V

图 6-4. VBIAS Shutdown Current vs Input Voltage




VIN = VBIAS VOUT = 0 V

图 6-5. VBIAS Shutdown Current vs Bias Voltage



VBIAS = 5 V I_{LOAD} = 200 mA

图 6-6. On-Resistance vs Input Voltage




VIN = VBIAS

图 6-7. QOD Resistance vs Bias Voltage


Copyright © 2022 Texas Instruments Incorporated

6.10 Typical Characteristics (continued)




VBIAS = 5 V C_L = 0.1 µF CT = Floating

图 6-8. Rise Time vs Input Voltage




VBIAS = 5 V C_L = 0.1 µF CT = Floating

图 6-9. Delay Time vs Input Voltage




VBIAS = 5 V C_L = 0.1 µF CT = Floating

图 6-10. Turn-On Time vs Input Voltage



VBIAS = 5 V C_L = 0.1 µF CT = Floating

图 6-11. Fall Time vs Input Voltage



VBIAS = 5 V C_L = 0.1 µF CT = Floating

图 6-12. Off Time vs Input Voltage

Copyright © 2022 Texas Instruments Incorporated


7 Detailed Description

7.1 Overview

The TPS22998 device is a single-channel load switch with a 4-mΩ power MOSFET designed to operate up to 10 A. The voltage range is 0.2 V to 5.5 V. A configurable rise time provides flexibility for power sequencing and minimizes inrush current for high capacitance loads.

An enable pin (ON) controls the switch, which is capable of interfacing directly with low voltage GPIO signals. The TPS22998 device uses quick output discharge when switch turns off, pulling the output down to 0 V through an internal 50-Ω resistor.

7.2 Functional Block Diagram



7.3 Feature Description

7.3.1 ON and OFF Control

The ON pin controls the state of the switch. The ON pin is compatible with standard GPIO logic threshold so it can be used in a wide variety of applications. When the pin pull high, the device enables, and when it is low, the device disables.

7.3.2 Adjustable Slew Rate

The CT pin is a tri-state pin, meaning that it has three different slew rates depending on the connection to the pin. The CT pin can be grounded, pulled high, or left floating. Floating defines as an effective resistance to GND or other pins greater than 10 MΩ.

Copyright © 2022 Texas Instruments Incorporated

7.3.3 Thermal Shutdown

When the device temperature reaches 150°C (typical), the device shuts itself off to prevent thermal damage. After it cools off by about 20°C, the device turns back on. If the device is kept in a thermally stressful environment, then the device oscillates between these two states until it can keep its temperature below the thermal shutdown point.

7.4 Device Functional Modes

The below table summarizes the device functional modes:

ON	Fault Condition	VOUT State
L	None	QOD to GND
H	None	Connected to VIN
H	Thermal shutdown	QOD to GND

Copyright © 2022 Texas Instruments Incorporated

8 Application and Implementation

备注

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI’s customers are responsible for determining suitability of components for their purposes, as well as validating and testing their design implementation to confirm system functionality.

8.1 Application Information

This section highlights some of the design considerations when implementing this device in various applications.

8.2 Typical Application

This typical application demonstrates how to use the TPS22998 device to limit startup inrush current.




图 8-1. TPS22998 Basic Application

8.2.1 Design Requirements

For this example, the values below are used as the design parameters.

表 8-1. Design Parameters

PARAMETER	VALUE
V_{BIAS}	3.3 V
V_{IN}	1.8 V
Load capacitance	470 µF
Maximum inrush current	1 A

Copyright © 2022 Texas Instruments Incorporated

8.2.2 Detailed Design Procedure

When the switch enables, the charge up the output capacitance from 0 V to the set value (1.8 V in this example). This charge arrives in the form of inrush current. Calculate inrush current using 方程式 1.

$$\text{Inrush Current} = C_L \times dVOUT/dt \quad (1)$$

Where:

- C_L is the output capacitance.
- dVOUT is the change in VOUT during the ramp up of the output voltage when device is enabled. Because rise time is 10% of VOUT to 90% of VOUT, this is 80% of the VIN value.
- dt is the rise time in VOUT during the ramp up of the output voltage when the device is enabled.

The TPS22998 offers an adjustable rise time for VOUT, allowing the user to control the inrush current during turn on. Calculate the appropriate rise time using the design requirements and the inrush current equation as shown below.

$$1A = 470\ \mu F \times (1.8\ V \times 80\%) / dt \quad (2)$$

$$dt = 677\mu s \quad (3)$$

To ensure an inrush current of less than 1 A, a C_T setting that yields a rise time of more than 677 µs must be chosen. By pulling the CT pin high, a rise time of 900 µs is selected, limiting the inrush current to below 1 A.

8.2.3 Application Performance Plots

The below scope shot shows the TPS22998 turning on into a 470- µF load with the CT pin tied to VBIAS.




图 8-2. TPS22998 Turn-On into 470 µF (CT = V_{BIAS})

Copyright © 2022 Texas Instruments Incorporated

9 Power Supply Recommendations

The TPS22998 device is designed to operate with a VIN range of 0.2 V to 5.5 V. Regulate the VIN power supply well and place as close to the device terminal as possible. The power supply must be able to withstand all transient load current steps. In most situations, using an input capacitance (C_{IN}) of 1 μF is sufficient to prevent the supply voltage from dipping when the switch is turned on. In cases where the power supply is slow to respond to a large transient current or large load current step, additional bulk capacitance can be required on the input.

10 Layout

10.1 Layout Guidelines

For best performance, all traces must be as short as possible. To be most effective, place the input and output capacitors close to the device to minimize the effects that parasitic trace inductances can have on normal operation. Using wide traces for VIN, VOUT, and GND helps minimize the parasitic electrical effects.

10.2 Layout Example




图 10-1. TPS22998 Layout Example

11 Device and Documentation Support

TI offers an extensive line of development tools. Tools and software to evaluate the performance of the device, generate code, and develop solutions are listed below.

11.1 接收文档更新通知

要接收文档更新通知，请导航至 ti.com 上的器件产品文件夹。点击 *订阅更新* 进行注册，即可每周接收产品信息更改摘要。有关更改的详细信息，请查看任何已修订文档中包含的修订历史记录。

11.2 支持资源

TI E2E™ 支持论坛是工程师的重要参考资料，可直接从专家获得快速、经过验证的解答和设计帮助。搜索现有解答或提出自己的问题可获得所需的快速设计帮助。

链接的内容由各个贡献者“按原样”提供。这些内容并不构成 TI 技术规范，并且不一定反映 TI 的观点；请参阅 TI 的《使用条款》。

11.3 Trademarks

TI E2E™ is a trademark of Texas Instruments.
所有商标均为其各自所有者的财产。

11.4 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

11.5 术语表

TI 术语表	本术语表列出并解释了术语、首字母缩略词和定义。

Copyright © 2022 Texas Instruments Incorporated

12 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

Copyright © 2022 Texas Instruments Incorporated

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package | Pins	Package qty | Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
TPS22998RYZR	Active	Production	WQFN-HR (RYZ) | 10	3000 | LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	-40 to 105	1LF
TPS22998RYZR.A	Active	Production	WQFN-HR (RYZ) | 10	3000 | LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	-40 to 105	1LF

(1) **Status:** For more details on status, see our product life cycle.

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.


In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

PACKAGE OUTLINE

RYZ0010A


WQFN-HR - 0.8 mm max height

PLASTIC QUAD FLATPACK - NO LEAD




NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.



LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE:30X




SOLDER MASK DETAILS
NOT TO SCALE

4226834/B 06/2021

NOTES: (continued)

3. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/slua271).



SOLDER PASTE EXAMPLE
BASED ON 0.1 mm THICKNESS
SCALE: 30X

4226834/B 06/2021

NOTES: (continued)

5. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

重要通知和免责声明

TI“按原样”提供技术和可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证没有瑕疵且不做出任何明示或暗示的担保，包括但不限于对适销性、与某特定用途的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任：(1) 针对您的应用选择合适的 TI 产品，(2) 设计、验证并测试您的应用，(3) 确保您的应用满足相应标准以及任何其他安全、安保法规或其他要求。

这些资源如有变更，恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的相关应用。严禁以其他方式对这些资源进行复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。对于因您对这些资源的使用而对 TI 及其代表造成的任何索赔、损害、成本、损失和债务，您将全额赔偿，TI 对此概不负责。

TI 提供的产品受 TI 销售条款)、TI 通用质量指南 或 ti.com 上其他适用条款或 TI 产品随附的其他适用条款的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。 除非德州仪器 (TI) 明确将某产品指定为定制产品或客户特定产品，否则其产品均为按确定价格收入目录的标准通用器件。

TI 反对并拒绝您可能提出的任何其他或不同的条款。

版权所有 © 2025，德州仪器 (TI) 公司

最后更新日期：2025 年 10 月