
TPS62901-Q1 3V 至 18V、1A、汽车类、低 I_Q 降压转换器，且+165°C

1 特性

- 符合面向汽车应用的 AEC-Q100 标准：
  - 温度等级 1：–40°C 至 +125°C，T_A
  - 器件 HBM ESD 分类等级 2
  - CDM ESD 分级等级 C4B
- 提供功能安全
  - 可提供用于功能安全系统设计的文档
- 扩展 T_J 范围：至高达 165°C
- 高效率 DCS-Control 拓扑
  - $R_{DS(ON)}$：62mΩ 高侧，22mΩ 低侧
  - 无缝 PWM/PFM 转换
  - 内部补偿
- 4μA 低 I_Q（典型值）
- 高达 1A 的持续输出电流
- 整个温度范围内的输出电压精度为 ±1.5%
- 可配置的输出电压选项：
  - 0.6V 至 5.5V V_{FB} 外部分压器
  - V_{SET} 内部分压器
    - 16 个电压选项（0.4V 至 5.5V）
- 通过 MODE/S-CONF 引脚提高了灵活性
  - 2.5 MHz 或 1.0 MHz 开关频率
  - 具有动态模式更改选项的强制 PWM 或自动 PFM（省电模式）
  - 输出放电开和关
- 无需外部自举电容器
- 过流和过热保护
- 100% 占空比模式
- 精密使能输入
- 可调软启动和跟踪
- 电源正常状态输出
- 针对单层布线的引脚排列进行了优化
- 可湿性 2.2mm × 2.0mm VQFN 封装，间距为 0.5mm
- 借助 TPS62901-Q1 并使用 WEBENCH® Power Designer 创建定制设计方案



简化原理图

2 应用

- ADAS
- 车身电子装置和照明
- 信息娱乐系统与仪表组
- 混合动力、电动和动力总成系统

3 说明

TPS62901-Q1 是一款高效、小巧、灵活且易用的同步直流/直流降压转换器。2.5MHz 或 1.0MHz 的可选开关频率支持使用小型电感器，并提供快速瞬态响应。该器件在整个运行温度范围内支持 ±1.5% 的高 V_{OUT} 精度，并通过 DCS-Control 拓扑提高负载瞬态性能。3V 至 18V 的宽输入电压范围支持各种标称输入，例如 12V 电源轨、单节或多节锂离子电池、5V 或 3.3V 电源轨。


TPS62901-Q1 可在轻负载时自动进入省电模式（如果选择了自动 PFM 或 PWM）以保持高效率。此外，为了在非常小的负载下提供高效率，该器件具有 4μA 的低典型静态电流。AEE（如果启用）可在 V_{IN}、V_{OUT} 和负载电流范围内提供高效率。该器件包含一个 MODE/Smart-CONF 输入，用来设置内部和外部分压器、开关频率、输出电压放电和自动省电模式或强制 PWM 操作。

封装信息

器件型号	封装(1)	封装尺寸(2)
TPS62901-Q1	RYT (VQFN, 9)	2.20mm × 2.00mm

(1) 如需了解所有可用封装，请参阅数据表末尾的可订购产品附录。

(2) 封装尺寸（长 × 宽）为标称值，并包括引脚（如适用）。



效率与输出电流间的关系（3.3 V_O，2.5MHz，1μH，自动 PFM 或 PWM）

本文档旨在为方便起见，提供有关 TI 产品中文版本的信息，以确认产品的概要。有关适用的官方英文版本的最新信息，请访问 www.ti.com，其内容始终优先。TI 不保证翻译的准确性和有效性。在实际设计之前，请务必参考最新版本的英文版本。

Table of Contents

1 特性 ... 1
2 应用 ... 1
3 说明 ... 1
4 Revision History ... 2
5 Device Comparison Table ... 3
6 Pin Configuration and Functions ... 4
7 Specifications ... 5
7.1 Absolute Maximum Ratings ... 5
7.2 ESD Ratings ... 5
7.3 Recommended Operating Conditions ... 5
7.4 Thermal Information ... 5
7.5 Electrical Characteristics ... 6
7.6 Typical Characteristics ... 8
8 Detailed Description ... 12
8.1 Overview ... 12
8.2 Functional Block Diagram ... 12
8.3 Feature Description ... 13
8.4 Device Functional Modes ... 21
9 Application and Implementation ... 23
9.1 Application Information ... 23
9.2 Typical Application with Adjustable Output Voltage ... 23
9.3 Typical Application with Selectable V_{OUT} using VSET ... 34
9.4 System Examples ... 39
9.5 Power Supply Recommendations ... 43
9.6 Layout ... 43
10 Device and Documentation Support ... 45
10.1 Device Support ... 45
10.2 Documentation Support ... 45
10.3 接收文档更新通知 ... 45
10.4 支持资源 ... 45
10.5 Trademarks ... 45
10.6 静电放电警告 ... 46
10.7 术语表 ... 46
11 Mechanical, Packaging, and Orderable Information ... 46

4 Revision History

DATE	REVISION	NOTES
June 2023	*	Initial release

Copyright © 2023 Texas Instruments Incorporated

5 Device Comparison Table

Device Number	Output Current	Input Voltage	Operating Temperature Range	Switching Frequency	PWM Mode	V_O Adjust
TPS62903-Q1	0 A – 3 A	3 V – 18 V	–40°C to 165°C	Selectable 1-MHz or 2.5-MHz options	Selectable auto PFM/PWM or forced PWM	Externally programmable or 16 internal options
TPS62902-Q1	0 A – 2 A					
TPS62901-Q1	0 A – 1 A					
TPS62903	0 A – 0.3 A	3 V – 18 V	–40°C to 125°C	Selectable 1-MHz or 2.5-MHz options	Selectable auto PFM/PWM or forced PWM	Externally programmable or 16 internal options
TPS62902	0 A – 2 A					
TPS62901	0 A – 1 A					

Copyright © 2023 Texas Instruments Incorporated

6 Pin Configuration and Functions




图 6-1. 9-Pin RYT VQFN Package (Top View, Device Pins Face Down)

表 6-1. Pin Functions

Pin		Type(1)	Description
Name	Number		
PG	1	O	Open-drain power-good output. High = V_{OUT} is ready. Low = V_{OUT} is below nominal regulation. This pin requires a pullup resistor.
SW	2	—	Switch pin of the converter and is connected to the internal power switches. Connect the inductor between SW and the output capacitor.
VOS	3	I	Output voltage sense pin. Connect directly to the positive pin of the output capacitor.
GND	4	—	Ground pin. This pin must be connected directly to the common ground plane.
EN	5	I	Enable input pin. Connect to logic low to disable the device. Pull high to enable the device. Do not leave this pin unconnected.
VIN	6	I	Power supply input pin. Ensure the input capacitor is connected as close as possible between the VIN and GND pins.
MODE/ S-CONF	7	I	Device mode selection (auto PFM/PWM or forced PWM operation) and SmartConfig pin. Connect high, low, or to a resistor to configure the device according to 表 8-1. Do not leave this pin unconnected.
SS/TR	8	I	Soft start and tracking pin. An external capacitor connected from this pin to GND defines the rise time for the internal reference voltage. The pin can also be used as an input for tracking and sequencing. The pin can be left floating for the fastest ramp-up time.
FB/VSET	9	I	Depends on device configuration (see 节 8.3.1.) • FB: Voltage feedback input. Connect a resistive output voltage divider to this pin. • VSET: Output voltage setting pin. Connect a resistor to GND to choose the output voltage according to 表 8-2.

(1) O = output, I = input

Copyright © 2023 Texas Instruments Incorporated

7 Specifications

7.1 Absolute Maximum Ratings

over operating temperature range (unless otherwise noted)(1)

		MIN	MAX	UNIT
Voltage(2)	VIN, EN, PG, MODE/S-CONF	–0.3	19.5	V
Voltage(2)	SW (3)	–0.3	V_{IN} + 0.3	V
Voltage(2)	SW (AC, less than 10ns)(3)	–3.0	23	V
Voltage(2)	FB/VSET, SS/TR, VOS	–0.3	6	V
T_J	Junction temperature	–55	165	°C
T_{stg}	Storage temperature	–65	165	°C

(1) Operation outside the Absolute Maximum Ratings may cause permanent device damage. Absolute Maximum Ratings do not imply functional operation of the device at these or any other conditions beyond those listed under Recommended Operating Conditions. If used outside the Recommended Operating Conditions but within the Absolute Maximum Ratings, the device may not be fully functional, and this may affect device reliability, functionality, performance, and shorten the device lifetime.
(2) All voltage values are with respect to network ground terminal.
(3) While switching.

7.2 ESD Ratings

				VALUE	UNIT
$V_{(ESD)}$	Electrostatic discharge	Human body model (HBM), per AEC-Q100-002 HBM ESD Classification Level 2, all pins(1)		±2000	V
$V_{(ESD)}$	Electrostatic discharge	Charged device model (CDM), per AEC-Q100-011 CDM ESD Classification level C4B.	All pins	±500	V
			Corner pins (3, 4, 7, and 9)	±750	

(1) AEC Q100-002 indicates HBM stressing is done in accordance with the ANSI/ESDA/JEDEC JS-001 specification.

7.3 Recommended Operating Conditions

Over operating junction temperature range (unless otherwise noted)

		MIN	NOM	MAX	UNIT
V_I	Input voltage range	3.0		18	V
V_O	Output voltage range	0.4		5.5	V
C_I	Effective input capacitance	3	10		µF
C_O	Effective output capacitance (2.5MHz selection)(1)	10	22	100 (1)	µF
C_O	Effective output capacitance (1MHz selection)(1)	10	22	100 (1)	µF
L	Output inductance(2)	1	2.2	4.7(3)	µH
I_{OUT}	Output current	0		1	A
I_{SINK_PG}	Sink current at PG-Pin			1	mA
T_J	Junction temperature (4)	–40		165	°C

(1) This is for capacitors directly at the output of the device. More capacitance is allowed if there is a series resistance associated to the capacitor.
(2) Nominal inductance value.
(3) Larger values of inductance can be used to reduce the ripple current, but larger values of inductance can have a negative impact on efficiency and the overall transient response.
(4) Operating lifetime is derated at junction temperatures greater than 165°C.

7.4 Thermal Information

THERMAL METRIC(1)		VQFN (RYT)		UNIT
		JEDEC PCB	TPS6290xEVM-xxx	
$R_{\theta JA}$	Junction-to-ambient thermal resistance	97.2	73.5	°C/W

Copyright © 2023 Texas Instruments Incorporated

7.4 Thermal Information (continued)

THERMAL METRIC(1)		VQFN (RYT)		UNIT
		JEDEC PCB	TPS6290xEVM-xxx	
$R_{\theta JC(top)}$	Junction-to-case (top) thermal resistance	74.4	N/A	°C/W
$R_{\theta JB}$	Junction-to-board thermal resistance	25	N/A	°C/W
Ψ_{JT}	Junction-to-top characterization parameter	2.7	4.3	°C/W
Ψ_{JB}	Junction-to-board characterization parameter	24.7	28	°C/W

(1) For more information about traditional and new thermal metrics, see the Semiconductor and IC Package Thermal Metrics application report.

7.5 Electrical Characteristics

V_I = 3 V to 18 V, T_J = -40C °C to +165°C, Typical values at V_I = 12 V and T_A = 25 °C unless otherwise noted

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
SUPPLY						
I_Q	Operating Quiescent Current (Power Save Mode)	Iout = 0 mA device not switching		4		µA
$I_{Q;PWM}$	Operating Quiescent Current (PWM Mode)	VIN= 12 V, VOUT = 1.2 V; Iout = 0 mA, device switching		8		mA
I_{SD}	Shutdown current into VIN pin	EN = 0 V, T_J = –40 °C to 150°C		0.27	3.5	µA
V_{UVLO}	Undervoltage Lockout	V_{IN} rising, T_J = –40 °C to 150°C	2.85	2.925	3.0	V
	Undervoltage lockout	V_{IN} falling	2.71	2.79	2.87	V
V_{UVLO}	Undervoltage lockout hysteresis			130		mV
CONTROL & INTERFACE						
I_{LKG}	EN input leakage current	EN = 5 V		10	310	nA
$V_{IH;MODE}$	High-level input voltage at MODE/S-CONF Pin		1.0			V
$V_{IL;MODE}$	Low-level input voltage at MODE/S-CONF Pin				0.15	V
T_{SD}	Thermal shutdown threshold	T_J rising	168	175	185	°C
	Thermal shutdown hysteresis	T_J falling		12.5		
V_{IH}	High-level input voltage at EN-Pin		0.97	1.0	1.03	V
V_{IL}	Low-level input voltage at EN-Pin		0.820	0.850	0.880	V
V_{PG}	Power-good threshold	V_{FB} rising, referenced to V_{FB} nominal	93%	96%	99%	
		V_{FB} falling, referenced to V_{FB} nominal	88%	92%	96%	
V_{PG_HYS}	Power-good threshold hysteresis		1.5%	3.5%	6%	
$V_{PG,OL}$	Low-level output voltage at PG pin	I_{SINK} = 1 mA			0.4	V
$I_{PG,LKG}$	Input leakage current into PG pin	V_{PG} = 5 V, T_J = –40 °C to 150 °C		25	550	nA
$t_{PG,DLY}$	Power-good delay time	V_{FB} rising and falling		32		µs
C_{SET}	Maximum capacitance connected to VSET pin				30	pF
POWER SWITCHES						
$I_{LKG;SW}$	Leakage current into SW-Pin	EN = 0 V, V_{SW} = V_{OS} = 5.5 V, T_J up to 150°C		2	7	µA
$R_{DS;ON}$	High-side FET on resistance	V_{IN} > 4 V, I_{SW} = 500 mA		62	111	mΩ
	Low-side FET on resistance	V_{IN} > 4 V, I_{SW} = 500 mA		22	41	
I_{LIM}	High-side FET current limit		1.8	2.2	2.8	A
	Low-side FET current limit		1.6	2	2.4	A
$I_{LIM;SINK}$	Low-side FET sink current limit		1.3	1.7	2.5	A

Copyright © 2023 Texas Instruments Incorporated


7.5 Electrical Characteristics (continued)

V_I = 3 V to 18 V, T_J = -40C °C to +165°C, Typical values at V_I = 12 V and T_A = 25 °C unless otherwise noted

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
f_{SW}	Switching frequency	2.5-MHz selection		2.5		MHz
$T_{ON(MIN)}$	Minimum On-time			30		ns
f_{SW}	Switching frequency	1.0-MHz selection		1.0		MHz
OUTPUT						
V_O	Output voltage regulation	VSET Configuration selected, T_J = 25°C	–1%		+1%	
V_O	Output voltage regulation	VSET Configuration selected	–1.5%		+1.5%	
V_{FB}	Feedback regulation voltage	Adjustable Configuration selected		0.6		V
V_{FB}	Feedback voltage regulation	FB-Option selected. T_J = 25°C.	–0.6%		+0.6%	
V_{FB}	Feedback voltage regulation	FB-Option selected	–1.25%		+1.25%	
I_{FB}	Input leakage current into FB pin	Adjustable configuration, VFB = 0.6 V		1	70	nA
T_{delay}	Start-up delay time	I_O = 0 mA, time from EN=HIGH until start switching, Adjustable Configuration selected		600	1400	µs
	Start-up delay time	I_O = 0 mA, time from EN=HIGH until start switching, VSET Configuration selected. The typical value is based on the first option of VSET configuration.		650	1850	µs
T_{SS}	Soft-start time	I_O = 0 mA after T_{delay}, from 1st switching pulse until target V_O, Css=Open		150		µs
I_{SS}	SS/TR source current		2.25	2.5	2.75	µA
$V_{FB}/V_{SS/TR}$	Tracking gain, adjustable configuration			0.75		
$V_{FB}/V_{SS/TR}$	Tracking gain tolerance			±8		mV
R_{DISCH}	Active discharge resistance	Discharge = ON - Option Selected, EN = LOW		7.5	30	Ω

Copyright © 2023 Texas Instruments Incorporated

7.6 Typical Characteristics



Measured with the device not switching

图 7-1. Quiescent Current vs Temperature




图 7-2. Shutdown Current vs Temperature






图 7-3. Feedback Voltage Accuracy - External Feedback Selected




V_{OUT} = 5.0 V

图 7-4. Output Voltage Accuracy - VSET Selected



V_{OUT} = 3.3 V

图 7-5. Output Voltage Accuracy - VSET Selected




V_{OUT} = 2.5 V

图 7-6. Output Voltage Accuracy - VSET Selected


Copyright © 2023 Texas Instruments Incorporated

7.6 Typical Characteristics (continued)




V_{OUT} = 1.8 V

图 7-7. Output Voltage Accuracy - VSET Selected



V_{OUT} = 1.2 V

图 7-8. Output Voltage Accuracy - VSET Selected



V_{OUT} = 0.6 V

图 7-9. Output Voltage Accuracy - VSET Selected






图 7-10. Tracking Voltage Gain vs Temperature



V_{OUT} = 1.2 V F_{SW} = 2.5 MHz FPWM I_{OUT} = 0 A

图 7-11. Switching Frequency vs Temperature



V_{OUT} = 1.2 V F_{SW} = 1.0 MHz FPWM I_{OUT} = 0 A

图 7-12. Switching Frequency vs Temperature

Copyright © 2023 Texas Instruments Incorporated

7.6 Typical Characteristics (continued)




图 7-13. High Side RDS_{ON} vs Temperature




图 7-14. Low Side RDS_{ON} vs Temperature




图 7-15. High Side I_{LIM} vs Temperature




图 7-16. Low Side I_{LIM} vs Temperature




图 7-17. Negative I_{LIM} vs Temperature




图 7-18. Soft Start Current vs Temperature

Copyright © 2023 Texas Instruments Incorporated

7.6 Typical Characteristics (continued)




图 7-19. Power Good Thresholds vs Temperature




图 7-20. V_{VIN} UVLO Thresholds vs Temperature




图 7-21. Percise EN Threshold vs Temperature





图 7-22. Percise EN Threshold vs Temperature

8 Detailed Description

8.1 Overview

The TPS62901-Q1 synchronous switched mode power converters are based on DCS-Control (Direct Control with Seamless Transition into power save mode). DCS-Control is an advanced regulation topology that combines the advantages of hysteretic, voltage mode, and current mode control. This control loop takes information about output voltage changes and feeds the information directly to a fast comparator stage. DCS-Control sets the switching frequency, which is constant for steady-state operating conditions, and provides immediate response to dynamic load changes. To get accurate DC load regulation, a voltage feedback loop is used. The internally compensated regulation network achieves fast and stable operation with small external components and low-ESR capacitors.

8.2 Functional Block Diagram



Copyright © 2023 Texas Instruments Incorporated

8.3 Feature Description

8.3.1 Mode Selection and Device Configuration MODE/S-CONF

With MODE/S-CONF (SmartConfig), this device features an input with two functions. This pin can be used to customize the device behavior in two ways:

- Select the device mode (Forced PWM or Auto PFM /PWM with AEE operation) with a HIGH-level or LOW-level.
- Select the device configuration (switching frequency, internal or external feedback, output discharge, and auto PFM/PWM mode) by connecting a single resistor to the MODE/S-CONF pin.

The TPS62901-Q1 interprets this pin during the start-up sequence after the internal OTP readout and before the device starts switching in soft start (see 图 8-1). If the device reads a HIGH-level or LOW-level, the dynamic mode change is active and auto PFM/PWM or FPWM mode can be changed during operation. If the TPS62901-Q1 reads a resistor value, the device is configured according to the resistance value in 表 8-1 and there is no further interpretation during operation and device mode or other configurations can only be changed by power cycling or disabling the device.

备注

The MODE/S-CONF pin must not be left floating. Connect the pin high, low, or to a resistor to configure the device according to 表 8-1.




图 8-1. Interpretation of S-CONF and VSET Flow

表 8-1. SmartConfig Setting Table

#	Level Or Resistor Value [Ω] (1)	FB/VSET Pin	F_{SW} (MHz)	Output Discharge	Mode (Auto Or Forced PWM)	Dynamic Mode Change
	Setting Options by Level					
1	GND	External FB	2.5(2)	yes	Auto PFM/PWM with AEE	Active
2	HIGH (> V_{IH_MODE})	External FB	2.5	yes	Forced PWM	
	Setting Options by Resistor					
3	7.15 k	External FB	2.5(2)	no	Auto PFM/PWM with AEE	Not active
4	8.87 k	External FB	2.5	no	Forced PWM	
5	11.0 k	External FB	1	yes	Auto PFM/PWM	
6	13.7 k	External FB	1	yes	Forced PWM	
7	16.9 k	External FB	1	no	Auto PFM/PWM	
8	21.0 k	External FB	1	no	Forced PWM	
9	26.1 k	VSET	2.5(2)	yes	Auto PFM/PWM with AEE	
10	32.4 k	VSET	2.5	yes	Forced PWM	
11	40.2 k	VSET	2.5(2)	no	Auto PFM/PWM with AEE	
12	49.9 k	VSET	2.5	no	Forced PWM	
13	61.9 k	VSET	1	yes	Auto PFM/PWM	
14	76.8 k	VSET	1	yes	Forced PWM	
15	95.3 k	VSET	1	no	Auto PFM/PWM	
16	118 k	VSET	1	no	Forced PWM	

(1) E96 resistor series, 1% accuracy, temperature coefficient better or equal than ±200 ppm/°C
(2) F_{SW} varies based on V_{IN} and V_{OUT}. See 节 8.4.3 for more details.

8.3.2 Adjustable V_O Operation (External Voltage Divider)

The TPS62901-Q1 can be programmed by the MODE/S-CONF pin to operating in a classical configuration where the FB/VSET pin is used as the feedback pin, sensing V_O through an external resistive divider. The TPS62901-Q1 can also be programmed to 1 of 16 different fixed output voltages (see 节 8.3.3).

If the device is configured to operate in the classical adjustable V_O operation, the FB/VSET pin is used as the feedback pin and must sense V_O through an external divider network. 图 8-2 shows the typical schematic for this configuration.




图 8-2. Adjustable V_O Operation Schematic

Copyright © 2023 Texas Instruments Incorporated

8.3.3 Selectable V_O Operation (VSET and Internal Voltage Divider)

If the device is configured to VSET operation, V_O is sensed only through the VOS pin by an internal resistor divider. The target V_O is programmed by an external resistor (R_{VSET}) connected between the VSET pin and GND. 图 8-3 shows the typical schematic for this configuration.

CAUTION

The MODE/S-CONF pin must not be configured for external feedback operation (see 表 8-1) if only R_{VSET} (R2 as shown in 图 8-3) is populated. This causes the output voltage to become unregulated and can damage to the device or surrounding circuitry.




图 8-3. Selectable V_O Operation Schematic

表 8-2. VSET Selection Table

#	Level Or Resistor Value [Ω] (1)	Target V_O [V]
1	GND	1.2
2	4.64 k	0.4
3	5.76 k	0.6
4	7.15 k	0.8
5	8.87 k	1.0
6	11.0 k	1.1
7	13.7 k	1.3
8	16.9 k	1.35
9	21.0 k	1.8
10	26.1 k	1.9
11	40.2 k	2.5
12	61.9 k	3.8
13	76.8 k	5.0
14	95.3 k	1.25
15	118.0 k	5.5
16	249.00 k or larger/Open	3.3

(1) E96 resistor series, 1% accuracy, temperature coefficient better or equal than ±200 ppm/°C

8.3.4 Soft Start and Tracking (SS/TR)

With the SS/TR pin, the user can adjust the soft-start behavior or track an external voltage source (see 节 8.3.4.1 for operation details).

Copyright © 2023 Texas Instruments Incorporated

The internal soft-start circuitry controls the output voltage slope during start-up. This avoids excessive inrush current and makes sure there is a controlled output voltage rise time. The soft-start circuitry also prevents unwanted voltage drops from high impedance power sources or batteries. When EN is set high to start operation, the device starts switching after the start-up delay, while the internal reference, and hence V_O, rises with a slope controlled by the 2.5µA (typical) I_{SS} current source and an external capacitor connected to the SS/TR pin and the 2.5µA (typical) I_{SS} current source.

备注

Shorting or pulling the SS/TR pin LOW externally prevents the device from switching as this sets the internal reference voltage to 0 V.

备注

Leaving the SS/TR pin unconnected provides the fastest start-up response, but this can result in some output voltage overshoot depending on the Vout value, load current, and external component sizes. Adding or increasing the soft-start capacitor (C_{SS}) minimizes or removes the voltage overshoot.

If the device is set to shut down (EN = GND), undervoltage lockout, or thermal shutdown, an internal resistor pulls the SS/TR pin down to make sure there is a proper low level. Returning from those states causes a new start-up sequence as set by the SS/TR connection.

8.3.4.1 Tracking Function

If a tracking function is desired, the SS/TR pin can be used for this purpose by connecting it to an external tracking voltage. The output voltage tracks that voltage with the typical gain and offset as specified in the *Electrical Characteristics*.

备注

In forced PWM (FPWM) mode the output voltage increases and decreases with any changes in the tracking voltage, but in auto PFM (power save) mode, the output voltage only decreases based on the load current.




图 8-4. Tracking Operation Simplified Schematic

$$V_{FB} = 0.75 \times V_{SS/TR} \quad (1)$$

When the SS/TR pin voltage is above 0.8 V, the internal voltage is clamped and the device goes to normal regulation. This action works for rising and falling tracking voltages with the same behavior, as long as the input voltage is inside the recommended operating conditions. For decreasing the SS/TR pin voltage in PFM mode, the device does not sink current from the output. The resulting decrease of the output voltage can therefore be slower than the SS/TR pin voltage if the load is light. When driving the SS/TR pin with an external voltage, do not exceed the voltage rating of the SS/TR pin, which is 6 V. The SS/TR pin is internally connected with a resistor to GND when EN = 0.

If the input voltage drops below undervoltage lockout, the output voltage goes to zero, independent of the tracking voltage. 图 8-5 shows how to connect devices to get ratiometric and simultaneous sequencing by using the tracking function. See 节 9.4.3 in the systems examples.

Copyright © 2023 Texas Instruments Incorporated




图 8-5. Schematic for Ratiometric and Simultaneous Start-Up

The resistive divider of R7 and R8 can be used to change the ramp rate of VOUT2 to be faster, slower, or the same as VOUT1.

A sequential start-up is achieved by connecting the PG pin of VOUT of device 1 to the EN pin of device 2. PG requires a pullup resistor. Ratiometric start-up sequence happens if both supplies are sharing the same soft-start capacitor. 方程式 18 gives the soft-start time, though the SS/TR current has to be doubled. Details about these and other tracking and sequencing circuits are found in the *Sequencing and Tracking With the TPS621-Family and TPS821-Family* application report.

备注

If the voltage at the FB pin is below its typical value of 0.6 V, the output voltage accuracy can have a wider tolerance than specified. The current of 2.5 µA out of the SS/TR pin also has an influence on the tracking function, especially for high resistive external voltage dividers on the SS/TR pin.

8.3.5 Smart Enable with Precise Threshold

The voltage applied at the enable pin of the TPS62901-Q1 is compared to a fixed threshold rising voltage. This allows the user to drive the pin by a slowly changing voltage and enables the use of an external RC network to achieve a power-up delay.

Copyright © 2023 Texas Instruments Incorporated

The precise enable input allows the user to program the undervoltage lockout by adding a resistor divider to the input of the EN pin.

The enable input threshold for a falling edge is lower than the rising edge threshold. The TPS62901-Q1 starts operation when the rising threshold is exceeded. For proper operation, the EN pin must be terminated and must not be left floating. Pulling the EN pin low forces the device into shutdown. In this mode, the internal high-side and low-side MOSFETs are turned off and the entire internal control circuitry is switched off.

An internal resistor pulls the EN pin to GND when the device is disabled and avoids the pin to be floating (after the device is enabled, the pulldown is removed). This prevents an uncontrolled start-up of the device in case the EN pin cannot be driven to a low level safely. With EN low, the device is in shutdown mode. The device is turned on with EN set to a high level. The pulldown control circuit disconnects the pulldown resistor on the EN pin after the internal control logic and the reference have been powered up. With EN set to a low level, the device enters shutdown mode and the pulldown resistor is activated again.

8.3.6 Power Good (PG)

The TPS62901-Q1 has a built-in power-good (PG) feature to indicate whether the output voltage has reached its target and the device is ready. The PG signal can be used for start-up sequencing of multiple rails. The PG pin is an open-drain output that requires a pullup resistor to any voltage up to the recommended input voltage level. PG is low when the device is turned off due to EN, UVLO (undervoltage lockout), or thermal shutdown. V_{IN} must remain present for the PG pin to stay low.

If the power-good output is not used, TI recommends to tie to GND or leave the output open.

表 8-3. Power-Good Indicator Functional Table

Logic Signals				PG Status
V_{IN}	EN Pin	Thermal Shutdown	V_{OUT}	
V_{IN} > UVLO	HIGH	No	V_{OUT} on target	High Impedance
			V_{OUT} < target	LOW
		Yes	×	LOW
	LOW	×	×	LOW
1.8 V < V_{IN} < UVLO	×	×	×	LOW
V_{IN} < 1.8 V	×	×	×	Undefined

备注

For prebiased V_{OUT} conditions (during start-up) of 60% or more of the programmed output voltage, a minimum 250-µs external soft start (C_{SS} > 0.75 nF) is required. If the 250-µs soft start minimum is not ensured and V_{OUT} is prebiased above 60% of the programmed output voltage during start-up, PG can be seen asserted "early" before V_{OUT} reaches the PG rising threshold, a glitch on PG can be observed, or both.

8.3.7 Output Discharge Function

The purpose of the discharge function is to make sure there is a defined down-ramp of the output voltage when the device is being disabled, and to also keep the output voltage close to 0 V when the device is off. This can be especially useful for applications with a system wide EN function that removes the output load in conjunction with disabling the power supply.

The output discharge feature is only active after the TPS62901-Q1 has been enabled at least once since the supply voltage was applied (V_{VIN} > UVLO). The internal discharge resistor is connected to the VOS pin. The discharge function is enabled as soon as the device is disabled, in thermal shutdown, or in undervoltage lockout. The minimum supply voltage required for the discharge function to remain active typically is 2 V.

Copyright © 2023 Texas Instruments Incorporated

8.3.8 Undervoltage Lockout (UVLO)

If the input voltage drops, the undervoltage lockout prevents mis-operation of the device by switching off both the power FETs. The device is fully operational for voltages above the rising UVLO threshold and turns off if the input voltage trips below the threshold for a falling supply voltage.

8.3.9 Current Limit and Short-Circuit Protection

The TPS62901-Q1 is protected against overload and short-circuit events. If the inductor current exceeds the high-side FET current limit (I_{LIMH}), the high-side switch is turned off and the low-side switch is turned on to ramp down the inductor current. The high-side FET turns on again only if the current in the low-side FET has decreased below the low-side FET current limit threshold AND the internal I_{LIM} recovery delay has expired.

备注

While the internal recovery delay generally keeps the switching frequency within the normal operating range of the device , the switching frequency is not tightly controlled during overload events.

Due to internal propagation delay, the actual current can exceed the static current limit during that time. The dynamic current limit is given as 方程式 2:

$$I_{peak(typ)} = I_{LIMH} + \frac{V_L}{L} \times t_{pd} \quad (2)$$

where

- I_{LIMH} is the static high-side FET current limit as specified in the *Electrical Characteristics*.
- L is the effective inductance at the peak current.
- V_L is the voltage across the inductor (V_{IN}–V_{OUT}).
- t_{PD} is the internal propagation delay of typically 50 ns.

The current limit can exceed static values, especially if the input voltage is high and very small inductance is used. The dynamic high-side switch peak current can be calculated as follows:

$$I_{peak(typ)} = I_{LIMH} + \frac{V_{VIN} - V_{VOUT}}{L} \times 50ns \quad (3)$$

The TPS62901-Q1 also includes a low-side negative current limit ($I_{LIM:SINK}$) to protect against excessive negative currents that can occur in forced PMW mode under heavy to light load transient conditions. If the negative current in the low-side switch exceeds the $I_{LIM:SINK}$ threshold, the low-side switch is disabled. Both the low-side and high-side switches remain off until an internal timer re-enables the high-side switch based on the selected PWM switching frequency.

CAUTION

If Forced PWM (FPWM) mode is being used, TI recommends that the inductor be sized such that the inductor ripple current, ΔI_L (see 方程式 9), does not exceed 2.6 A to avoid the potential for continuous operation of the negative current limit with no output load (I_O = 0 A).

8.3.10 High Temperature Specifications

The TPS62901-Q1 is capable of high operating junction temperatures up to 165°C. The AEC-Q100 Grade-1 maximum ambient temperature requirement (T_{A_max} = 125°C) combined with power dissipation on integrated chips often results in device operating temperatures well above 125 °C. Additionally, although Grade 1 with extended temperature does not exist as a standard by itself, the 165°C maximum operating junction temperature allows for the TPS62901-Q1 to be used in applications with ambient temperatures upwards of 150°C that require less device power dissipation.

Copyright © 2023 Texas Instruments Incorporated

备注

For more information on the different thermal metrics for semiconductor integrated circuits (ICs) including the relationship between the operating junction (T_J) and ambient (T_A) temperatures of a device, refer to the *Semiconductor and IC Package Thermal Metrics* application report.

The TPS62901-Q1 is designed to sustain these high temperatures while maintaining performance and reliability, which is accomplished by compliant electrical specifications up to T_J = 165°C. In addition, extra reliability testing has been performed that exceeds the AEC-Q100 Grade 1 requirements.

8.3.11 Thermal Shutdown

The junction temperature, T_J, of the device is monitored by an internal temperature sensor. If T_J rises and exceeds the thermal shutdown threshold, T_{SD}, the device shuts down. Both the high-side and low-side power FETs are turned off and PG goes low. When T_J decreases below the hysteresis, the converter resumes normal operation, beginning with soft start. In PSM during a PFM skip pause (when both high-side and low-side FETs are off, the thermal shutdown feature is not active. A shutdown or restart is only triggered during a switching cycle. See 节 8.4.2.

Copyright © 2023 Texas Instruments Incorporated

8.4 Device Functional Modes

8.4.1 Forced Pulse Width Modulation (FPWM) Operation

The TPS62901-Q1 has two operating modes: Forced PWM (FPWM) mode discussed in this section and auto PFM and PWM as discussed in 节 8.4.2.

With the MODE/S-CONF pin configured for FPWM mode, the TPS62901-Q1 operates with pulse width modulation in continuous conduction mode (CCM) with a nominal switching frequency of either 2.5 MHz or 1.0 MHz. The frequency variation in PWM is controlled and depends on V_{IN}, V_{OUT}, and the inductance. The on time in forced PWM mode is given by 方程式 4:

$$T_{ON} = \frac{V_{OUT}}{V_{IN}} \times \frac{1}{f_{SW}} \tag{4}$$

For very small output voltages, a minimum on time of approximately 30 ns is kept to limit switching losses. The operating frequency is thereby reduced from its nominal value, which keeps efficiency high.

8.4.2 Power Save Mode Operation (Auto PFM and PWM)

When the MODE/S-CONF pin is configured for power save mode (auto PFM and PWM). The device operates in PWM mode as long the output current is higher than half of the ripple current of the inductor, and seamlessly transitions to PSM operation as the load decreases. In power save mode, the device operates in PFM mode by reducing the switching frequency linearly with the load current to maintain high efficiency under light load operation. The device remains in power save mode as long as the inductor current remains discontinuous, and the transition out of PSM also occurs seamlessly when the load current increases above the DCM boundary.

In addition to operating in PFM under light load, when the 2.5 MHz F_{SW} option is selected, the TPS62901-Q1 further adjusts the on time (TON), depending on the input voltage and the output voltage to maintain highest efficiency using the AEE function as described in 节 8.4.3 .

In power save mode, the TON time can be estimated using 方程式 4 for 1 MHz and 方程式 8 for 2.5 MHz.

For higher input voltages and small output voltages, an absolute minimum on time of approximately 30 ns is kept to limit switching losses. The operating frequency is thereby reduced from its nominal value, which keeps efficiency high. Using TON, the typical peak inductor current in power save mode is approximated by 方程式 5:

$$ILPSM_{peak} = \frac{V_{IN} - V_{OUT}}{L} \times T_{ON} \tag{5}$$

The output voltage ripple in power save mode is given by 方程式 6:

$$\Delta V = \frac{L \times V_{IN}^2}{200 \times C} + \left(\frac{1}{V_{IN} - V_{OUT}} + \frac{1}{V_{OUT}}\right) \tag{6}$$

where

- L is the effective inductance.
- C is the output effective capacitance.

备注

When V_{IN} decreases to typically 15% above V_{OUT}, the TPS62901-Q1 does not enter power save mode, regardless of the load current. The device maintains output regulation in PWM mode.

8.4.3 AEE (Automatic Efficiency Enhancement)

When the MODE/S-CONF pin is configured for auto PFM/PWM with AEE mode, the TPS62901-Q1 provides the highest efficiency over the entire input voltage and output voltage range by automatically adjusting the switching frequency of the converter (see 方程式 7). To keep the efficiency high over the entire duty cycle range, the

Copyright © 2023 Texas Instruments Incorporated

switching frequency is adjusted while maintaining the ripple current amplitudes. This feature compensates for the very small duty cycles of high V_{IN} to low V_{OUT} conversions, which can limit the control range in other topologies.

$$F_{SW}\left(MHz\right) = 10 \times V_{OUT} \times \frac{V_{IN} - V_{OUT}}{V_{IN}^{2}} \quad (7)$$

Traditionally, the efficiency of a switched mode converter decreases if V_{OUT} decreases, V_{IN} increases, or both. By decreasing the switching losses at lower V_{OUT} values or higher V_{IN} values, the AEE feature provides an efficiency enhancement across various duty cycles, especially for the lower V_{OUT} values, where fixed frequency converters suffer from a significant efficiency drop.

To accomplish this, the AEE function in the TPS62901-Q1 adjusts the on time (TON) depending on the input voltage and the output voltage, and the on time in steady-state operation can be estimated as using 方程式 8:

$$T_{ON}\left(ns\right) = 100 \times \frac{V_{IN}}{V_{IN} - V_{OUT}} \quad (8)$$

By using the same TON configuration (see 方程式 9) across the entire load range in AEE mode, the inductor ripple current in AEE mode becomes effectively independent of the output voltage and can be approximated by 方程式 9:

$$\Delta I_{L}\left(mA\right) = T_{ON} \times \frac{V_{IN} - V_{OUT}}{L} = 0.1 \times \frac{V_{IN}\,(V)}{L\,(\mu H)} \quad (9)$$

The TPS62901-Q1 operates in AEE mode as long as the output current is higher than half the ripple current of the inductor. To maintain high efficiency at light loads, the device enters power save mode at the boundary to discontinuous mode (DCM), which happens when the output current becomes smaller than half the inductor ripple current.

8.4.4 100% Duty-Cycle Operation

The duty cycle of the buck converter operating in PWM mode is given as D = V_{OUT} / V_{IN}. The duty cycle increases as the input voltage comes close to the output voltage and the off time gets smaller. When the minimum off time of typically 80 ns is reached, the TPS62901-Q1 scales down its switching frequency while it approaches 100% mode. In 100% mode, the device keeps the high-side switch on continuously. The high-side switch stays turned on as long as the output voltage is below the internal set point, allowing the conversion of small input to output voltage differences (for example, getting longest operation time of battery-powered applications). In 100% duty cycle mode, the low-side FET is switched off.

The minimum input voltage to maintain output voltage regulation, depending on the load current and the output voltage level, can be calculated as:

$$V_{IN\,(MIN)} = V_{OUT} + I_{OUT} \times \left(R_{DS(ON)} + R_{L}\right) \quad (10)$$

where

- IOUT is the output current.
- $R_{DS(on)}$ is the on-state resistance of the high-side FET.
- R_{L} is the DC resistance of the inductor used.

8.4.5 Starting into a Prebiased Load

The TPS62901-Q1 is capable of starting into a prebiased output. The device only starts switching when the internal soft-start ramp is equal or higher than the feedback voltage. If the voltage at the feedback pin is biased to a higher voltage than the nominal value, the TPS62901-Q1 does not start switching unless the voltage at the feedback pin drops to the target. See the note in 节 8.3.6 regarding the soft-start requirement during prebiased conditions.

Copyright © 2023 Texas Instruments Incorporated

9 Application and Implementation

备注

以下应用部分中的信息不属于 TI 器件规格的范围，TI 不担保其准确性和完整性。TI 的客 户应负责确定器件是否适用于其应用。客户应验证并测试其设计，以确保系统功能。

9.1 Application Information

The TPS62901-Q1 devices are highly efficient, small, and highly flexible synchronous step-down DC/DC converters that are easy to use. A wide input voltage range of 3 V to 18 V supports a wide variety of inputs like 12-V supply rails, single-cell or multi-cell Li-Ion, and 5-V or 3.3-V rails.

9.2 Typical Application with Adjustable Output Voltage




图 9-1. Typical Application Circuit

9.2.1 Design Requirements

表 9-1. List of Components

Reference	Description	Manufacturer
IC	18 V, 1-A step-down converter	TPS62901-Q1 series; Texas Instruments
L	2.2-µH inductor	XGL4020-222; Coilcraft
CIN	10 µF, 25 V, Ceramic, X8R	CGA6P1X8R1E106K250AE, TDK
COUT	22 µF, 16 V, Ceramic, X8L	CGA6P1X8L1C226M250AC, TDK
CSS	Depends on soft-start time; see 节 9.2.2.3.3.3.	AEC-Q200 qualified, 16 V, Ceramic, X8R
R1	Depending on V_{OUT}; see 节 9.2.2.2.	AEC-Q200 qualified, Standard 1% metal film
R2	Depending on V_{OUT}; see 节 9.2.2.2.	AEC-Q200 qualified, Standard 1% metal film
R3	Depending on device setting, see 节 8.3.1.	AEC-Q200 qualified, Standard 1% metal film

9.2.2 Detailed Design Procedure

9.2.2.1 Custom Design With WEBENCH® Tools

Click here to create a custom design using the TPS62901-Q1 device with the WEBENCH® Power Designer.

1. Start by entering the input voltage (V_{IN}), output voltage (V_{OUT}), and output current (I_{OUT}) requirements.
2. Optimize the design for key parameters such as efficiency, footprint, and cost using the optimizer dial.
3. Compare the generated design with other possible solutions from Texas Instruments.

Copyright © 2023 Texas Instruments Incorporated

The WEBENCH Power Designer provides a customized schematic along with a list of materials with real-time pricing and component availability.

In most cases, these actions are available:

- Run electrical simulations to see important waveforms and circuit performance
- Run thermal simulations to understand board thermal performance
- Export customized schematic and layout into popular CAD formats
- Print PDF reports for the design, and share the design with colleagues

Get more information about WEBENCH tools at www.ti.com/WEBENCH.

9.2.2.2 Programming the Output Voltage

When the MODE/S_CONF pin is configured for external feedback, the output voltage of the TPS62901-Q1 is fully adjustable. It can be programmed for output voltages from 0.6 V to 5.5 V using a resistor divider from V_{OUT} to GND. The voltage at the FB pin is regulated to 600 mV. The value of the output voltage is set by the selection of the resistor divider from 方程式 11. TI recommends to choose resistor values that allow a current of at least 2 µA, meaning the value of R2 must not exceed 400 kΩ. Lower resistor values are recommended for highest accuracy and most robust design.

$$R_1 = R_2 \times \left(\frac{VOUT}{VFB} - 1\right) \tag{11}$$

With typical VFB = 0.6 V:

表 9-2. Setting the Output Voltage

Nominal Output Voltage	R1	R2	Exact Output Voltage
0.75 V	24.9 kΩ	100 kΩ	0.749 V
1.2 V	100 kΩ	100 kΩ	1.2 V
1.5 V	150 kΩ	100 kΩ	1.5 V
1.8 V	200 kΩ	100 kΩ	1.8 V
2.0 V	49.9 kΩ	21.5 kΩ	1.992 V
2.5 V	100 kΩ	31.6 kΩ	2.498 V
3.0 V	100 kΩ	24.9 kΩ	3.009 V
3.3 V	113 kΩ	24.9 kΩ	3.322 V
5.0V	182 kΩ	24.9 kΩ	4.985 V

9.2.2.3 External Component Selection

The external components have to fulfill the needs of the application, but also the stability criteria of the control loop of the device. The TPS62901-Q1 is optimized to work within a range of external components.

9.2.2.3.1 Output Filter and Loop Stability

The TPS62901-Q1 is designed to be stable with a range of L-C filter combinations. The LC output filters inductance and capacitance have to be considered together, creating a double pole responsible for the corner frequency of the converter using 方程式 12.

$$f_{LC} = \frac{1}{2\pi\sqrt{L \times C}} \tag{12}$$

Proven nominal values for inductance and ceramic capacitance are given in 表 9-3 and are recommended for use with the effective capacitance considered to vary by +20% and –50%. Different values can work, but care has to be taken on the loop stability, which is affected. More information including a detailed LC stability matrix can be found in the *Optimizing the TPS62130/40/50/60 Output Filter* application report.

Copyright © 2023 Texas Instruments Incorporated

表 9-3. Recommended LC Output Filter Combinations

	4.7 µF	10 µF	22 µF	47 µF	100 µF	200 µF
1 µH		√	√(1)	√	√	√(3)
1.5 µH		√	√	√	√(3)	
2.2 µH		√	√(2)	√	√(3)	
3.3 µH	√	√	√	√		

(1) This LC combination is the standard value and recommended for most applications with 2.5-MHz switching frequency.
(2) This LC combination is the standard value and recommended for most applications with 1-MHz switching frequency.
(3) Output capacitance must have a ESR of ≥ 10 mΩ for stable operation, see 节 9.4.2.

The TPS62901-Q1 includes an internal 3-pF feedforward capacitor, connected between the VOS and FB pins. This capacitor impacts the frequency behavior and sets a pole and zero in the control loop with the resistors of the feedback divider, per 方程式 13 and 方程式 14:

$$f_{zero} = \frac{1}{2\pi \times R_1 \times 3pF} \tag{13}$$

$$f_{pole} = \frac{1}{2\pi \times 3pF} \times \left(\frac{1}{R_1} \times \frac{1}{R_2}\right) \tag{14}$$

Although the TPS62901-Q1 devices are stable without the pole and zero being in a particular location, an external feedforward capacitor can be added to adjust their locations to the specific needs of the application can provide better performance in power save mode, improved transient response, or both. A more detailed discussion on the optimization for stability versus transient response can be found in the *Optimizing Transient Response of Internally Compensated DC-DC Converters* and *Feedforward Capacitor to Improve Stability and Bandwidth of TPS621/821-Family* application reports.

9.2.2.3.2 Inductor Selection

The TPS62901-Q1 is designed for a nominal 1-µH inductor. Larger values can be used to achieve a lower inductor current ripple, but they can have a negative impact on efficiency and transient response. Smaller values than 1 µH cause a larger inductor current ripple, which causes larger negative inductor current in forced PWM mode at low or no output current. Therefore, TI does not recommend them at large voltages across the inductor as it is the case for high input voltages and low output voltages. Low-output current in forced PWM mode causes a larger negative inductor current peak, which can exceed the negative current limit. At low or no output current and small inductor values, the output voltage cannot be regulated any more. More detailed information on further LC combinations can be found in the *Optimizing the TPS62130/40/50/60 Output Filter* application report.

The inductor selection is affected by several factors like inductor ripple current, output ripple voltage, PWM-to-PFM transition point, and efficiency. In addition, the inductor selected has to be rated for appropriate saturation current and DC resistance (DCR). 方程式 15 calculates the maximum inductor current.

$$I_{L(MAX)} = I_{OUT(MAX)} + \frac{\Delta I_{L(MAX)}}{2} \tag{15}$$

$$\Delta I_{L(MAX)} = V_{OUT} \times \frac{1 - \frac{V_{OUT}}{V_{IN(MAX)}}}{L_{(MIN)} \times f_{SW}} \tag{16}$$

where

- $I_{L(max)}$ is the maximum inductor current.
- $\Delta I_{L(max)}$ is the maximum peak-to-peak inductor ripple current.
- $L_{(min)}$ is the minimum effective inductor value.
- f_{sw} is the actual PWM switching frequency.
- V_{OUT} is the output voltage.
- $V_{IN(max)}$ is the maximum expected output voltage.

Copyright © 2023 Texas Instruments Incorporated

Calculating the maximum inductor current using the actual operating conditions gives the needed minimum saturation current of the inductor. TI recommends to add a margin of about 20%. A larger inductor value is also useful to get lower ripple current, but increases the transient response time and size as well. The following inductors have been used with the TPS62901-Q1 and are recommended for use:

表 9-4. List of Inductors

Type	Inductance [µH]	Current [A](1)	Dimensions [L × B × H] mm	Manufacturer
XGL4020-102ME	1.0 µH, ±20%	8.8	4.0 × 4.0 × 2.1	Coilcraft
XGL4020-222ME	2.2 µH, ±20%	6.2	4.0 × 4.0 × 2.1	Coilcraft

(1) I_{SAT} at 30% drop

The inductor value also determines the load current at which power save mode is entered:

$$I_{Load(PSM)} = \frac{1}{2} \times \Delta I_L \quad (17)$$

9.2.2.3.3 Capacitor Selection

9.2.2.3.3.1 Output Capacitor

The recommended value for the output capacitor is 22 µF. The architecture of the TPS62901-Q1 allows the use of tiny ceramic output capacitors with low equivalent series resistance (ESR). These capacitors provide low output voltage ripple and are recommended. To keep its low resistance up to high frequencies and to get narrow capacitance variation with temperature, TI recommends the use of X7R or X8R dielectric capacitors. Using a higher value has advantages like smaller voltage ripple and a tighter DC output accuracy in power save mode (see the *Optimizing the TPS62130/40/50/60 Output Filter* application report).

In power save mode, the output voltage ripple depends on the following:

- Output capacitance
- ESR
- ESL
- Peak inductor current

Using ceramic capacitors provides small ESR, ESL, and low ripple. The output capacitor must be as close as possible to the device.

For large output voltages, the DC bias effect of ceramic capacitors is large and the effective capacitance has to be observed.

9.2.2.3.3.2 Input Capacitor

For most applications, 10 µF nominal is sufficient and is recommended, though a larger value reduces input current ripple further. The input capacitor buffers the input voltage for transient events and also decouples the converter from the supply. TI recommends a low-ESR multilayer ceramic capacitor (MLCC) for best filtering and must be placed between VIN and GND as close as possible to those pins.

表 9-5. List of Capacitors

Type (1)	Nominal Capacitance [µF]	Voltage Rating [V]	Size	Manufacturer
CGA6P1X8R1E106K250AE	10	25	1210	TDK
CGA6P1X8L1C226M250AC	22	16	1210	TDK

(1) Lower of I_{RMS} at 40°C rise or I_{SAT} at 30% drop

9.2.2.3.3.3 Soft-Start Capacitor

A capacitor connected between SS/TR pin and GND allows a user-programmable start-up slope of the output voltage.

Copyright © 2023 Texas Instruments Incorporated




图 9-2. Soft-Start Operation Simplified Schematic

An internal constant current source is provided to charge the external capacitance. The capacitor required for a given soft-start ramp time is given by:

$$C_{SS} = T_{SS} \times \frac{I_{SS}}{V_{REF}} \quad (18)$$

where


- C_{SS} is the capacitance required at the SS/TR pin.
- T_{SS} is the desired soft-start ramp time.
- I_{SS} is the SS/TR source current, see the *Electrical Characteristics*.
- V_{REF} is the feedback regulation voltage divided by tracking gain (V_{FB} / 0.75); see the *Electrical Characteristics*.

The fastest achievable typical ramp time is 150 µs, even if the external C_{ss} capacitance is lower than 680 pF or the pin is open.

Copyright © 2023 Texas Instruments Incorporated


9.2.3 Application Curves

9.2.3.1 Application Curves Vout = 1.8 V




V_{OUT} = 1.8 V L = 1.0 µH F_{sw} = 2.5 MHz
Auto PFM/PWM

图 9-3. Efficiency vs Output Current




V_{OUT} = 1.8 V L = 1.0 µH F_{sw} = 2.5 MHz
Forced PWM

图 9-4. Efficiency vs Output Current




V_{OUT} = 1.8 V L = 1.0 µH F_{sw} = 2.5 MHz
Auto PFM/PWM

图 9-5. Switching Frequency vs Input Voltage




V_{OUT} = 1.8 V L = 1.0 µH F_{sw} = 2.5 MHz
Forced PWM

图 9-6. Switching Frequency vs Input Voltage



V_{OUT} = 1.8 V L = 1.0 µH F_{sw} = 2.5 MHz
Auto PFM/PWM


图 9-7. Output Voltage vs Output Current



V_{OUT} = 1.8 V L = 1.0 µH F_{sw} = 2.5 MHz
Forced PWM


图 9-8. Output Voltage vs Output Current

Copyright © 2023 Texas Instruments Incorporated




V_{OUT} = 1.8 V L = 2.2 µH F_{sw} = 1.0 MHz
Auto PFM/PWM

图 9-9. Efficiency vs Output Current




V_{OUT} = 1.8 V L = 2.2 µH F_{sw} = 1.0 MHz
Forced PWM

图 9-10. Efficiency vs Output Current




V_{OUT} = 1.8 V L = 2.2 µH F_{sw} = 1.0 MHz
Auto PFM/PWM

图 9-11. Switching Frequency vs Input Voltage




V_{OUT} = 1.8 V L = 2.2 µH F_{sw} = 1.0 MHz
Forced PWM

图 9-12. Switching Frequency vs Input Voltage



V_{OUT} = 1.8 V L = 2.2 µH F_{sw} = 1.0 MHz
Auto PFM/PWM

图 9-13. Output Voltage vs Output Current




V_{OUT} = 1.8 V L = 2.2 µH F_{sw} = 1.0 MHz
Forced PWM

图 9-14. Output Voltage vs Output Current


Copyright © 2023 Texas Instruments Incorporated

9.2.3.2 Application Curves Vout = 1.2 V




V_{OUT} = 1.2 V L = 1.0 µH F_{sw} = 2.5 MHz
Auto PFM/PWM

图 9-15. Efficiency vs Output Current




V_{OUT} = 1.2 V L = 1.0 µH F_{sw} = 2.5 MHz
Forced PWM

图 9-16. Efficiency vs Output Current




V_{OUT} = 1.2 V L = 1.0 µH F_{sw} = 2.5 MHz
Auto PFM/PWM

图 9-17. Switching Frequency vs Input Voltage




V_{OUT} = 1.2 V L = 1.0 µH F_{sw} = 2.5 MHz
Forced PWM

图 9-18. Switching Frequency vs Input Voltage



V_{OUT} = 1.2 V L = 1.0 µH F_{sw} = 2.5 MHz
Auto PFM/PWM


图 9-19. Output Voltage vs Output Current



V_{OUT} = 1.2 V L = 1.0 µH F_{sw} = 2.5 MHz
Forced PWM


图 9-20. Output Voltage vs Output Current

Copyright © 2023 Texas Instruments Incorporated




V_{OUT} = 1.2 V L = 2.2 µH F_{sw} = 1.0 MHz
Auto PFM/PWM

图 9-21. Efficiency vs Output Current




V_{OUT} = 1.2 V L = 2.2 µH F_{sw} = 1.0 MHz
Forced PWM

图 9-22. Efficiency vs Output Current




V_{OUT} = 1.2 V L = 2.2 µH F_{sw} = 1.0 MHz
Auto PFM/PWM

图 9-23. Switching Frequency vs Input Voltage




V_{OUT} = 1.2 V L = 2.2 µH F_{sw} = 1.0 MHz
Forced PWM

图 9-24. Switching Frequency vs Input Voltage



V_{OUT} = 1.2 V L = 2.2 µH F_{sw} = 1.0 MHz
Auto PFM/PWM

图 9-25. Output Voltage vs Output Current




V_{OUT} = 1.2 V L = 2.2 µH F_{sw} = 1.0 MHz
Forced PWM

图 9-26. Output Voltage vs Output Current


Copyright © 2023 Texas Instruments Incorporated

9.2.3.3 Application Curves Vout = 0.6 V




V_{OUT} = 0.6 V L = 1.0 µH F_{sw} = 2.5 MHz
Auto PFM/PWM

图 9-27. Efficiency vs Output Current




V_{OUT} = 0.6 V L = 1.0 µH F_{sw} = 2.5 MHz
Forced PWM

图 9-28. Efficiency vs Output Current




V_{OUT} = 0.6 V L = 1.0 µH F_{sw} = 2.5 MHz
Auto PFM/PWM

图 9-29. Switching Frequency vs Input Voltage




V_{OUT} = 0.6 V L = 1.0 µH F_{sw} = 2.5 MHz
Forced PWM

图 9-30. Switching Frequency vs Input Voltage



V_{OUT} = 0.6 V L = 1.0 µH F_{sw} = 2.5 MHz
Auto PFM/PWM


图 9-31. Output Voltage vs Output Current



V_{OUT} = 0.6 V L = 1.0 µH F_{sw} = 2.5 MHz
Forced PWM


图 9-32. Output Voltage vs Output Current

Copyright © 2023 Texas Instruments Incorporated




V_{OUT} = 0.6 V L = 2.2 µH F_{sw} = 1.0 MHz
Auto PFM/PWM

图 9-33. Efficiency vs Output Current




V_{OUT} = 0.6 V L = 2.2 µH F_{sw} = 1.0 MHz
Forced PWM

图 9-34. Efficiency vs Output Current




V_{OUT} = 0.6 V L = 2.2 µH F_{sw} = 1.0 MHz
Auto PFM/PWM

图 9-35. Switching Frequency vs Input Voltage




V_{OUT} = 0.6 V L = 2.2 µH F_{sw} = 1.0 MHz
Forced PWM

图 9-36. Switching Frequency vs Input Voltage



V_{OUT} = 0.6 V L = 2.2 µH F_{sw} = 1.0 MHz
Auto PFM/PWM

图 9-37. Output Voltage vs Output Current



V_{OUT} = 0.6 V L = 2.2 µH F_{sw} = 1.0 MHz
Forced PWM

图 9-38. Output Voltage vs Output Current

Copyright © 2023 Texas Instruments Incorporated

9.3 Typical Application with Selectable V_{OUT} using VSET




图 9-39. Typical Application Circuit (VSET)

9.3.1 Design Requirements

表 9-6. List of Components

Reference	Description	Manufacturer
IC	18 V, 1-A step-down converter	TPS62901-Q1 series; Texas Instruments
L	2.2-µH inductor	XGL4020-222; Coilcraft
CIN	10 µF, 25 V, Ceramic, X8R	CGA6P1X8R1E106K250AE, TDK
COUT	22 µF, 16 V, Ceramic, X8L	CGA6P1X8L1C226M250AC, TDK
CSS	Depends on soft-start time; see 节 9.2.2.3.3.3.	AEC-Q200 qualified, 16 V, Ceramic, X8R
R2	Depending on V_{OUT}; see .节 8.3.3	AEC-Q200 qualified, Standard 1% metal film
R3	Depending on device setting, see 节 8.3.1.	AEC-Q200 qualified, Standard 1% metal film

9.3.2 Detailed Design Procedure


9.3.2.1 Programming the Output Voltage

When the resitor (R3) on the MODE/S-CONF pin is sized for "VSET" (internal FB) operation (see 表 8-1) , the output voltage of the TPS62901-Q1 becomes selectable with a resistor (R2) from the FB/VSET pin the GND. The output can be programmed to one of 16 different fixed output voltages ranging from 0.4 V to 5.5 V based on 表 8-2.

Copyright © 2023 Texas Instruments Incorporated


9.3.3 Application Curves

9.3.3.1 Application Curves Vout = 5 V




V_{OUT} = 5.0 V L = 1.0 µH F_{sw} = 2.5 MHz
Auto PFM/PWM

图 9-40. Efficiency vs Output Current




V_{OUT} = 5.0 V L = 1.0 µH F_{sw} = 2.5 MHz
Forced PWM

图 9-41. Efficiency vs Output Current




V_{OUT} = 5.0 V L = 1.0 µH F_{sw} = 2.5 MHz
Auto PFM/PWM

图 9-42. Switching Frequency vs Input Voltage




V_{OUT} = 5.0 V L = 1.0 µH F_{sw} = 2.5 MHz
Forced PWM

图 9-43. Switching Frequency vs Input Voltage



V_{OUT} = 5.0 V L = 1.0 µH F_{sw} = 2.5 MHz
Auto PFM/PWM


图 9-44. Output Voltage vs Output Current



V_{OUT} = 5.0 V L = 1.0 µH F_{sw} = 2.5 MHz
Forced PWM


图 9-45. Output Voltage vs Output Current

Copyright © 2023 Texas Instruments Incorporated




V_{OUT} = 5.0 V L = 2.2 µH F_{sw} = 1.0 MHz
Auto PFM/PWM

图 9-46. Efficiency vs Output Current




V_{OUT} = 5.0 V L = 2.2 µH F_{sw} = 1.0 MHz
Forced PWM

图 9-47. Efficiency vs Output Current




V_{OUT} = 5.0 V L = 2.2 µH F_{sw} = 1.0 MHz
Auto PFM/PWM

图 9-48. Switching Frequency vs Input Voltage




V_{OUT} = 5.0 V L = 2.2 µH F_{sw} = 1.0 MHz
Forced PWM

图 9-49. Switching Frequency vs Input Voltage



V_{OUT} = 5.0 V L = 2.2 µH F_{sw} = 1.0 MHz
Auto PFM/PWM

图 9-50. Output Voltage vs Output Current




V_{OUT} = 5.0 V L = 2.2 µH F_{sw} = 1.0 MHz
Forced PWM

图 9-51. Output Voltage vs Output Current


Copyright © 2023 Texas Instruments Incorporated

9.3.3.2 Application Curves Vout = 3.3 V




V_{OUT} = 3.3 V L = 1.0 µH F_{sw} = 2.5 MHz
Auto PFM/PWM

图 9-52. Efficiency vs Output Current




V_{OUT} = 3.3 V L = 1.0 µH F_{sw} = 2.5 MHz
Forced PWM

图 9-53. Efficiency vs Output Current




V_{OUT} = 3.3 V L = 1.0 µH F_{sw} = 2.5 MHz
Auto PFM/PWM

图 9-54. Switching Frequency vs Input Voltage




V_{OUT} = 3.3 V L = 1.0 µH F_{sw} = 2.5 MHz
Forced PWM

图 9-55. Switching Frequency vs Input Voltage



V_{OUT} = 3.3 V L = 1.0 µH F_{sw} = 2.5 MHz
Auto PFM/PWM


图 9-56. Output Voltage vs Output Current



V_{OUT} = 3.3 V L = 1.0 µH F_{sw} = 2.5 MHz
Forced PWM


图 9-57. Output Voltage vs Output Current

Copyright © 2023 Texas Instruments Incorporated




V_{OUT} = 3.3 V L = 2.2 µH F_{sw} = 1.0 MHz
Auto PFM/PWM

图 9-58. Efficiency vs Output Current




V_{OUT} = 3.3 V L = 2.2 µH F_{sw} = 1.0 MHz
Forced PWM

图 9-59. Efficiency vs Output Current




V_{OUT} = 3.3 V L = 2.2 µH F_{sw} = 1.0 MHz
Auto PFM/PWM

图 9-60. Switching Frequency vs Input Voltage




V_{OUT} = 3.3 V L = 2.2 µH F_{sw} = 1.0 MHz
Forced PWM

图 9-61. Switching Frequency vs Input Voltage



V_{OUT} = 3.3 V L = 2.2 µH F_{sw} = 1.0 MHz
Auto PFM/PWM

图 9-62. Output Voltage vs Output Current



V_{OUT} = 3.3 V L = 2.2 µH F_{sw} = 1.0 MHz
Forced PWM

图 9-63. Output Voltage vs Output Current

Copyright © 2023 Texas Instruments Incorporated

9.4 System Examples

9.4.1 LED Power Supply

The TPS62901-Q1 can be used as a power supply for power LEDs. The FB pin can be easily set to lower values than nominal by using the SS/TR pin. With that, the voltage drop on the sense resistor (R2) is reduced to avoid excessive power loss. Because the SS/TR pin provides 2.5 µA (typical), the feedback pin voltage can be adjusted by an external resistor per 方程式 19. This drop, proportional to the LED current, is used to regulate the output voltage (anode voltage) to a proper level to drive the LED. Both analog and PWM dimming are supported with the TPS62901-Q1. 图 9-64 shows an application circuit, tested with analog dimming.




图 9-64. Single Power LED Supply

The resistor at SS/TR defines the FB voltage. The resistor at SS/TR is set to 304 mV by $R_{SS/TR}$ = R4 = 162 kΩ using 方程式 19. This cuts the losses on R2 to half from the nominal 0.6 V of feedback voltage while it still provides good accuracy.

$$V_{FB} = 0.75 \times 2.5\mu A \times R_{SS/TR} \quad (19)$$

The device now supplies a constant current set by resistor R2 from FB/VSET to GND. The minimum input voltage has to be rated according the forward voltage needed by the LED used. More information is available in the *Step-Down LED Driver With Dimming With the TPS621-Family and TPS821-Family* application report.

9.4.2 Powering Multiple Loads

In applications where the TPS62901-Q1 is used to power multiple load circuits, the total capacitance on the output can be very large. To properly regulate the output voltage, there must be an appropriate AC signal level on the VOS pin. Tantalum capacitors have a large enough ESR to keep output voltage ripple sufficiently high on the VOS pin. With low-ESR ceramic capacitors, the output voltage ripple can get very low, so TI does not recommend to use a large capacitance directly on the output of the device. If there are several load circuits with their associated input capacitor on a PCB, these loads are typically distributed across the board. This adds enough trace resistance (R_{trace}) to keep a large enough AC signal on the VOS pin for proper regulation.

The minimum total trace resistance on the distributed load is 10 mΩ. The total capacitance n × CIN in the use case below was 32 × 47 µF of ceramic X7R capacitors.

Copyright © 2023 Texas Instruments Incorporated




图 9-65. Multiple Loads

备注

图 9-65 shows an external feedback configuration, but the internal (VSET) configuration can also be used.

9.4.3 Voltage Tracking

图 9-66 shows how two TPS62901-Q1s can be configured to tracking output voltages. In this configuration, Device 2 follows the voltage applied to its SS/TR pin from Device 1 output. A ramp on the SS/TR pin of Device 2 to 0.8 V in turn ramps VOUT2 according to the 0.6-V reference on V_{FB} and the R4//R5 resistor divider.

For this example, to track the 3.8 V (VOUT1) of Device 1 a resistor divider (R7//R8) on SS/TR of Device 2 is required to generate 0.8 V when the output voltage (VOUT1) is in regulation. Due to the I_{SS} current of 2.5 µA from the SS/TR pin, the equivalent resistance of R7 // R8 must be kept below 15 kΩ to minimize any offset the I_{SS} current can cause on the SS/TR pin voltage.

Copyright © 2023 Texas Instruments Incorporated




图 9-66. Tracking Example




图 9-67. Tracking

9.4.4 Inverting Buck-Boost (IBB)

The need to generate negative voltage rails for electronic designs is a common challenge. The wide 3-V to 18-V input voltage range of the TPS62901-Q1 makes it ideal for an inverting buck-boost (IBB) circuit, where the output voltage is inverted or negative with respect to ground.

The circuit operation in the IBB topology differs from that in the traditional buck topology. Though the components are connected the same as with a traditional buck converter, the output voltage terminals are reversed. See 图 9-68.

The maximum input voltage that can be applied to an IBB converter is less than the maximum voltage that can be applied to the TPS62901-Q1 in a typical buck configuration. This is because the ground pin of the IC is connected to the (negative) output voltage. Therefore, the input voltage across the device is V_{IN} to V_{OUT}, and not V_{IN} to ground. Thus, the input voltage range of the TPS62901-Q1 in an IBB configuration becomes 3 V to 18 V + V_{OUT}, where V_{OUT} is a negative value.

The output voltage range is the same as when configured as a buck converter, but only negative. Thus, the output voltage for a TPS62901-Q1 in an IBB configuration can be set between –0.4 V and –5.5 V.

The maximum output current for the TPS62901-Q1 in an IBB topology is normally lower than a traditional buck configuration due to the average inductor current being higher in an IBB configuration. Traditionally, lower input or (more negative) output voltages results in a lower maximum output current. However, using a larger inductor value or the higher 2.5-MHz frequency setting can be used to recover some or all of this lost maximum current capability.

When implementing an IBB design, it is important to understand that the IC ground is tied to the negative voltage rail, and in turn, the electrical characteristics of the TPS62901-Q1 device are referenced to this rail. During power up, as there is no charge in the output capacitor and the IC GND pin (and V_{OUT}) are effectively 0 V, thus parameters such as the V_{IN} UVLO and EN thresholds are the same as in a typical buck configuration. However, after the output voltage is in regulation, due to the negative voltage on the IC GND pin, the device traditionally continues to operate below what can appear to be the normal UVLO or EN falling thresholds relative to the system ground. Take care if the user is using the dynamic mode change feature on the MODE pin of the TPS62901-Q1 or driving the EN pin from an upstream microcontroller as the high and low thresholds are relative to the negative rail and not the system ground.

More information on using a DCS regulator in an IBB configuration can be found in the *Description Compensating the Current Mode Boost Control Loop*, *Using the TPS6215x in an Inverting Buck-Boost Topology*, and *Using the TPS629210 in an Inverting Buck-Boost Topology* application notes.




图 9-68. IBB Example with Adjustable Feedback

Copyright © 2023 Texas Instruments Incorporated

备注

图 9-68 shows an external feedback configuration, but the internal (VSET) configuration can also be used.

9.5 Power Supply Recommendations

The power supply to the TPS62901-Q1 must have a current rating according to the supply voltage, output voltage, and output current of the TPS62901-Q1. At a minimum, the input power supply must provide enough power to cover the maximum output power divided by the efficiency at maximum load. A good rule of thumb is to use a supply with an additional 50% of power capability to withstand the additional loading associated with power up, transient events, and potential overload events.

备注

For current limited input supplies with a variable supply voltage, the minimum supply voltage must be used to determine if the power supply is sufficient.

9.6 Layout

9.6.1 Layout Guidelines

A proper layout is critical for the operation of a switched mode power supply, even more at high switching frequencies. Therefore, the PCB layout of the TPS62901-Q1 demands careful attention to make sure the device works correctly and to get the performance specified. A poor layout can lead to issues like poor regulation (both line and load), stability and accuracy weaknesses, increased EMI radiation, and noise sensitivity.

See 图 9-69 for the recommended layout of the TPS62901-Q1, which is designed for common external ground connections. The input capacitor must be placed as close as possible between the VIN and GND pin of TPS62901-Q1. Also, connect the VOS pin in the shortest way to VOUT at the output capacitor.

Provide low inductive and resistive paths for loops with high di/dt. Therefore paths, conducting the switched load current must be as short and wide as possible. Provide low capacitive paths (with respect to all other nodes) for traces with high dv/dt. Therefore, the input and output capacitance must be placed as close as possible to the IC pins and parallel wiring over long distances as well as narrow traces must be avoided. Loops that conduct an alternating current must outline an area as small as possible, as this area is proportional to the energy radiated.

Sensitive nodes like FB and VOS need to be connected with short wires and not nearby high dv/dt signals (for example, SW). As they carry information about the output voltage, they must be connected as close as possible to the actual output voltage (at the output capacitor). The capacitor on the SS/TR pin as well as the FB resistors, R1 and R2, must be kept close to the IC and connected directly to those pins and the system ground plane. The same applies to the VSET resistor if VSET is used to scale the output voltage.

The package uses the pins for power dissipation. Thermal vias on the VIN and GND pins help to spread the heat through the PCB.

In case any of the digital inputs EN and MODE/S-CONF must be tied to the input supply voltage at V_{IN}, the connection must be made directly at the input capacitor as indicated in the schematics.

The recommended layout is implemented on the EVM and shown in the *TPS6290x-Q1 Step-Down Converter Evaluation Module* user's guide.

Copyright © 2023 Texas Instruments Incorporated

9.6.2 Layout Example




图 9-69. Layout

9.6.3 Thermal Considerations

Implementation of integrated circuits in low-profile and fine-pitch surface-mount packages typically requires special attention to power dissipation. Many system-dependent issues such as thermal coupling, airflow, added heat sinks and convection surfaces, and the presence of other heat-generating components affect the power-dissipation limits of a given component.

The basic approaches for enhancing thermal performance are:

- Improving the power dissipation capability of the PCB design, for example, increasing copper thickness, thermal vias, number of layers
- Introducing airflow in the system

For more details on how to use the thermal parameters, see the *Thermal Characteristics of Linear and Logic Packages Using JEDEC PCB Designs* and *Semiconductor and IC Package Thermal Metrics* application reports.

The TPS62901-Q1 is designed for a maximum operating junction temperature (T_J) of 165°C. Therefore, the maximum output power is limited by the power losses that can be dissipated over the actual thermal resistance, given by the package and the surrounding PCB structures. If the thermal resistance of the package is given, the size of the surrounding copper area and a proper thermal connection of the IC can reduce the thermal resistance. To get an improved thermal behavior, TI recommends to use top layer metal to connect the device with wide and thick metal lines. Internal ground layers can connect to vias directly under the IC for improved thermal performance.

If short circuit or overload conditions are present, the device is protected by limiting internal power dissipation.

The device is qualified for long term qualification with 165°C junction temperature. For more details about the derating and life time of the HotRod™ package, see the *Derating and Lifetime Calculations for FCOL Packages HotRod and FC-SOT* application note.

Copyright © 2023 Texas Instruments Incorporated

10 Device and Documentation Support

10.1 Device Support

10.1.1 第三方产品免责声明

TI 发布的与第三方产品或服务有关的信息，不能构成与此类产品或服务或保修的适用性有关的认可，不能构成此类产品或服务单独或与任何 TI 产品或服务一起的表示或认可。

10.1.2 Development Support

10.1.2.1 Custom Design With WEBENCH® Tools

Click here to create a custom design using the TPS62901-Q1 device with the WEBENCH® Power Designer.

1. Start by entering the input voltage (V_{IN}), output voltage (V_{OUT}), and output current (I_{OUT}) requirements.
2. Optimize the design for key parameters such as efficiency, footprint, and cost using the optimizer dial.
3. Compare the generated design with other possible solutions from Texas Instruments.

The WEBENCH Power Designer provides a customized schematic along with a list of materials with real-time pricing and component availability.

In most cases, these actions are available:

- Run electrical simulations to see important waveforms and circuit performance
- Run thermal simulations to understand board thermal performance
- Export customized schematic and layout into popular CAD formats
- Print PDF reports for the design, and share the design with colleagues

Get more information about WEBENCH tools at www.ti.com/WEBENCH.

10.2 Documentation Support

10.2.1 Related Documentation

For related documentation see the following:

- Texas Instruments, *Derating and Lifetime Calculations for FCOL Packages HotRod and FC-SOT* application note
- Texas Instruments, *Semiconductor and IC Package Thermal Metrics* application report
- Texas Instruments, *Thermal Characteristics of Linear and Logic Packages Using JEDEC PCB Designs* application report
- Texas Instruments, *TPS6290x-Q1 Step-Down Converter Evaluation Module* user's guide
- Texas Instruments, *Using the TPS629210 in an Inverting Buck-Boost Topology* application report
- Texas Instruments, *Description Compensating the Current Mode Boost Control Loop* application report

10.3 接收文档更新通知

要接收文档更新通知，请导航至 ti.com 上的器件产品文件夹。点击 *订阅更新* 进行注册，即可每周接收产品信息更改摘要。有关更改的详细信息，请查看任何已修订文档中包含的修订历史记录。

10.4 支持资源

TI E2E™ 支持论坛是工程师的重要参考资料，可直接从专家获得快速、经过验证的解答和设计帮助。搜索现有解答或提出自己的问题可获得所需的快速设计帮助。

链接的内容由各个贡献者“按原样”提供。这些内容并不构成 TI 技术规范，并且不一定反映 TI 的观点；请参阅 TI 的《使用条款》。

10.5 Trademarks

HotRod™ and TI E2E™ are trademarks of Texas Instruments.
WEBENCH® is a registered trademark of Texas Instruments.
所有商标均为其各自所有者的财产。

Copyright © 2023 Texas Instruments Incorporated

10.6 静电放电警告



静电放电 (ESD) 会损坏这个集成电路。德州仪器 (TI) 建议通过适当的预防措施处理所有集成电路。如果不遵守正确的处理和安装程序，可能会损坏集成电路。

ESD 的损坏小至导致微小的性能降级，大至整个器件故障。精密的集成电路可能更容易受到损坏，这是因为非常细微的参数更改都可能会导致器件与其发布的规格不相符。

10.7 术语表

TI 术语表　　本术语表列出并解释了术语、首字母缩略词和定义。

11 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

Copyright © 2023 Texas Instruments Incorporated

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package | Pins	Package qty | Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
TPS62901QRYTRQ1	Active	Production	VQFN-HR (RYT) | 9	3000 | LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	-40 to 165	TS01
TPS62901QRYTRQ1.A	Active	Production	VQFN-HR (RYT) | 9	3000 | LARGE T&R	Yes	SN	Level-2-260C-1 YEAR	-40 to 165	TS01

(1) **Status:** For more details on status, see our product life cycle.

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

OTHER QUALIFIED VERSIONS OF TPS62901-Q1 :

- Catalog : TPS62901

NOTE: Qualified Version Definitions:


- Catalog - TI's standard catalog product

PACKAGE OUTLINE

RYT0009A


VQFN-HR - 0.9 mm max height

PLASTIC SMALL OUTLINE - NO LEAD




NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.



LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE: 30X



NON SOLDER MASK
DEFINED
(PREFERRED)


SOLDER MASK DEFINED

SOLDER MASK DETAILS

4226765/B 05/2024

NOTES: (continued)

3. This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/slua271).



SOLDER PASTE EXAMPLE
BASED ON 0.125 MM THICK STENCIL
SCALE: 30X

4226765/B 05/2024

NOTES: (continued)

4. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

重要通知和免责声明

TI“按原样”提供技术和可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证没有瑕疵且不做出任何明示或暗示的担保，包括但不限于对适销性、与某特定用途的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任：(1) 针对您的应用选择合适的 TI 产品，(2) 设计、验证并测试您的应用，(3) 确保您的应用满足相应标准以及任何其他安全、安保法规或其他要求。

这些资源如有变更，恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的相关应用。严禁以其他方式对这些资源进行复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。对于因您对这些资源的使用而对 TI 及其代表造成的任何索赔、损害、成本、损失和债务，您将全额赔偿，TI 对此概不负责。

TI 提供的产品受 TI 销售条款)、TI 通用质量指南 或 ti.com 上其他适用条款或 TI 产品随附的其他适用条款的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。 除非德州仪器 (TI) 明确将某产品指定为定制产品或客户特定产品，否则其产品均为按确定价格收入目录的标准通用器件。

TI 反对并拒绝您可能提出的任何其他或不同的条款。

版权所有 © 2026，德州仪器 (TI) 公司

最后更新日期：2025 年 10 月