

## LMV331 单路、LMV393 双路、LMV339 四路通用低电压比较器

### 1 特性

- 2.7V 和 5V 性能
- 低电源电流
  - LMV331 26  $\mu$ A 典型值
  - LMV393 50  $\mu$ A 典型值
  - LMV339 100  $\mu$ A 典型值
- 输入共模电压范围包括接地
- 低输出饱和电压 150mV 典型值
- 集电极开路输出可实现最大限度灵活性

### 2 应用

- 扫地机器人
- 服务器 PSU
- 无绳电动工具
- 电器
- 楼宇自动化
- 工厂自动化与控制

### 3 说明


LMV393 和 LMV339 器件分别是双路和四路比较器的低电压 ( 2.7V 至 5.5V ) 版本, 它们的工作电压范围为 5V 至 30V。LMV331 是单路比较器。

LMV331、LMV339 和 LMV393 是颇具成本效益的器件, 适用于在便携式消费类电子产品的电路设计中要求低电压运行、低功耗和节省空间的应用。无需消耗全部的电源电流, 这类器件便可达到或超出常见 LM339 和 LM393 器件的规格。

器件信息

| 器件型号              | 封装 ( 引脚 ) <sup>(1)</sup> | 本体尺寸 ( 标称值 ) <sup>(2)</sup> |
|-------------------|--------------------------|-----------------------------|
| LMV339<br>( 四通道 ) | SOIC (14)                | 3.91mm × 8.65mm             |
|                   | TSSOP (14)               | 4.40mm × 5.00mm             |
|                   | X2QFN (14)               | 2.00mm × 2.00mm             |
| LMV393<br>( 双通道 ) | SOIC (8)                 | 3.91mm × 4.90mm             |
|                   | TSSOP (8)                | 3.00mm × 4.40mm             |
| LMV331<br>( 单通道 ) | SC-70 (5)                | 1.25mm × 2.00mm             |
|                   | SOT-23 (5)               | 1.60mm × 2.90mm             |

- (1) 如需了解所有可用封装, 请参阅数据表末尾的可订购产品附录。  
 (2) 封装尺寸 ( 长 × 宽 ) 为标称值, 并包括引脚 ( 如适用 )



简化版原理图




## Table of Contents


|                                                        |          |                                                                  |           |
|--------------------------------------------------------|----------|------------------------------------------------------------------|-----------|
| <b>1 特性</b> .....                                      | <b>1</b> | 6.3 Feature Description.....                                     | <b>9</b>  |
| <b>2 应用</b> .....                                      | <b>1</b> | 6.4 Device Functional Modes.....                                 | <b>9</b>  |
| <b>3 说明</b> .....                                      | <b>1</b> | <b>7 Application and Implementation</b> .....                    | <b>10</b> |
| <b>4 Pin Configuration and Functions</b> .....         | <b>3</b> | 7.1 Application Information.....                                 | 10        |
| <b>5 Specifications</b> .....                          | <b>4</b> | 7.2 Typical Application.....                                     | 10        |
| 5.1 Absolute Maximum Ratings.....                      | 4        | <b>8 Power Supply Recommendations</b> .....                      | <b>12</b> |
| 5.2 ESD Ratings.....                                   | 4        | <b>9 Layout</b> .....                                            | <b>12</b> |
| 5.3 Recommended Operating Conditions.....              | 4        | 9.1 Layout Guidelines.....                                       | 12        |
| 5.4 Thermal Information.....                           | 4        | 9.2 Layout Example.....                                          | 12        |
| 5.5 Electrical Characteristics, $V_{CC+} = 2.7V$ ..... | 5        | <b>10 Device and Documentation Support</b> .....                 | <b>13</b> |
| 5.6 Switching Characteristics, $V_{CC+} = 2.7V$ .....  | 5        | 10.1 Related Links.....                                          | 13        |
| 5.7 Electrical Characteristics, $V_{CC+} = 5V$ .....   | 6        | <b>11 Trademarks</b> .....                                       | <b>13</b> |
| 5.8 Switching Characteristics, $V_{CC+} = 5V$ .....    | 6        | <b>12 静电放电警告</b> .....                                           | <b>13</b> |
| 5.9 Typical Characteristics.....                       | 7        | <b>13 术语表</b> .....                                              | <b>13</b> |
| <b>6 Detailed Description</b> .....                    | <b>9</b> | <b>14 Revision History</b> .....                                 | <b>14</b> |
| 6.1 Overview.....                                      | 9        | <b>15 Mechanical, Packaging, and Orderable Information</b> ..... | <b>15</b> |
| 6.2 Functional Block Diagram.....                      | 9        |                                                                  |           |

## 4 Pin Configuration and Functions


**LMV339 . . . D OR PW PACKAGE  
(TOP VIEW)**



**LMV339 . . . RUC PACKAGE  
(TOP VIEW)**



**LMV393 . . . D, DDU, DGK OR PW PACKAGE  
(TOP VIEW)**



**LMV331 . . . DBV OR DCK PACKAGE  
(TOP VIEW)**




**表 4-1. Pin Functions**

| PIN                                    |          |             |              |               | TYPE | DESCRIPTION                   |
|----------------------------------------|----------|-------------|--------------|---------------|------|-------------------------------|
| NAME                                   | LMV331   | LMV393      | LMV339       |               |      |                               |
|                                        | DBV, DCK | D, DGK , PW | D, PW        | RUC           |      |                               |
| 1IN - ,<br>2IN - ,<br>3IN - ,<br>4IN - | 3        | 2, 6        | 4, 6, 8, 10  | 3, 5, 7, 9    | I    | Comparator negative input pin |
| 1IN+ ,<br>2IN+ ,<br>3IN+ ,<br>4IN+     | 1        | 3, 5        | 5, 7, 9, 11  | 4, 6, 8, 10   | I    | Comparator positive input pin |
| GND                                    | 2        | 4           | 12           | 11            | I    | Ground                        |
| 1OUT,<br>2OUT,<br>3OUT,<br>4OUT        | 4        | 1, 7        | 2, 1, 14, 13 | 1, 14, 13, 12 | O    | Comparator output pin         |
| V <sub>CC</sub> +                      | 5        | 8           | 3            | 2             | I    | Supply Pin                    |

## 5 Specifications

### 5.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)<sup>(1)</sup>

|                  |                                                                           | MIN                                                          | MAX               | UNIT |
|------------------|---------------------------------------------------------------------------|--------------------------------------------------------------|-------------------|------|
| V <sub>CC</sub>  | Supply voltage <sup>(2)</sup>                                             |                                                              | 5.5               | V    |
| V <sub>ID</sub>  | Differential input voltage <sup>(3)</sup>                                 |                                                              | ±5.5              | V    |
| V <sub>I</sub>   | Input voltage range (either input)                                        | 0                                                            | V <sub>CC</sub> + | V    |
|                  | Duration of output short circuit (one amplifier) to ground <sup>(4)</sup> | At or below T <sub>A</sub> = 25°C,<br>V <sub>CC</sub> ≤ 5.5V |                   |      |
|                  |                                                                           | Unlimited                                                    |                   |      |
| T <sub>J</sub>   | Operating virtual junction temperature                                    |                                                              | 150               | °C   |
| T <sub>stg</sub> | Storage temperature range                                                 | – 65                                                         | 150               | °C   |

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* can cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under [§ 5.3](#) is not implied. Exposure to absolute-maximum-rated conditions for extended periods can affect device reliability.
- (2) All voltage values (except differential voltages and V<sub>CC</sub> specified for the measurement of I<sub>OS</sub>) are with respect to the network GND.
- (3) Differential voltages are at IN+ with respect to IN–.
- (4) Short circuits from outputs to V<sub>CC</sub> can cause excessive heating and eventual destruction.

### 5.2 ESD Ratings

|                    |                         |                                                                                          | VALUE | UNIT |
|--------------------|-------------------------|------------------------------------------------------------------------------------------|-------|------|
| V <sub>(ESD)</sub> | Electrostatic discharge | Human body model (HBM), per ANSI/ESDA/JEDEC JS-001, all pins <sup>(1)</sup>              | ±2000 | V    |
|                    |                         | Charged device model (CDM), per JEDEC specification JESD22-C101, all pins <sup>(2)</sup> | ±1000 |      |

- (1) JEDEC document JEP155 states that 500V HBM allows safe manufacturing with a standard ESD control process.
- (2) JEDEC document JEP157 states that 250V CDM allows safe manufacturing with a standard ESD control process.

### 5.3 Recommended Operating Conditions

|                  |                                          | MIN                   | MAX | UNIT |
|------------------|------------------------------------------|-----------------------|-----|------|
| V <sub>CC</sub>  | Supply voltage (single-supply operation) | 2.7                   | 5.5 | V    |
| V <sub>OUT</sub> | Output voltage                           | V <sub>CC</sub> + 0.3 |     |      |
| T <sub>A</sub>   | Operating free-air temperature           | – 40                  | 125 | °C   |

### 5.4 Thermal Information

| THERMAL METRIC <sup>(1)</sup> |                                              | LMV339  |     |      | LMV393 |     |     |     | LMV331 |     | UNIT |
|-------------------------------|----------------------------------------------|---------|-----|------|--------|-----|-----|-----|--------|-----|------|
|                               |                                              | D       | PW  | RUC  | D      | DDU | DGK | PW  | DBV    | DCK |      |
|                               |                                              | 14 PINS |     |      | 8 PINS |     |     |     | 5 PINS |     |      |
| R <sub>θJA</sub>              | Junction-to-ambient thermal resistance       | 136     | 155 | 216  | 168    | 210 | 216 | 222 | 224    | 238 | °C/W |
| R <sub>θJC(top)</sub>         | Junction-to-case (top) thermal resistance    | —       | —   | 51.3 | —      | —   | —   | —   | —      | —   |      |
| R <sub>θJB</sub>              | Junction-to-board thermal resistance         | —       | —   | 59.0 | —      | —   | —   | —   | —      | —   |      |
| ψ <sub>JT</sub>               | Junction-to-top characterization parameter   | —       | —   | 1.2  | —      | —   | —   | —   | —      | —   |      |
| ψ <sub>JB</sub>               | Junction-to-board characterization parameter | —       | —   | 59.0 | —      | —   | —   | —   | —      | —   |      |

- (1) For more information about traditional and new thermal metrics, see the *IC Package Thermal Metrics* application report, [SPRA953](#).

## 5.5 Electrical Characteristics, $V_{CC+} = 2.7V$

$V_{CC+} = 2.7V$ , GND = 0V, at specified free-air temperature (unless otherwise noted)

| PARAMETER      | TEST CONDITIONS                                         | $T_A$                         | MIN  | TYP        | MAX | UNIT              |
|----------------|---------------------------------------------------------|-------------------------------|------|------------|-----|-------------------|
| $V_{IO}$       | Input offset voltage                                    | 25°C                          |      | +0.5       | 7   | mV                |
| $\alpha_{VIO}$ | Average temperature coefficient of input offset voltage | – 40°C to 125°C               |      | 5          |     | $\mu V/^{\circ}C$ |
| $I_{IB}$       | Input bias current                                      | 25°C                          |      | 0.005      | 250 | nA                |
|                |                                                         | – 40°C to 125°C               |      |            | 400 |                   |
| $I_{IO}$       | Input offset current                                    | 25°C                          |      | 0.001      | 50  | nA                |
|                |                                                         | – 40°C to 125°C               |      |            | 150 |                   |
| $I_O$          | Output current (sinking)                                | $V_O \leq 1.5V$               | 25°C | 5          | 23  | mA                |
|                | Output Leakage Current                                  | 25°C                          |      | 0.003      |     | $\mu A$           |
|                |                                                         | – 40°C to 125°C               |      |            | 1   |                   |
| $V_{ICR}$      | Common-mode input voltage range                         | 25°C                          |      | – 0.1 to 2 |     | V                 |
| $V_{SAT}$      | Saturation voltage                                      | $I_O \leq 1.5mA$              | 25°C | 150        |     | mV                |
| $I_{CC}$       | Supply current                                          | LMV331                        | 25°C | 26         | 100 | $\mu A$           |
|                |                                                         | LMV393 (both comparators)     | 25°C | 50         | 140 |                   |
|                |                                                         | LMV339 (all four comparators) | 25°C | 100        | 200 |                   |

## 5.6 Switching Characteristics, $V_{CC+} = 2.7V$

$T_A = 25^{\circ}C$ ,  $V_{CC+} = 2.7V$ ,  $R_L = 5.1k\Omega$ , GND = 0V (unless otherwise noted)

| PARAMETER        |                                                      | TEST CONDITIONS         | TYP  | UNIT |
|------------------|------------------------------------------------------|-------------------------|------|------|
| t <sub>PHL</sub> | Propagation delay high to low level output switching | Input overdrive = 10mV  | 1000 | ns   |
|                  |                                                      | Input overdrive = 100mV | 350  |      |
| t <sub>PLH</sub> | Propagation delay low to high level output switching | Input overdrive = 10mV  | 500  | ns   |
|                  |                                                      | Input overdrive = 100mV | 400  |      |

## 5.7 Electrical Characteristics, $V_{CC+} = 5V$

$V_{CC+} = 5V$ ,  $GND = 0V$ , at specified free-air temperature (unless otherwise noted)

| PARAMETER                                                              | TEST CONDITIONS               | $T_A$           | MIN          | TYP   | MAX | UNIT              |
|------------------------------------------------------------------------|-------------------------------|-----------------|--------------|-------|-----|-------------------|
| $V_{IO}$ Input offset voltage                                          |                               | 25°C            |              | +0.5  | 7   | mV                |
|                                                                        |                               | – 40°C to 125°C |              |       | 9   |                   |
| $\alpha_{VIO}$ Average temperature coefficient of input offset voltage |                               | 25°C            |              | 5     |     | $\mu V/^{\circ}C$ |
| $I_{IB}$ Input bias current                                            |                               | 25°C            |              | 0.005 | 250 | nA                |
|                                                                        |                               | – 40°C to 125°C |              |       | 400 |                   |
| $I_{IO}$ Input offset current                                          |                               | 25°C            |              | 0.001 | 50  | nA                |
|                                                                        |                               | – 40°C to 125°C |              |       | 150 |                   |
| $I_O$ Output current (sinking)                                         | $V_O \leq 1.5V$               | 25°C            | 10           | 84    |     | mA                |
| Output Leakage Current                                                 |                               | 25°C            |              | 0.003 |     | $\mu A$           |
|                                                                        |                               | – 40°C to 125°C |              |       | 1   |                   |
| $V_{ICR}$ Common-mode input voltage range                              |                               | 25°C            | – 0.1 to 4.2 |       |     | V                 |
| $A_{VD}$ Large-signal differential voltage gain                        |                               | 25°C            | 20           | 50    |     | V/mV              |
| $V_{SAT}$ Saturation voltage                                           | $I_O \leq 4\text{ mA}$        | 25°C            |              | 150   | 400 | mV                |
|                                                                        |                               | – 40°C to 125°C |              |       | 700 |                   |
| $I_{CC}$ Supply current                                                | LMV331                        | 25°C            |              | 26    | 120 | $\mu A$           |
|                                                                        |                               | – 40°C to 125°C |              |       | 150 |                   |
|                                                                        | LMV393 (both comparators)     | 25°C            |              | 50    | 200 |                   |
|                                                                        |                               | – 40°C to 125°C |              |       | 250 |                   |
|                                                                        | LMV339 (all four comparators) | 25°C            |              | 100   | 300 |                   |
|                                                                        |                               | – 40°C to 125°C |              |       | 350 |                   |

## 5.8 Switching Characteristics, $V_{CC+} = 5V$

$T_A = 25^{\circ}C$ ,  $V_{CC+} = 5V$ ,  $R_L = 5.1k\Omega$ ,  $GND = 0V$  (unless otherwise noted)

| PARAMETER                                                      | TEST CONDITIONS         | TYP | UNIT |
|----------------------------------------------------------------|-------------------------|-----|------|
| $t_{PHL}$ Propagation delay high to low level output switching | Input overdrive = 10mV  | 600 | ns   |
|                                                                | Input overdrive = 100mV | 200 |      |
| $t_{PLH}$ Propagation delay low to high level output switching | Input overdrive = 10mV  | 450 | ns   |
|                                                                | Input overdrive = 100mV | 300 |      |

## 5.9 Typical Characteristics

Unless otherwise specified, VS = +5V, single supply, TA = 25°C




图 5-1. Supply Current vs Supply Voltage Output High




图 5-2. Supply Current vs Supply Voltage Output Low




图 5-3. Output Voltage vs Output Current




图 5-4. Input Bias Current vs Supply Voltage




图 5-5. Response Time vs Input Overdrives Negative Transition (V<sub>CC</sub>=5V)




图 5-6. Response Time vs Input Overdrives Positive Transition (V<sub>CC</sub> = 5V)

5.9 Typical Characteristics (continued)

Unless otherwise specified, VS = +5V, single supply, TA = 25°C




图 5-7. Response Time vs Input Overdrives Negative Transition (V<sub>CC</sub> = 2.7V)




图 5-8. Response Time vs Input Overdrives Positive Transition (V<sub>CC</sub> = 2.7V)


## 6 Detailed Description

### 6.1 Overview

The LMV331, LMV393 and LMV339 family of comparators have the ability to operate up to 5V on the supply pin. This standard device has proven ubiquity and versatility across a wide range of applications. This is due to its low  $I_q$  and fast response.

The open-drain output allows the user to configure the output's logic low voltage ( $V_{OL}$ ) and can be utilized to enable the comparator to be used in AND functionality.

### 6.2 Functional Block Diagram



### 6.3 Feature Description

The LMV331, LMV393 and LMV339 consists of a PNP input, whose  $V_{be}$  creates a limit on the input common mode voltage capability, allowing LMV33x to accurately function from ground to  $V_{CC} - V_{be}$  (about 700mV) differential input. This enables much head room for modern day supplies of 3.3V and 5.0V.

The output consists of an open drain NPN (pull-down or low side) transistor. The output NPN sinks current when the negative input voltage is higher than the positive input voltage and the offset voltage. The  $V_{OL}$  is resistive and scales with the output current. Please see 图 5-3 for  $V_{OL}$  values with respect to the output current.

### 6.4 Device Functional Modes

#### 6.4.1 Voltage Comparison

The LMV33x operates solely as a voltage comparator, comparing the differential voltage between the positive and negative pins and outputs a logic low or high impedance (logic high with pull-up) based on the input differential polarity.

## 7 Application and Implementation

### 备注

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes, as well as validating and testing their design implementation to confirm system functionality.

### 7.1 Application Information

LMV331, LMV393, and LMV339 typically is used to compare a single signal to a reference or two signals against each other. Many users take advantage of the open drain output to drive the comparison logic output to a logic voltage level to an MCU or logic device. The wide supply range and high voltage capability makes LMV331, LMV393, and LMV339 an excellent choice for level shifting to a higher or lower voltage.

### 7.2 Typical Application




图 7-1. Typical Application Schematic

#### 7.2.1 Design Requirements

For this design example, use the parameters listed in 表 7-1 as the input parameters.

表 7-1. Design Parameters

| DESIGN PARAMETER                             | EXAMPLE VALUE     |
|----------------------------------------------|-------------------|
| Input Voltage Range                          | 0V to 4.2V        |
| Supply Voltage                               | 2.7V to 5V        |
| Logic Supply Voltage ( $R_{PULLUP}$ Voltage) | 1V to 5V          |
| Output Current ( $V_{LOGIC}/R_{PULLUP}$ )    | 1 $\mu$ A to 20mA |
| Input Overdrive Voltage                      | 100mV             |
| Reference Voltage                            | 2.5V              |
| Load Capacitance ( $C_L$ )                   | 15pF              |

#### 7.2.2 Detailed Design Procedure

When using LMV331, LMV393, and LMV339 in a general comparator application, determine the following:

- Input Voltage Range
- Minimum Overdrive Voltage
- Output and Drive Current
- Response Time

### 7.2.2.1 Input Voltage Range

When choosing the input voltage range, the input common mode voltage range ( $V_{ICR}$ ) must be taken in to account. If operating temperature is above or below 25°C the  $V_{ICR}$  can range from 0V to  $V_{CC} - 0.7V$ . This limits the input voltage range to as high as  $V_{CC} - 0.7V$  and as low as 0V. Operation outside of this range can yield incorrect comparisons.

Below is a possible list of input voltage situation and the outcomes:

1. When both IN- and IN+ are both within the common mode range:
  - a. If IN- is higher than IN+ and the offset voltage, the output is low and the output transistor is sinking current
  - b. If IN- is lower than IN+ and the offset voltage, the output is high impedance and the output transistor is not conducting
2. When IN- is higher than common mode and IN+ is within common mode, the output is low and the output transistor is sinking current
3. When IN+ is higher than common mode and IN- is within common mode, the output is high impedance and the output transistor is not conducting
4. When IN- and IN+ are both higher than common mode, the output is low and the output transistor is sinking current

### 7.2.2.2 Minimum Overdrive Voltage

Overdrive Voltage is the differential voltage produced between the positive and negative inputs of the comparator over the offset voltage ( $V_{IO}$ ). To make an accurate comparison; the Overdrive Voltage ( $V_{OD}$ ) must be higher than the input offset voltage ( $V_{IO}$ ). Overdrive voltage can also determine the response time of the comparator, with the response time decreasing with increasing overdrive. 图 7-2 show positive and negative response times with respect to overdrive voltage.

### 7.2.2.3 Output and Drive Current

Output current is determined by the pull-up resistance ( $R_{pullup}$ ) and Vlogic voltage, refer to 图 7-1. The output current produces a output low voltage ( $V_{OL}$ ) from the comparator. In which  $V_{OL}$  is proportional to the output current. Use 图 5-3 to determine  $V_{OL}$  based on the output current.

The output current can also effect the transient response. This is explained in the next section.

### 7.2.2.4 Response Time

The transient response can be determined by the load capacitance ( $C_L$ ), load/pull-up resistance ( $R_{PULLUP}$ ) and equivalent collector-emitter resistance ( $R_{CE}$ ).

- The positive response time ( $\tau_P$ ) is approximately  $\tau_P = R_{PULLUP} \times C_L$
- The negative response time ( $\tau_N$ ) is approximately  $\tau_N = R_{CE} \times C_L$ 
  - $R_{CE}$  can be determine by taking the slope of 图 5-3 in it's linear region at the desired temperature, or by dividing the  $V_{OL}$  by  $I_{out}$

### 7.2.3 Application Curves

The following curves were generated with 5V on  $V_{CC}$  and  $V_{Logic}$ ,  $R_{PULLUP} = 5.1k\Omega$ , and 50pF scope probe.




图 7-2. Response Time for Various Overdrives (Negative Transition)

## 8 Power Supply Recommendations

For fast response and comparison applications with noisy or AC inputs, a bypass capacitor is recommended on the supply pin to reject any variation on the supply voltage. This variation cause temporary fluctuations in the comparator's input common mode range and create an inaccurate comparison.

## 9 Layout

### 9.1 Layout Guidelines

For accurate comparator applications without hysteresis, a stable power supply is necessary with minimized noise and glitches, which can affect the high level input common mode voltage range. To achieve this, add a bypass capacitor between the supply voltage and ground. This can be implemented on the positive power supply and negative supply (if available). If a negative supply is not being used, do not put a capacitor between the IC's GND pin and system ground.

### 9.2 Layout Example




图 9-1. LMV331 Layout Example

## 10 Device and Documentation Support

### 10.1 Related Links

The table below lists quick access links. Categories include technical documents, support and community resources, tools and software, and quick access to sample or buy.

**表 10-1. Related Links**

| PARTS  | PRODUCT FOLDER             | SAMPLE & BUY               | TECHNICAL DOCUMENTS        | TOOLS & SOFTWARE           | SUPPORT & COMMUNITY        |
|--------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| LMV331 | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> |
| LMV393 | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> |
| LMV339 | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> | <a href="#">Click here</a> |

## 11 Trademarks

所有商标均为其各自所有者的财产。

## 12 静电放电警告



静电放电 (ESD) 会损坏这个集成电路。德州仪器 (TI) 建议通过适当的预防措施处理所有集成电路。如果不遵守正确的处理和安装程序，可能会损坏集成电路。

ESD 的损坏小至导致微小的性能降级，大至整个器件故障。精密的集成电路可能更容易受到损坏，这是因为非常细微的参数更改都可能会导致器件与其发布的规格不相符。

## 13 术语表

**TI 术语表**      本术语表列出并解释了术语、首字母缩略词和定义。

## 14 Revision History

注：以前版本的页码可能与当前版本的页码不同

| Changes from Revision U (October 2020) to Revision V (May 2025)                                              | Page |
|--------------------------------------------------------------------------------------------------------------|------|
| • 更新了器件信息表.....                                                                                              | 1    |
| • Corrected incorrect <i>Feature Description</i> text about input voltage conditions for output sinking..... | 9    |
| <hr/>                                                                                                        |      |
| Changes from Revision T (January 2015) to Revision U (October 2020)                                          | Page |
| • 更新了整个文档中的表、图和交叉参考的编号格式.....                                                                                | 1    |
| <hr/>                                                                                                        |      |
| Changes from Revision S (January 2015) to Revision T (January 2015)                                          | Page |
| • 添加了应用、器件信息表、引脚功能表、ESD 等级表、热性能信息表、典型特性、特性说明部分、器件功能模式、应用和实施部分、电源相关建议部分、布局部分、器件和文档支持部分以及机械、封装和可订购信息部分.....    | 1    |
| • 删除了订购信息表请参阅数据表末尾的可订购产品附录.....                                                                              | 1    |
| <hr/>                                                                                                        |      |
| Changes from Revision R (May 2012) to Revision S (January 2015)                                              | Page |
| • Updated operating temperature range.....                                                                   | 4    |
| <hr/>                                                                                                        |      |
| Changes from Revision Q (April 2012) to Revision R (May 2012)                                                | Page |
| • Added RUC to marking list (table later removed in T).....                                                  | 3    |
| <hr/>                                                                                                        |      |
| Changes from Revision P (March 2012) to Revision Q (April 2012)                                              | Page |
| • Corrected the Top Side Marking for RUC package, RT_ (table removed in T).....                              | 3    |
| <hr/>                                                                                                        |      |
| Changes from Revision O (February 2012) to Revision P (March 2012)                                           | Page |
| • Corrected typo in Ordering Information Table for Top Side Marking, R9_ (table removed in T).....           | 3    |
| <hr/>                                                                                                        |      |
| Changes from Revision N (April 2011) to Revision O (February 2012)                                           | Page |
| • Changed $V_I$ in the <i>Absolute Maximum Ratings</i> from 5.5V to $V_{CC+}$ .....                          | 4    |
| <hr/>                                                                                                        |      |
| Changes from Revision M (November 2005) to Revision N (April 2011)                                           | Page |
| • 将文档格式从 Quicksilver 变更为 DocZone.....                                                                        | 1    |
| • Added RUC package pin out drawing.....                                                                     | 3    |
| <hr/>                                                                                                        |      |

## 15 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

## PACKAGING INFORMATION

| Orderable part number       | Status<br>(1) | Material type<br>(2) | Package   Pins   | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|-----------------------------|---------------|----------------------|------------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| <a href="#">LMV331IDBVR</a> | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (R1IF, R1IK)        |
| LMV331IDBVR.A               | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (R1IF, R1IK)        |
| LMV331IDBVR.B               | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (R1IF, R1IK)        |
| LMV331IDBVRE4               | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (R1IF, R1IK)        |
| LMV331IDBVRG4               | Active        | Production           | SOT-23 (DBV)   5 | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (R1IF, R1IK)        |
| <a href="#">LMV331IDBVT</a> | Obsolete      | Production           | SOT-23 (DBV)   5 | -                     | -           | Call TI                              | Call TI                           | -40 to 125   | (R1IF, R1IK)        |
| <a href="#">LMV331IDCKR</a> | Active        | Production           | SC70 (DCK)   5   | 3000   LARGE T&R      | Yes         | NIPDAU   NIPDAUAG                    | Level-1-260C-UNLIM                | -40 to 125   | (R2F, R2K, R2R)     |
| LMV331IDCKR.A               | Active        | Production           | SC70 (DCK)   5   | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (R2F, R2K, R2R)     |
| LMV331IDCKR.B               | Active        | Production           | SC70 (DCK)   5   | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (R2F, R2K, R2R)     |
| LMV331IDCKRE4               | Active        | Production           | SC70 (DCK)   5   | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (R2F, R2K, R2R)     |
| LMV331IDCKRG4               | Active        | Production           | SC70 (DCK)   5   | 3000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | (R2F, R2K, R2R)     |
| <a href="#">LMV331IDCKT</a> | Obsolete      | Production           | SC70 (DCK)   5   | -                     | -           | Call TI                              | Call TI                           | -40 to 125   | (R2F, R2R)          |
| <a href="#">LMV339ID</a>    | Obsolete      | Production           | SOIC (D)   14    | -                     | -           | Call TI                              | Call TI                           | -40 to 125   | LMV339I             |
| <a href="#">LMV339IDR</a>   | Active        | Production           | SOIC (D)   14    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LMV339I             |
| LMV339IDR.A                 | Active        | Production           | SOIC (D)   14    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LMV339I             |
| LMV339IDRG4                 | Active        | Production           | SOIC (D)   14    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LMV339I             |
| LMV339IDRG4.A               | Active        | Production           | SOIC (D)   14    | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | LMV339I             |
| <a href="#">LMV339IPW</a>   | Obsolete      | Production           | TSSOP (PW)   14  | -                     | -           | Call TI                              | Call TI                           | -40 to 125   | MV339I              |
| <a href="#">LMV339IPWR</a>  | Active        | Production           | TSSOP (PW)   14  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | MV339I              |
| LMV339IPWR.A                | Active        | Production           | TSSOP (PW)   14  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | MV339I              |
| LMV339IPWR.B                | Active        | Production           | TSSOP (PW)   14  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | MV339I              |
| LMV339IPWRG4                | Active        | Production           | TSSOP (PW)   14  | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | MV339I              |
| <a href="#">LMV393IDDUR</a> | Obsolete      | Production           | VSSOP (DDU)   8  | -                     | -           | Call TI                              | Call TI                           | -40 to 125   | RABR                |
| <a href="#">LMV393IDGKR</a> | Active        | Production           | VSSOP (DGK)   8  | 2500   LARGE T&R      | Yes         | NIPDAU   SN                          | Level-1-260C-UNLIM                | -40 to 125   | (R9B, R9Q, R9R)     |
| LMV393IDGKR.A               | Active        | Production           | VSSOP (DGK)   8  | 2500   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | (R9B, R9Q, R9R)     |
| LMV393IDGKR.B               | Active        | Production           | VSSOP (DGK)   8  | 2500   LARGE T&R      | Yes         | SN                                   | Level-1-260C-UNLIM                | -40 to 125   | (R9B, R9Q, R9R)     |
| <a href="#">LMV393IDR</a>   | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | MV393I              |
| LMV393IDR.A                 | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | MV393I              |
| LMV393IDR.B                 | Active        | Production           | SOIC (D)   8     | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | MV393I              |

| Orderable part number       | Status<br>(1) | Material type<br>(2) | Package   Pins | Package qty   Carrier | RoHS<br>(3) | Lead finish/<br>Ball material<br>(4) | MSL rating/<br>Peak reflow<br>(5) | Op temp (°C) | Part marking<br>(6) |
|-----------------------------|---------------|----------------------|----------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| <a href="#">LMV393IDRG4</a> | Active        | Production           | SOIC (D)   8   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | MV393I              |
| LMV393IDRG4.A               | Active        | Production           | SOIC (D)   8   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | MV393I              |
| LMV393IDRG4.B               | Active        | Production           | SOIC (D)   8   | 2500   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | MV393I              |
| <a href="#">LMV393IPW</a>   | Obsolete      | Production           | TSSOP (PW)   8 | -                     | -           | Call TI                              | Call TI                           | -40 to 125   | MV393I              |
| <a href="#">LMV393IPWR</a>  | Active        | Production           | TSSOP (PW)   8 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | MV393I              |
| LMV393IPWR.A                | Active        | Production           | TSSOP (PW)   8 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | MV393I              |
| LMV393IPWRG4                | Active        | Production           | TSSOP (PW)   8 | 2000   LARGE T&R      | Yes         | NIPDAU                               | Level-1-260C-UNLIM                | -40 to 125   | MV393I              |

<sup>(1)</sup> **Status:** For more details on status, see our [product life cycle](#).

<sup>(2)</sup> **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

<sup>(3)</sup> **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

<sup>(4)</sup> **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

<sup>(5)</sup> **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

<sup>(6)</sup> **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


**OTHER QUALIFIED VERSIONS OF LMV331, LMV393 :**

- Automotive : [LMV331-Q1](#), [LMV393-Q1](#)

NOTE: Qualified Version Definitions:

- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects


## TAPE AND REEL INFORMATION



\*All dimensions are nominal

| Device      | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|-------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| LMV331IDBVR | SOT-23       | DBV             | 5    | 3000 | 180.0              | 8.4                | 3.17    | 3.23    | 1.37    | 4.0     | 8.0    | Q3            |
| LMV331IDBVR | SOT-23       | DBV             | 5    | 3000 | 178.0              | 9.0                | 3.23    | 3.17    | 1.37    | 4.0     | 8.0    | Q3            |
| LMV331IDBVR | SOT-23       | DBV             | 5    | 3000 | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| LMV331IDCKR | SC70         | DCK             | 5    | 3000 | 178.0              | 9.0                | 2.4     | 2.5     | 1.2     | 4.0     | 8.0    | Q3            |
| LMV331IDCKR | SC70         | DCK             | 5    | 3000 | 178.0              | 9.0                | 2.4     | 2.5     | 1.2     | 4.0     | 8.0    | Q3            |
| LMV339IDR   | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| LMV339IDRG4 | SOIC         | D               | 14   | 2500 | 330.0              | 16.4               | 6.5     | 9.0     | 2.1     | 8.0     | 16.0   | Q1            |
| LMV339IPWR  | TSSOP        | PW              | 14   | 2000 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| LMV393IDGKR | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 5.25    | 3.35    | 1.25    | 8.0     | 12.0   | Q1            |
| LMV393IDGKR | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 5.3     | 3.3     | 1.3     | 8.0     | 12.0   | Q1            |
| LMV393IDR   | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LMV393IDR   | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LMV393IDRG4 | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LMV393IDRG4 | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| LMV393IPWR  | TSSOP        | PW              | 8    | 2000 | 330.0              | 12.4               | 7.0     | 3.6     | 1.6     | 8.0     | 12.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device      | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|-------------|--------------|-----------------|------|------|-------------|------------|-------------|
| LMV331IDBVR | SOT-23       | DBV             | 5    | 3000 | 205.0       | 200.0      | 33.0        |
| LMV331IDBVR | SOT-23       | DBV             | 5    | 3000 | 180.0       | 180.0      | 18.0        |
| LMV331IDBVR | SOT-23       | DBV             | 5    | 3000 | 210.0       | 185.0      | 35.0        |
| LMV331IDCKR | SC70         | DCK             | 5    | 3000 | 180.0       | 180.0      | 18.0        |
| LMV331IDCKR | SC70         | DCK             | 5    | 3000 | 180.0       | 180.0      | 18.0        |
| LMV339IDR   | SOIC         | D               | 14   | 2500 | 353.0       | 353.0      | 32.0        |
| LMV339IDRG4 | SOIC         | D               | 14   | 2500 | 353.0       | 353.0      | 32.0        |
| LMV339IPWR  | TSSOP        | PW              | 14   | 2000 | 353.0       | 353.0      | 32.0        |
| LMV393IDGKR | VSSOP        | DGK             | 8    | 2500 | 366.0       | 364.0      | 50.0        |
| LMV393IDGKR | VSSOP        | DGK             | 8    | 2500 | 370.0       | 355.0      | 55.0        |
| LMV393IDR   | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LMV393IDR   | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LMV393IDRG4 | SOIC         | D               | 8    | 2500 | 340.5       | 338.1      | 20.6        |
| LMV393IDRG4 | SOIC         | D               | 8    | 2500 | 353.0       | 353.0      | 32.0        |
| LMV393IPWR  | TSSOP        | PW              | 8    | 2000 | 353.0       | 353.0      | 32.0        |




# EXAMPLE BOARD LAYOUT


DBV0005A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:15X



SOLDER MASK DETAILS

4214839/K 08/2024

NOTES: (continued)


6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DBV0005A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR




SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:15X

4214839/K 08/2024

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.


DGK0008A



# PACKAGE OUTLINE

## VSSOP - 1.1 mm max height

SMALL OUTLINE PACKAGE



4214862/A 04/2023

### NOTES:

PowerPAD is a trademark of Texas Instruments.


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-187.

# EXAMPLE BOARD LAYOUT



DGK0008A

<sup>TM</sup> VSSOP - 1.1 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE: 15X



SOLDER MASK DETAILS

4214862/A 04/2023

NOTES: (continued)


6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.
8. Vias are optional depending on application, refer to device data sheet. If any vias are implemented, refer to their locations shown on this view. It is recommended that vias under paste be filled, plugged or tented.
9. Size of metal pad may vary due to creepage requirement.

## EXAMPLE STENCIL DESIGN

DGK0008A

<sup>TM</sup> VSSOP - 1.1 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
SCALE: 15X


4214862/A 04/2023

NOTES: (continued)


11. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
12. Board assembly site may have different recommendations for stencil design.

## DDU (R-PDSO-G8)


## PLASTIC SMALL-OUTLINE PACKAGE



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body dimensions do not include mold flash or protrusion.
  - D. Falls within JEDEC MO-187 variation CA.

**D0014A****PACKAGE OUTLINE****SOIC - 1.75 mm max height**

SMALL OUTLINE INTEGRATED CIRCUIT



4220718/A 09/2016

**NOTES:**


1. All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm, per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.43 mm, per side.
5. Reference JEDEC registration MS-012, variation AB.

# EXAMPLE BOARD LAYOUT



D0014A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



LAND PATTERN EXAMPLE  
SCALE:8X



SOLDER MASK DETAILS

4220718/A 09/2016

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

D0014A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT




SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:8X

4220718/A 09/2016

NOTES: (continued)



8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.



4214834/G 11/2024

## NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. Reference JEDEC MO-203.
4. Support pin may differ or may not be present.
5. Lead width does not comply with JEDEC.
6. Body dimensions do not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.25mm per side



4214834/G 11/2024

NOTES: (continued)

7. Publication IPC-7351 may have alternate designs.
8. Solder mask tolerances between and around signal pads can vary based on board fabrication site.



SOLDER PASTE EXAMPLE  
BASED ON 0.125 THICK STENCIL  
SCALE:18X

4214834/G 11/2024

NOTES: (continued)

9. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
10. Board assembly site may have different recommendations for stencil design.



## PACKAGE OUTLINE

**SOIC - 1.75 mm max height**

SMALL OUTLINE INTEGRATED CIRCUIT




1. Linear dimensions are in inches [millimeters]. Dimensions in parenthesis are for reference only. Controlling dimensions are in inches. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed .006 [0.15] per side.
4. This dimension does not include interlead flash.
5. Reference JEDEC registration MS-012, variation AA.

# EXAMPLE BOARD LAYOUT


D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:8X



SOLDER MASK DETAILS

4214825/C 02/2019

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT





SOLDER PASTE EXAMPLE  
BASED ON .005 INCH [0.125 MM] THICK STENCIL  
SCALE:8X

4214825/C 02/2019

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.



4220202/B 12/2023

## NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153.

# EXAMPLE BOARD LAYOUT



PW0014A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE: 10X



SOLDER MASK DETAILS

4220202/B 12/2023

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

# EXAMPLE STENCIL DESIGN

PW0014A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE: 10X

4220202/B 12/2023

NOTES: (continued)




8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.



## PACKAGE OUTLINE

## TSSOP - 1.2 mm max height

## SMALL OUTLINE PACKAGE



4221848/A 02/2015

NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-153, variation AA.

# EXAMPLE BOARD LAYOUT



PW0008A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
SCALE:10X



SOLDER MASK DETAILS  
NOT TO SCALE

4221848/A 02/2015

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

PW0008A

TSSOP - 1.2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:10X

4221848/A 02/2015

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## GENERIC PACKAGE VIEW


**RUC 14**

**X2QFN - 0.4 mm max height**

2 x 2, 0.4 mm pitch

PLASTIC QUAD FLATPACK - NO LEAD

This image is a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.



4229871/A

## 重要通知和免责声明

TI“按原样”提供技术和可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证没有瑕疵且不做任何明示或暗示的担保，包括但不限于对适销性、与某特定用途的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任：(1) 针对您的应用选择合适的 TI 产品，(2) 设计、验证并测试您的应用，(3) 确保您的应用满足相应标准以及任何其他安全、安保法规或其他要求。

这些资源如有变更，恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的相关应用。严禁以其他方式对这些资源进行复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。对于因您对这些资源的使用而对 TI 及其代表造成的任何索赔、损害、成本、损失和债务，您将全额赔偿，TI 对此概不负责。

TI 提供的产品受 [TI 销售条款](#)、[TI 通用质量指南](#) 或 [ti.com](#) 上其他适用条款或 TI 产品随附的其他适用条款的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。除非德州仪器 (TI) 明确将某产品指定为定制产品或客户特定产品，否则其产品均为按确定价格收入目录的标准通用器件。

TI 反对并拒绝您可能提出的任何其他或不同的条款。

版权所有 © 2026，德州仪器 (TI) 公司

最后更新日期：2025 年 10 月