	BOM-Bidirectional(001).xls							
	ted: 10/7/2015 10:51:40 AM							
	\$Rev:: Bidirection	\$ onal Converter - T	IDA-00653					
Designator	Quantity	Value	Description	PackageReference	PartNumber	Manufacturer	Alternate PartNumber	Alternate Manufacturer
!PCB C1	1	3300pF	Printed Circuit Board CAP, CERM, 3300pF, 100V, +/-5%, X7R, 0603	0603	XX#### 06031C332JAT2A	Any AVX	-	-
C2, C8, C11	3	10uF	CAP, CERM, 10uF, 16V, +/-20%, X5R, 0805	0805	0805YD106MAT2A	AVX		
C3 C4, C28,	6	0.1uF 0.1uF	CAP, CERM, 0.1uF, 50V, +/-10%, X7R, 0603 CAP, CERM, 0.1uF, 25V, +/-5%, X7R, 0603	0603 0603	06035C104KAT2A 06033C104JAT2A	AVX AVX		
C91, C93, C95, C97								
C5, C114 C6	1	100pF 2.2uF	CAP, CERM, 100pF, 50V, +/-5%, C0G/NP0, 0603 CAP, CERM, 2.2uF, 100V, +/-10%, X7R, 1206_190	0603 1206_190	C0603C101J5GAC GRM31CR72A225KA73	Kemet MuRata		
C7	1	0.47uF	CAP, CERM, 0.47uF, 100V, +/-10%, X7R, 1206	1206	L C3216X7R2A474K	TDK		
C9, C61, C70, C79,	9	2.2uF	CAP, CERM, 2.2uF, 16V, +/-10%, X5R, 0805	0805	0805YD225KAT2A	AVX		
C88, C99, C100,								
C101, C102 C10	1	100pF	CAP, CERM, 100pF, 50V, +/-5%, C0G/NP0, 0603	0603	06035A101JAT2A	AVX		
C12	1	10uF	CAP, CERM, 10uF, 25V, +/-10%, X5R, 0805	0805	C2012X5R1E106K125A B	TDK		
C13 C14, C15	1 2	10uF 33pF	CAP, CERM, 10uF, 6.3V, +/-20%, X5R, 0603 CAP, CERM, 33pF, 100V, +/-5%, COG/NP0, 0603	0603 0603	C0603C106M9PACTU 06031A330JAT2A	Kemet AVX		
C16, C25, C27, C63,	7	0.01uF	CAP, CERM, 0.01uF, 100V, +/-5%, X7R, 0603	0603	06031C103JAT2A	AVX		
C72, C81, C115								
C17, C20,	3	1uF	CAP, CERM, 1uF, 16V, +/-10%, X5R, 0603	0603	C0603C105K4PACTU	Kemet		
C23 C18, C19,	5	0.1uF	CAP, CERM, 0.1uF, 16V, +/-5%, X7R, 0603	0603	0603YC104JAT2A	AVX		
C21, C24, C90	-	2 205	CAD CERM 2 245 401/ 1/400/ VED 2000	0603	Cocoococivanacti	Komot		
C22, C71, C80, C89,	5	2.2uF	CAP, CERM, 2.2uF, 10V, +/-10%, X5R, 0603	0603	C0603C225K8PACTU	Kemet		
C94 C26, C103	2	0.022uF	CAP, CERM, 0.022uF, 25V, +/-10%, X7R, 0603	0603		Kemet		
C29, C30, C31	3	2.2uF	CAP, CERM, 2.2uF, 6.3V, +/-10%, X5R, 0603	0603		Kemet		
C33 C37, C38,	8	100pF 22uF	CAP, CERM, 100pF, 25V, +/-10%, X7R, 0603 CAP, CERM, 22uF, 50V, +/-20%, X5R, 6x5x5mm	0603 6x5x5mm	06033C101KAT2A CKG57NX5R1H226M50	TDK		
C40, C41, C49, C50,					0JH			
C52, C53 C39	1	0.1uF	CAP, CERM, 0.1uF, 25V, +/-10%, X7R, 0603	0603	GRM188R71E104KA01	MuRata		
C39, C45,	4	1000pF	CAP, CERM, 1000pF, 100V, +/-5%, X7R, 0603	0603	D 06031C102JAT2A	AVX		
C51, C57 C42, C54,	8	10uF	CAP, CERM, 10uF, 100V, +/-20%, X7S, 2220	2220	C5750X7S2A106M	TDK		
C64, C66, C73, C75,								
C82, C84 C43, C46,	4	1uF	CAP, CERM, 1uF, 16V, +/-10%, X7R, 0805	0805	B37941K9105K62	EPCOS Inc		
C55, C58 C44, C56,	16	47uF	CAP, CERM, 47uF, 16V, +/-20%, X5R, 1210	1210	GRM32ER61C476ME15	MuRata		
C65, C67, C74, C76,					L			
C83, C85, C116,								
C117, C118,								
C119, C120,								
C121, C122, C123								
C47	1	330uF	CAP, AL, 330uF, 100V, +/-20%, ohm, SMD	MN0	EMVE101GTR331MMN 0S	Nippon Chemi-Con		
C48	1	470uF	CAP, AL, 470uF, 25V, +/-20%, ohm, SMD	JA0	EMVA250ADA471MJA0 G	Nippon Chemi-Con		
C59, C68, C77, C86	4	330pF	CAP, CERM, 330pF, 50V, +/-5%, C0G/NP0, 0603	0603	06035A331JAT2A	AVX		
C60, C69, C78, C87	4	0.1uF	CAP, CERM, 0.1uF, 25V, +/-10%, X7R, 0603	0603	06033C104KAT2A	AVX		
C62	1	4.7uF	CAP, CERM, 4.7uF, 25V, +/-10%, X5R, 0805	0805	C2012X5R1E475K125A B	TDK		
C104 C106,	1 4	22pF 1uF	CAP, CERM, 22pF, 50V, +/-5%, C0G/NP0, 0603 CAP, CERM, 1 µF, 25 V, +/- 10%, X7R, 0603_095	0603 0603_095	06035A220JAT2A C0603C105K3RACTU	AVX Kemet		
C108, C109, C112	7		ονι , σετιίκ, τ μι , 25 v, τη τουο, χετι, σσσσ_σσσ	0000_000		remer		
C107, C110,	4	1000pF	CAP, CERM, 1000 pF, 50 V, +/- 10%, X7R, 0603	0603	C0603X102K5RACTU	Kemet		
C111, C113 D1, D3, D4	3	200V	Diode, Switching, 200V, 0.2A, SOT-23	SOT-23	BAS21-7-F	Diodes Inc.		
D1, D3, D4 D2, D7, D16	3	Red	LED, Red, SMD	LED_0805	LTST-C170KRKT	Lite-On		
D5, D6, D17	3	40V	Diode, Schottky, 40 V, 0.5 A, SOD-123	SOD-123	MBR0540T1G	ON Semiconductor		
D8, D9,	8	12V	Diode, Zener, 12V, 500mW, SOD-123	SOD-123	MMSZ4699-V	Vishay-Semiconductor		
D10, D11, D12, D14,								
D15, D18 D13, D19,	8	15V	Diode, Schottky, 15 V, 1 A, DO-216-AA	DO-216-AA	UPS115UE3/TR7	Microsemi		
D20, D21, D22, D23,								
D24, D25 FID1, FID2,	3		Fiducial mark. There is nothing to buy or mount.	Fiducial	N/A	N/A		
FID3 H1, H2, H3,	7		Machine Screw, Round, #4-40 x 1/4, Nylon, Philips	Screw	NY PMS 440 0025 PH	B&F Fastener Supply		
H4, H5, H6, H7			panhead					

Designator	Quantity	Value	Description	PackageReference	PartNumber	Manufacturer	Alternate PartNumber	Alternate Manufacturer
J1	1		Header (shrouded), 100mil, 5x2, Gold, TH	5x2 Shrouded header	5103308-1	TE Connectivity		
J2, J3, J4, J5, J6, J7	6		Connector Lug, wire range #6 - 4/0, 600V	Connector Lug, 1.075x0.45x0.45 inch	90562	Morris Products		
J8, J9, J11	3		Header,2x1, 100mil, TH	Header, 2x1, 100mil,	22-27-2021	Molex		
J10	1		Header, 2x1, 100mil, SMT	TH Header, 2x1, 100mil,	800-10-002-10-001000	Mill-Max		
				TH				
J12	1		Header, TH, 100mil, 4x1, Gold plated, 230 mil above insulator	4x1 Header	TSW-104-07-G-S	Samtec		
L1, L2	2	1uH	Inductor, Shielded, Composite, 1uH, 57.5A, 0.000929	15.2x8x16.2mm	XAL1580-102MEB	Coilcraft		
L3, L4, L5,	4	4.7uH	ohm, SMD Inductor, Shielded E Core, Ferrite, 4.7 μH, 30 A,	29.7x15.36x27.94mm	SED2015H 472KI	Coilcraft		
L3, L4, L3, L6	4	4.7 011	0.00186 ohm, SMD	29.7 X 13.30X27.9411111	3LK291311-472KL	Colician		
LBL1	1		Thermal Transfer Printable Labels, 0.650" W x 0.200" H		THT-14-423-10	Brady	-	-
Q1	1	-20V	10,000 per roll MOSFET, P-CH, -20V, -2.4A, SOT-23	0.200"W SOT-23	FDN302P	Fairchild Semiconductor		None
Q4, Q7, Q8,	8	30V	MOSFET, N-CH, 30V, 51A, SON 5x6mm	SON 5x6mm	CSD17570Q5B	Texas Instruments		None
Q9, Q20, Q26, Q30,								
Q39								
Q5, Q6, Q18, Q22,	8	100V	MOSFET, N-CH, 100V, 1.7mOhm, DDPAK-7	DDPAK-7	IPB017N10N5	Infineon Technologies		None
Q28, Q32,								
Q38, Q42 Q11, Q14	2	601/	MOSEET NICH 60V 0.24A SOT 22	SOT 22	2N7002E-T1-E3	Viehov Ciliooniy		None
Q11, Q14 Q15, Q25,	4	60V -100V	MOSFET, N-CH, 60V, 0.24A, SOT-23 MOSFET, P-CH, -100V, -0.6A, SOT-23	SOT-23 SOT-23	ZXMP10A13FTA	Vishay-Siliconix Diodes Inc.		None None
Q35, Q45	•	20.1/	Transister DND 20 V 40 A CMD 2	CMD 9	ECHOLOG TI LI	ON Coming a direct		
Q16, Q17, Q24, Q27,	8	30 V	Transistor, PNP, 30 V, 12 A, SMD-8	SMD-8	ECH8102-TL-H	ON Semiconductor		
Q36, Q37,								
Q46, Q47 R1, R16	2	330	RES, 330 ohm, 1%, 0.1W, 0603	0603	RC0603FR-07330RL	Yageo America		
R2	1	39.0k	RES, 39.0k ohm, 1%, 0.1W, 0603	0603	RC0603FR-0739KL	Yageo America		
R3 R4	1	150k/1% 120k	RES, 150k ohm, 1%, 0.1W, 0603 RES, 120k ohm, 1%, 0.1W, 0603	0603 0603	CRCW0603150KFKEA RC0603FR-07120KL	Vishay-Dale Yageo America		
R5, R122	2	49.9	RES, 49.9 ohm, 1%, 0.1W, 0603	0603	CRCW060349R9FKEA	Vishay-Dale		
R6 R7, R118	2	27.0k 10.0k	RES, 27.0k ohm, 1%, 0.1W, 0603 RES, 10.0k ohm, 1%, 0.1W, 0603	0603 0603	RC0603FR-0727KL CRCW060310K0FKEA	Yageo America Vishay-Dale		
R8	1	1k_1%	RES, 1.0k ohm, 5%, 0.1W, 0603	0603	CRCW060310K0FKEA	Vishay-Dale Vishay-Dale		
R9	11	330	RES, 330, 5%, 0.1 W, 0603	0603	CRCW0603330RJNEA	Vishay-Dale		
R10 R11	1	560 3.0k	RES, 560 ohm, 1%, 0.1W, 0603 RES, 3.0k ohm, 5%, 0.1W, 0603	0603 0603	RC0603FR-07560RL CRCW06033K00JNEA	Yageo America Vishay-Dale		
R12, R112,	3	100k	RES, 100 k, 5%, 0.1 W, 0603	0603	CRCW0603100KJNEA	Vishay-Dale		
R116 R13, R14	2	1.50k	RES, 1.50k ohm, 0.1%, 0.1W, 0603	0603	RG1608P-152-B-T5	Susumu Co Ltd		
R15, R20,	5	0	RES, 0 ohm, 5%, 0.1W, 0603	0603	MCR03EZPJ000	Rohm		
R21, R22, R23								
R17, R111,	5	1.00k	RES, 1.00k ohm, 1%, 0.1W, 0603	0603	CRCW06031K00FKEA	Vishay-Dale		
R115, R117, R119								
R19, R38,	6	1.0k	RES, 1.0k ohm, 5%, 0.1W, 0603	0603	CRCW06031K00JNEA	Vishay-Dale		
R124, R125,								
R126, R127								
R24, R26	2	100	RES, 100 ohm, 1%, 0.1W, 0603	0603	CRCW0603100RFKEA ERJ-M1WTF2M0U	Vishay-Dale		
R27, R36, R52, R57,	8	0.002	RES, 0.002, 1%, 1 W, 2512	2512	ERJ-IVITWTF2IVIUU	Panasonic		
R71, R76,								
R90, R95 R28	1	33.0k	RES, 33.0 k, 1%, 0.1 W, 0603	0603	CRCW060333K0FKEA	Vishay-Dale		
R29	1	8.06k	RES, 8.06 k, 1%, 0.1 W, 0603	0603	CRCW06038K06FKEA	Vishay-Dale		
R30, R39, R53, R59,	8	10.0k	RES, 10.0k ohm, 0.1%, 0.1W, 0603	0603	RG1608P-103-B-T5	Susumu Co Ltd		
R72, R78,								
R91, R97 R33	1	1.10k	RES, 1.10 k, 1%, 0.1 W, 0603	0603	RC0603FR-071K1L	Yageo America		
R34, R41,	8	10.0k	RES, 10.0 k, 1%, 0.1 W, 0603	0603	CRCW060310K0FKEA	Vishay-Dale		
R56, R63, R75, R82,								
R94, R101								
R35 R40, R43,	13	1.00k 1.0k_1%	RES, 1.00 k, 1%, 0.1 W, 0603 RES, 1.0k ohm, 5%, 0.1W, 0603	0603 0603	CRCW06031K00FKEA CRCW06031K00JNEA	Vishay-Dale Vishay-Dale		
R45, R46,	13	1.UK_1/0	1.20, 1.0k 01111, 070, 0.119, 0000	0000	CACAAOOO INOUNEA	Violity-Dale		
R61, R64, R65, R80,								
R65, R80, R83, R84,								
R99, R102,								
R103 R42, R60,	4	120	RES, 120, 5%, 0.1 W, 0603	0603	CRCW0603120RJNEA	Vishay-Dale		
R79, R98						-		
R43, R135 R44, R47,	2 12	0 26.1k	RES, 0 ohm, 5%, 0.125W, 0805 RES, 26.1k ohm, 1%, 0.1W, 0603	0805 0603	CRCW08050000Z0EA CRCW060326K1FKEA	Vishay-Dale Vishay-Dale		
R49, R62,								
R66, R68, R81, R85,								
R87, R100,								
R104, R106 R48, R67,	4	40.2k	RES, 40.2k ohm, 1%, 0.1W, 0603	0603	CRCW060340K2FKEA	Vishay-Dale		
R86, R105						,		
R51, R70, R89, R108	4	1.64k_1%	RES, 1.65k ohm, 1%, 0.1W, 0603	0603	CRCW06031K65FKEA	Vishay-Dale		]
R109,	4	2.00k	RES, 2.00k ohm, 1%, 0.1W, 0603	0603	CRCW06032K00FKEA	Vishay-Dale		
R110,								
R113, R114 R120	1	0	RES, 0 ohm, 5%, 0.1W, 0603	0603	ERJ-3GEY0R00V	Panasonic		
R121	1	31.6k_1%	RES, 31.6k ohm, 1%, 0.1W, 0603	0603	CRCW060331K6FKEA	Vishay-Dale		
R128 R130	1	75.0 10.0	RES, 75.0, 1%, 0.1 W, 0603 RES, 10.0 ohm, 1%, 0.1W, 0603	0603 0603	CRCW060375R0FKEA CRCW060310R0FKEA	Vishay-Dale Vishay-Dale		
S1	1		Switch, Push Button, SMD	2.9x2x3.9mm SMD	SKRKAEE010	Alps		
T1	11	60 uH	xfmr, ?0%	12x12.5 mm	750342460	WURTH ELEKTRONIK		

Designator			Description	PackageReference		Manufacturer	Alternate PartNumber	Alternate Manufacturer
TP1, TP2,	55	White	Test Point, Miniature, White, TH	White Miniature	5002	Keystone	1	1
TP4, TP5, TP6, TP7,	1 1	1	'	Testpoint			•	1
TP6, TP7,	1 '	1	'	1				Ι,
TP10, TP11,	1 1	1	'	1			•	1
TP13, TP14,		1	'	1			•	1
TP15, TP16,		1	'	1			•	1
TP17, TP18,	,	1	'	1			•	1
TP19, TP20,	,	1	'	1			•	1
TP21, TP22,		1	'	1			•	1
TP25, TP26,		1	'	1			•	1 [ '
TP25, TP26, TP27, TP28,		1	'	1			•	1
TP27, TP28, TP29, TP31,		1	'	1			•	1
TP32, TP33,		1	'	1			•	1
TP35, TP36,	,	1	'	1			•	1
TP37, TP38,	,	1	'	1			•	1
TP39, TP40,		1	'	1			•	1
TP41, TP42,		1		1			!	
TP43, TP44, TP45, TP46,		1	'	1			•	1
TP45, TP46, TP47, TP48,		1	'	1			•	1 1
TP49, TP50,		1	'	1			1	1
TP51, TP52,	,	1	'	1			•	1
TP53, TP55,	,	1	'	1			•	1 1
TP56, TP57,		1	'	1			1	1 1
TP58, TP59,	1 1	1	'	1			•	1
TP60	1 1	1	'	1			1	1
<b> </b>   '	1 1	1	'	1			1	1
<b>4</b>   '	1 1	1	'	1			•	1
<u>_</u> '	1'	1'	<u> </u>	1'			'	<u></u> _'
TP3	1	SMT	Test Point, Compact, SMT		5016	Keystone		
U1	1	LM34927MR	IC, Integrated Secondary Side Bias Regulator	Compact PSOP	LM34927MR	<sub>T1</sub>	4	None
U1 U2	1 1		IC, Integrated Secondary Side Bias Regulator FIXED LOW-DROPOUT VOLTAGE REGULATOR,	DCY0003A	TLV1117-33IDCY	Texas Instruments	<u> </u>	None
52	( ' '		DCY0003A	DCTOOOSA	ILVIII7-001D01	Texas monuments		None
U3	1		UCD3138128PFC, PFC0080	PFC0080A	UCD3138128PFC	Texas Instruments		None
U4, U6, U8,	4	UCC2721xDRM	IC, 120V Boot, 4A Peak, High Frequency High-Side Low		UCC2721xDRM	TI		None
U10	لبب	<u> </u>	Side Driver		4	4	4	<u> </u>
U5	1	1		DDA0008C	OPA2211AIDDA	Texas Instruments	Equivalent	Texas Instruments
<b>4</b>	1 1	1	Amplifier, 4.5 to 36 V, -40 to 125 degC, 8-pin SOP (DDA0008C), Green (RoHS & no Sb/Br)	1			1	1
U7, U9, U11	3	<del></del>		D0008A	OPA211AID	Texas Instruments	Equivalent	Texas Instruments
07, 00, 0	1	1	Amplifier, 4.5 to 36 V, -40 to 125 degC, 8-pin SOIC	Doodort	OF AZT TAILS	Texas monuments	Equivalent	Texas monuments
4 L	('	1'	(D0008A), Green (RoHS & no Sb/Br)	1				
U12	1		40-ns, microPOWER, Push-Pull Output Comparators,	D0008A	TLV3202AID	Texas Instruments		None
<b>4</b>		<u> </u>	D0008A	<b></b> '			<u> </u>	<u> </u>
U13	1	<b></b>		DBV0005A	SN74AHC1G08DBV	Texas Instruments	4	Texas Instruments
U14	1	<del>                                     </del>		DRL0006A	SN74LVC2G34DRL REF1112AIDBZT	Texas Instruments	- · -1	None Toyon Instruments
U15, U16, U17, U18	4	1	1 uA Shunt Voltage Reference, 1.25 V, 10 ppm / degC, 5 mA, -40 to 85 degC, 3-pin SOT-23 (DBZ), Green	DBZ0003A	REF111ZAIDDZ1	Texas Instruments	Equivalent	Texas Instruments
617, 5.5	1 '	1	(RoHS & no Sb/Br)	1				
U19	1			D0008A	SN65HVD233D	Texas Instruments	Equivalent	Texas Instruments
<b>4</b>   ' !	1 1	1	6 mA, -40 to 125 degC, 8-pin SOIC (D), Green (RoHS &				- q	
<i>i</i>	<u> </u>		no Sb/Br)				<u> </u>	
XF1, XF3,	4		FuseHolder	780x320x345mil	3587	Keystone		
XF5, XF7		1		1,,,,,	3000 A 000 IA TOA	1107		
C32, C34, C35, C36	0	22pF	CAP, CERM, 22pF, 50V, +/-5%, C0G/NP0, 0603	0603	06035A220JAT2A	AVX	!	
C35, C36	0	330pF	CAP, CERM, 330pF, 100V, +/-5%, X7R, 0603	0603	06031C331JAT2A	AVX	<del>                                     </del>	<del> </del>
Q2, Q3,			MOSFET, N-CH, 60V, 0.24A, SOT-23	SOT-23	2N7002E-T1-E3	Vishay-Siliconix	1	None
Q12, Q23,	1 1	1 '	100. 21,11 01., 11., 11	1	21 0022	Violity C	•	1105
Q34, Q43	1'	l'	'	l	<u> </u>			
<i>1</i> ——			· · · · · · · · · · · · · · · · · · ·					

Notes:

Unless otherwise noted in the Alternate PartNumber and/or Alternate Manufacturer columns, all parts may be substituted with equivalents.

## IMPORTANT NOTICE FOR TI REFERENCE DESIGNS

Texas Instruments Incorporated ("TI") reference designs are solely intended to assist designers ("Buyers") who are developing systems that incorporate TI semiconductor products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products.

TI reference designs have been created using standard laboratory conditions and engineering practices. TI has not conducted any testing other than that specifically described in the published documentation for a particular reference design. TI may make corrections, enhancements, improvements and other changes to its reference designs.

Buyers are authorized to use TI reference designs with the TI component(s) identified in each particular reference design and to modify the reference design in the development of their end products. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER TI INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN, including but not limited to any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services, or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

TI REFERENCE DESIGNS ARE PROVIDED "AS IS". TI MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE REFERENCE DESIGNS OR USE OF THE REFERENCE DESIGNS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. TI DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO TI REFERENCE DESIGNS OR USE THEREOF. TI SHALL NOT BE LIABLE FOR AND SHALL NOT DEFEND OR INDEMNIFY BUYERS AGAINST ANY THIRD PARTY INFRINGEMENT CLAIM THAT RELATES TO OR IS BASED ON A COMBINATION OF COMPONENTS PROVIDED IN A TI REFERENCE DESIGN. IN NO EVENT SHALL TI BE LIABLE FOR ANY ACTUAL, SPECIAL, INCIDENTAL, CONSEQUENTIAL OR INDIRECT DAMAGES, HOWEVER CAUSED, ON ANY THEORY OF LIABILITY AND WHETHER OR NOT TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, ARISING IN ANY WAY OUT OF TI REFERENCE DESIGNS OR BUYER'S USE OF TI REFERENCE DESIGNS.

TI reserves the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques for TI components are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

Reproduction of significant portions of TI information in TI data books, data sheets or reference designs is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards that anticipate dangerous failures, monitor failures and their consequences, lessen the likelihood of dangerous failures and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in Buyer's safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed an agreement specifically governing such use.

Only those TI components that TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components that have *not* been so designated is solely at Buyer's risk, and Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.