


TAPE AND REEL INFORMATION

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE


*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
SN74LV273ADBR	SSOP	DB	20	2000	330.0	16.4	8.2	7.5	2.5	12.0	16.0	Q1
SN74LV273ADGSR	VSSOP	DGS	20	5000	330.0	16.4	5.4	5.4	1.45	8.0	16.0	Q1
SN74LV273ADGVR	TVSOP	DGV	20	2000	330.0	12.4	6.9	5.6	1.6	8.0	12.0	Q1
SN74LV273ADWR	SOIC	DW	20	2000	330.0	24.4	10.9	13.3	2.7	12.0	24.0	Q1
SN74LV273ADWR	SOIC	DW	20	2000	330.0	24.4	10.8	13.3	2.7	12.0	24.0	Q1
SN74LV273ANSR	SOP	NS	20	2000	330.0	24.4	8.4	13.0	2.5	12.0	24.0	Q1
SN74LV273APWR	TSSOP	PW	20	2000	330.0	16.4	6.95	7.0	1.4	8.0	16.0	Q1
SN74LV273APWRG4	TSSOP	PW	20	2000	330.0	16.4	6.95	7.0	1.4	8.0	16.0	Q1
SN74LV273APWRG4	TSSOP	PW	20	2000	330.0	16.4	6.95	7.0	1.4	8.0	16.0	Q1
SN74LV273ARGYR	VQFN	RGY	20	3000	330.0	12.4	3.71	4.71	1.1	8.0	12.0	Q1
SN74LV273ARKSR	VQFN	RKS	20	3000	180.0	12.4	2.8	4.8	1.2	4.0	12.0	Q1

TAPE AND REEL BOX DIMENSIONS


*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
SN74LV273ADBR	SSOP	DB	20	2000	353.0	353.0	32.0
SN74LV273ADGSR	VSSOP	DGS	20	5000	353.0	353.0	32.0
SN74LV273ADGVR	TVSOP	DGV	20	2000	353.0	353.0	32.0
SN74LV273ADWR	SOIC	DW	20	2000	356.0	356.0	45.0
SN74LV273ADWR	SOIC	DW	20	2000	356.0	356.0	45.0
SN74LV273ANSR	SOP	NS	20	2000	356.0	356.0	45.0
SN74LV273APWR	TSSOP	PW	20	2000	353.0	353.0	32.0
SN74LV273APWRG4	TSSOP	PW	20	2000	353.0	353.0	32.0
SN74LV273APWRG4	TSSOP	PW	20	2000	353.0	353.0	32.0
SN74LV273ARGYR	VQFN	RGY	20	3000	353.0	353.0	32.0
SN74LV273ARKSR	VQFN	RKS	20	3000	210.0	185.0	35.0