

TPS7A90 500mA, High-Accuracy, Low-Noise LDO Voltage Regulator

1 Features

- 1.0% accuracy over line, load, and temperature
- Low output noise: $4.7\mu\text{V}_{\text{RMS}}$ (10Hz – 100kHz)
- Low dropout: 100mV (maximum) at 0.5A
- Wide input voltage range: 1.4V to 6.5V
- Wide output voltage range: 0.8V to 5.7V
- High power-supply rejection ratio (PSRR):
 - 60dB at DC
 - 50dB at 100kHz
 - 30dB at 1MHz
- Fast transient response
- Adjustable start-up in-rush control with selectable soft-start charging current
- Open-drain power-good (PG) output
- $R_{\theta\text{JC}} = 3.2^\circ\text{C/W}$
- 2.5mm × 2.5mm, 10-pin WSON package

2 Applications

- [Macro remote radio units \(RRU\)](#)
- [Outdoor backhaul units](#)
- [Active antenna system mMIMO \(AAS\)](#)
- [Ultrasound scanners](#)
- [Lab and field instrumentation](#)
- [Sensor, imaging, and radar](#)

3 Description

The TPS7A90 is a low-noise ($4.7\mu\text{V}_{\text{RMS}}$), low-dropout (LDO) voltage regulator capable of sourcing 500mA with only 100mV of maximum dropout to 5V and from 200mV to 5.7V.

The TPS7A90 output is adjustable with external resistors from 0.8V to 5.7V. The TPS7A90 wide input voltage range supports operation as low as 1.4V and up to 6.5V.


With 1% output voltage accuracy (over line, load, and temperature) and soft-start capabilities to reduce in-rush current, the TPS7A90 is designed for powering sensitive analog low-voltage devices (such as voltage-controlled oscillators (VCOs), analog-to-digital converters (ADCs), and digital-to-analog converters [DACs]).

The TPS7A90 is designed to power noise-sensitive components such as components found in high-speed communication, video, medical, or test and measurement applications. The very low $4.7\mu\text{V}_{\text{RMS}}$ output noise and wideband PSRR (30dB at 1MHz) minimizes phase noise and clock jitter. These features maximize performance of clocking devices, ADCs, and DACs.

Package Information


PART NUMBER	PACKAGE ⁽¹⁾	PACKAGE SIZE ⁽²⁾
TPS7A90	DSK (WSON, 10)	2.5mm × 2.5mm

- (1) For more information, see [Section 10](#).
- (2) The package size (length × width) is a nominal value and includes pins, where applicable.



Typical Application Circuit

Copyright © 2016, Texas Instruments Incorporated



Typical Application Diagram



Table of Contents

1 Features	1	7 Application and Implementation	18
2 Applications	1	7.1 Application Information.....	18
3 Description	1	7.2 Typical Application.....	21
4 Pin Configuration and Functions	3	7.3 Power Supply Recommendations.....	23
5 Specifications	4	7.4 Layout.....	23
5.1 Absolute Maximum Ratings.....	4	8 Device and Documentation Support	25
5.2 ESD Ratings.....	4	8.1 Device Support.....	25
5.3 Recommended Operating Conditions.....	4	8.2 Documentation Support.....	25
5.4 Thermal Information.....	4	8.3 Receiving Notification of Documentation Updates....	25
5.5 Electrical Characteristics.....	5	8.4 Support Resources.....	25
5.6 Typical Characteristics.....	7	8.5 Trademarks.....	25
6 Detailed Description	13	8.6 Electrostatic Discharge Caution.....	25
6.1 Overview.....	13	8.7 Glossary.....	25
6.2 Functional Block Diagram.....	13	9 Revision History	26
6.3 Feature Description.....	13	10 Mechanical, Packaging, and Orderable Information	26
6.4 Device Functional Modes.....	16		

4 Pin Configuration and Functions




Figure 4-1. DSK Package, 2.5mm × 2.5mm, 10-Pin WSON (Top View)

Table 4-1. Pin Functions

PIN			DESCRIPTION
NAME	NO.	TYPE ⁽¹⁾	
EN	7	I	Enable pin. This pin turns the LDO on and off. If $V_{EN} \geq V_{IH(EN)}$, the regulator is enabled. If $V_{EN} \leq V_{IL(EN)}$, the regulator is disabled. The EN pin must connect to IN if the enable function is not used.
FB	3	I	Feedback pin. This pin is the input to the control loop error amplifier and is used to set the output voltage of the device.
GND	4	—	Device GND. Connect to the device thermal pad.
IN	9, 10	I	Input pin. A 10µF or greater input capacitor is required.
NR/SS	8	—	Noise reduction pin. Connect this pin to an external capacitor to bypass the noise generated by the internal band-gap reference. The capacitor reduces the output noise to very low levels and sets the output ramp rate to limit in-rush current.
OUT	1, 2	O	Regulated output. A 10µF or greater capacitor must connect from this pin to GND for stability.
PG	5	O	Open-drain, power-good indicator pin for the LDO output voltage. A from 10kΩ to 100kΩ external pullup resistor is required. This pin can be left floating or connected to GND if not used.
SS_CTRL	6	I	Soft-start control pin. Connect this pin either to GND or IN to change the NR/SS capacitor charging current. If a $C_{NR/SS}$ capacitor is not used, SS_CTRL must connect to GND to avoid output overshoot.
Thermal pad	Pad	—	Connect the thermal pad to the printed circuit board (PCB) ground plane. For an example layout, see Figure 7-5 .

(1) I = input, O = output

5 Specifications

5.1 Absolute Maximum Ratings

over operating junction temperature range and all voltages with respect to GND (unless otherwise noted)⁽¹⁾

		MIN	MAX	UNIT
Voltage	IN, PG, EN	−0.3	7.0	V
	IN, PG, EN (5% duty cycle, pulse duration ≤ 200μs)	−0.3	7.5	
	OUT	−0.3	V _{IN} + 0.3	
	SS_CTRL	−0.3	V _{IN} + 0.3	
	NR/SS, FB	−0.3	3.6	
Current	OUT	Internally limited		A
	PG (sink current into the device)		5	mA
Temperature	Operating junction, T _J	−55	150	°C
	Storage, T _{stg}	−55	150	°C

- (1) Operation outside the *Absolute Maximum Ratings* may cause permanent device damage. *Absolute Maximum Ratings* do not imply functional operation of the device at these or any other conditions beyond those listed under *Recommended Operating Conditions*. If used outside the *Recommended Operating Conditions* but within the *Absolute Maximum Ratings*, the device may not be fully functional, and this may affect device reliability, functionality, performance, and shorten the device lifetime.

5.2 ESD Ratings

			VALUE	UNIT
V _(ESD)	Electrostatic discharge	Human body model (HBM), per ANSI/ESDA/JEDEC JS-001 ⁽¹⁾	±2000	V
		Charged device model (CDM), per JEDEC specification JESD22-C101 ⁽²⁾	±500	

- (1) JEDEC document JEP155 states that 500V HBM allows safe manufacturing with a standard ESD control process.

- (2) JEDEC document JEP157 states that 250V CDM allows safe manufacturing with a standard ESD control process.

5.3 Recommended Operating Conditions

over operating junction temperature range (unless otherwise noted)

		MIN	MAX	UNIT
V _{IN}	Input supply voltage range	1.4	6.5	V
V _{OUT}	Output voltage range	0.8	5.7	V
I _{OUT}	Output current	0	0.5	A
C _{IN}	Input capacitor	10		μF
C _{OUT}	Output capacitor	10		μF
C _{NR/SS}	Noise-reduction capacitor	0	10	μF
C _{FF}	Feedforward capacitor	0	100	nF
R _{PG}	Power-good pullup resistance	10	100	kΩ
T _J	Junction temperature	−40	125	°C

5.4 Thermal Information

THERMAL METRIC ⁽¹⁾		TPS7A90	UNIT
		DSK (WSON)	
		10 PINS	
R _{θJA}	Junction-to-ambient thermal resistance	62.5	°C/W
R _{θJC(top)}	Junction-to-case (top) thermal resistance	59.7	°C/W
R _{θJB}	Junction-to-board thermal resistance	30.6	°C/W
ψ _{JT}	Junction-to-top characterization parameter	1.7	°C/W

5.4 Thermal Information (continued)

THERMAL METRIC ⁽¹⁾		TPS7A90	UNIT
		DSK (WSON)	
		10 PINS	
Ψ_{JB}	Junction-to-board characterization parameter	30.7	°C/W
$R_{\theta JC(bot)}$	Junction-to-case (bottom) thermal resistance	7.8	°C/W

(1) For more information about traditional and new thermal metrics, see the [Semiconductor and IC Package Thermal Metrics](#) application note.

5.5 Electrical Characteristics

over operating temperature range ($T_J = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$), $1.4\text{V} \leq V_{IN} \leq 6.5\text{V}$, $V_{OUT(NOM)} = 0.8\text{V}$, $I_{OUT} = 5\text{mA}$, $V_{EN} = 1.4\text{V}$, $C_{IN} = C_{OUT} = 10\mu\text{F}$, $C_{NR/SS} = C_{FF} = 0\text{nF}$, $SS_CTRL = \text{GND}$, and PG pin pulled up to V_{IN} with $100\text{k}\Omega$ (unless otherwise noted); typical values are at $T_J = 25^{\circ}\text{C}$

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{IN}	Input supply voltage range		1.4		6.5	V
V_{REF}	Reference voltage			0.8		V
V_{UVLO}	Input supply UVLO	V_{IN} rising		1.31	1.39	V
$V_{HYS(UVLO)}$	Input supply UVLO hysteresis			290		mV
V_{OUT}	Output voltage range		0.8		5.7	V
	Output voltage accuracy ⁽¹⁾	$1.4\text{V} \leq V_{IN} \leq 6.5\text{V}$, $5\text{mA} \leq I_{OUT} \leq 0.5\text{A}$	-1.0%		1.0%	
$\Delta V_{OUT(\Delta V_{IN})}$	Line regulation			0.005		%/V
$\Delta V_{OUT(\Delta I_{OUT})}$	Load regulation ⁽²⁾	$5\text{mA} \leq I_{OUT} \leq 0.5\text{A}$		0.02		%/A
V_{DO}	Dropout voltage	$1.4\text{V} \leq V_{IN} \leq 5.0\text{V}$, $I_{OUT} = 0.5\text{A}$, $V_{FB} = 0.8\text{V} - 3\%$			100	mV
		$5.0\text{V} < V_{IN} \leq 5.7\text{V}$, $I_{OUT} = 0.5\text{A}$, $V_{FB} = 0.8\text{V} - 3\%$			200	
I_{LIM}	Output current limit	V_{OUT} forced at $0.9 \times V_{OUT(NOM)}$, $V_{IN} = V_{OUT(NOM)} + 300\text{mV}$	0.8	1.1	1.5	A
I_{GND}	GND pin current	$V_{IN} = 6.5\text{V}$, $I_{OUT} = 5\text{mA}$		2.1	3.5	mA
		$V_{IN} = 1.4\text{V}$, $I_{OUT} = 0.5\text{A}$			4	
I_{SDN}	Shutdown GND pin current	PG = (open), $V_{IN} = 6.5\text{V}$, $V_{EN} = 0.4\text{V}$		0.1	15	μA
I_{EN}	EN pin current	$V_{IN} = 6.5\text{V}$, $0\text{V} \leq V_{EN} \leq 6.5\text{V}$	-0.2		0.2	μA
$V_{IL(EN)}$	EN pin low-level input voltage (device disabled)		0		0.4	V
$V_{IH(EN)}$	EN pin high-level input voltage (device enabled)		1.1		6.5	V
I_{SS_CTRL}	SS_CTRL pin current	$V_{IN} = 6.5\text{V}$, $0\text{V} \leq V_{SS_CTRL} \leq 6.5\text{V}$	-0.2		0.2	μA
$V_{IT(PG+)}$	PG pin threshold rising	For PG transitioning low with rising V_{OUT} , expressed as a percentage of $V_{OUT(NOM)}$	84%	90.9%	95%	
$V_{IT(PG-)}$	PG pin threshold falling	For PG transitioning low with falling V_{OUT} , expressed as a percentage of $V_{OUT(NOM)}$	82%	88.9%	93%	
$V_{HYS(PG)}$	PG pin hysteresis	For PG transitioning high with rising V_{OUT} , expressed as a percentage of $V_{OUT(NOM)}$		1%		
$V_{OL(PG)}$	PG pin low-level output voltage	$V_{OUT} < V_{IT(PG)}$, $I_{PG} = -1\text{mA}$ (current into device)			0.4	V
$I_{LKG(PG)}$	PG pin leakage current	$V_{OUT} > V_{IT(PG)}$, $V_{PG} = 6.5\text{V}$			1	μA
$I_{NR/SS}$	NR/SS pin charging current	$V_{NR/SS} = \text{GND}$, $V_{SS_CTRL} = \text{GND}$	4.0	6.2	9.0	μA
		$V_{NR/SS} = \text{GND}$, $V_{SS_CTRL} = V_{IN}$	65	100	150	
I_{FB}	FB pin leakage current	$V_{IN} = 6.5\text{V}$, $V_{FB} = 0.8\text{V}$	-100		100	nA
PSRR	Power-supply ripple rejection	$f = 500\text{kHz}$, $V_{IN} = 3.8\text{V}$, $V_{OUT(NOM)} = 3.3\text{V}$, $I_{OUT} = 250\text{mA}$, $C_{NR/SS} = 10\text{nF}$, $C_{FF} = 10\text{nF}$		39		dB

5.5 Electrical Characteristics (continued)


over operating temperature range ($T_J = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$), $1.4\text{V} \leq V_{\text{IN}} \leq 6.5\text{V}$, $V_{\text{OUT(NOM)}} = 0.8\text{V}$, $I_{\text{OUT}} = 5\text{mA}$, $V_{\text{EN}} = 1.4\text{V}$, $C_{\text{IN}} = C_{\text{OUT}} = 10\mu\text{F}$, $C_{\text{NR/SS}} = C_{\text{FF}} = 0\text{nF}$, $\text{SS_CTRL} = \text{GND}$, and PG pin pulled up to V_{IN} with $100\text{k}\Omega$ (unless otherwise noted); typical values are at $T_J = 25^{\circ}\text{C}$

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_n	Output noise voltage	$\text{BW} = 10\text{Hz to } 100\text{kHz}$, $V_{\text{IN}} = 1.8\text{V}$, $V_{\text{OUT(NOM)}} = 0.8\text{V}$, $I_{\text{OUT}} = 0.5\text{A}$, $C_{\text{NR/SS}} = 10\text{nF}$, $C_{\text{FF}} = 10\text{nF}$		4.7		μV_{RMS}
	Noise spectral density	$f = 10\text{kHz}$, $V_{\text{IN}} = 1.8\text{V}$, $V_{\text{OUT(NOM)}} = 0.8\text{V}$, $I_{\text{OUT}} = 0.5\text{A}$, $C_{\text{NR/SS}} = 10\text{nF}$, $C_{\text{FF}} = 10\text{nF}$		13		$\text{nV}/\sqrt{\text{Hz}}$
R_{diss}	Output active discharge resistance	$V_{\text{EN}} = \text{GND}$		250		Ω
T_{sd}	Thermal shutdown temperature	Shutdown, temperature increasing		160		$^{\circ}\text{C}$
		Reset, temperature decreasing		140		

- (1) When the device connects to external feedback resistors at the FB pin, external resistor tolerances are not included.
- (2) The device is not tested under conditions where $V_{\text{IN}} > V_{\text{OUT}} + 2.5\text{V}$ and $I_{\text{OUT}} = 0.5\text{A}$ because the power dissipation is higher than the maximum rating of the package. Also, this accuracy specification does not apply on any application condition that exceeds the power dissipation limit of the package under test.


5.6 Typical Characteristics

at $T_J = 25^\circ\text{C}$, $1.4\text{V} \leq V_{IN} \leq 6.5\text{V}$, $V_{IN} \geq V_{OUT(NOM)} + 0.3\text{V}$, $V_{OUT} = 0.8\text{V}$, $SS_CTRL = \text{GND}$, $I_{OUT} = 5\text{mA}$, $V_{EN} = 1.1\text{V}$, $C_{OUT} = 10\mu\text{F}$, $C_{NR/SS} = C_{FF} = 0\text{nF}$, PG pin pulled up to V_{OUT} with $100\text{k}\Omega$, and $SS_CTRL = \text{GND}$ (unless otherwise noted)




$V_{OUT} = 0.8\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{OUT} = 10\mu\text{F}$, $C_{NR/SS} = C_{FF} = 10\text{nF}$

Figure 5-1. PSRR vs Frequency and Input Voltage




$V_{OUT} = 1.2\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{OUT} = 10\mu\text{F}$, $C_{NR/SS} = C_{FF} = 10\text{nF}$

Figure 5-2. PSRR vs Frequency and Input Voltage




$V_{OUT} = 3.3\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{OUT} = 10\mu\text{F}$, $C_{NR/SS} = C_{FF} = 10\text{nF}$

Figure 5-3. PSRR vs Frequency and Input Voltage




$V_{OUT} = 5\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{OUT} = 10\mu\text{F}$, $C_{NR/SS} = C_{FF} = 10\text{nF}$

Figure 5-4. PSRR vs Frequency and Input Voltage



$V_{OUT} = 1.2\text{V}$, $V_{IN} = V_{EN} = 1.5\text{V}$, $C_{OUT} = 10\mu\text{F}$, $C_{NR/SS} = C_{FF} = 10\text{nF}$

Figure 5-5. PSRR vs Frequency and Output Current




$V_{OUT} = 3.3\text{V}$, $V_{IN} = V_{EN} = 3.6\text{V}$, $C_{OUT} = 10\mu\text{F}$, $C_{NR/SS} = C_{FF} = 10\text{nF}$

Figure 5-6. PSRR vs Frequency and Output Current


5.6 Typical Characteristics (continued)

at $T_J = 25^\circ\text{C}$, $1.4\text{V} \leq V_{IN} \leq 6.5\text{V}$, $V_{IN} \geq V_{OUT(NOM)} + 0.3\text{V}$, $V_{OUT} = 0.8\text{V}$, $SS_CTRL = \text{GND}$, $I_{OUT} = 5\text{mA}$, $V_{EN} = 1.1\text{V}$, $C_{OUT} = 10\mu\text{F}$, $C_{NR/SS} = C_{FF} = 0\text{nF}$, PG pin pulled up to V_{OUT} with $100\text{k}\Omega$, and $SS_CTRL = \text{GND}$ (unless otherwise noted)




$V_{OUT} = 1.2\text{V}$, $V_{IN} = V_{EN} = 1.7\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{OUT} = 10\mu\text{F}$,
 $C_{FF} = 10\text{nF}$

Figure 5-7. PSRR vs Frequency and $C_{NR/SS}$




$V_{IN} = V_{OUT} + 1.0\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{IN} = C_{OUT} = 10\mu\text{F}$, $C_{NR/SS} = C_{FF} = 10\text{nF}$, V_{RMS} BW = 10Hz to 100kHz

Figure 5-8. Spectral Noise Density vs Frequency and Output Voltage




$V_{IN} = 2.2\text{V}$, $V_{OUT} = 1.2\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{IN} = C_{OUT} = 10\mu\text{F}$,
 $C_{FF} = 10\text{nF}$, V_{RMS} BW = 10Hz to 100kHz

Figure 5-9. Spectral Noise Density vs Frequency and $C_{NR/SS}$




$V_{IN} = 2.2\text{V}$, $V_{OUT} = 1.2\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{IN} = C_{OUT} = 10\mu\text{F}$,
 $C_{NR/SS} = 10\text{nF}$, V_{RMS} BW = 10Hz to 100kHz

Figure 5-10. Spectral Noise Density vs Frequency and C_{FF}



$V_{IN} = 2.2\text{V}$, $V_{OUT} = 1.2\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{IN} = 10\mu\text{F}$, $C_{NR/SS} = C_{FF} = 10\text{nF}$, V_{RMS} BW = 10Hz to 100kHz

Figure 5-11. Spectral Noise Density vs Frequency and C_{OUT}



$V_{IN} = 1.4\text{V}$, $V_{OUT} = 0.8\text{V}$

Figure 5-12. Current Limit Foldback

5.6 Typical Characteristics (continued)

at $T_J = 25^\circ\text{C}$, $1.4\text{V} \leq V_{IN} \leq 6.5\text{V}$, $V_{IN} \geq V_{OUT(NOM)} + 0.3\text{V}$, $V_{OUT} = 0.8\text{V}$, $SS_CTRL = \text{GND}$, $I_{OUT} = 5\text{mA}$, $V_{EN} = 1.1\text{V}$, $C_{OUT} = 10\mu\text{F}$, $C_{NR/SS} = C_{FF} = 0\text{nF}$, PG pin pulled up to V_{OUT} with $100\text{k}\Omega$, and $SS_CTRL = \text{GND}$ (unless otherwise noted)




Figure 5-13. Current Limit vs Temperature




Figure 5-14. Dropout Voltage vs Output Current




Figure 5-15. Dropout Voltage vs Input Voltage




Figure 5-16. Load Regulation




Figure 5-17. Line Regulation




Figure 5-18. Shutdown Current vs Input Voltage

5.6 Typical Characteristics (continued)

at $T_J = 25^\circ\text{C}$, $1.4\text{V} \leq V_{IN} \leq 6.5\text{V}$, $V_{IN} \geq V_{OUT(NOM)} + 0.3\text{V}$, $V_{OUT} = 0.8\text{V}$, $SS_CTRL = \text{GND}$, $I_{OUT} = 5\text{mA}$, $V_{EN} = 1.1\text{V}$, $C_{OUT} = 10\mu\text{F}$, $C_{NR/SS} = C_{FF} = 0\text{nF}$, PG pin pulled up to V_{OUT} with $100\text{k}\Omega$, and $SS_CTRL = \text{GND}$ (unless otherwise noted)




Figure 5-19. Ground Current vs Output Current




Figure 5-20. Ground Current vs Input Voltage




Figure 5-21. PG Low Level Voltage vs PG Current ($V_{IN} = 1.4\text{V}$)




Figure 5-22. PG Low Level Voltage vs PG Current ($V_{IN} = 6.5\text{V}$)




Figure 5-23. PG Threshold vs Temperature




Figure 5-24. PG Leakage Current vs Temperature

5.6 Typical Characteristics (continued)

at $T_J = 25^\circ\text{C}$, $1.4\text{V} \leq V_{IN} \leq 6.5\text{V}$, $V_{IN} \geq V_{OUT(NOM)} + 0.3\text{V}$, $V_{OUT} = 0.8\text{V}$, $SS_CTRL = \text{GND}$, $I_{OUT} = 5\text{mA}$, $V_{EN} = 1.1\text{V}$, $C_{OUT} = 10\mu\text{F}$, $C_{NR/SS} = C_{FF} = 0\text{nF}$, PG pin pulled up to V_{OUT} with $100\text{k}\Omega$, and $SS_CTRL = \text{GND}$ (unless otherwise noted)




Figure 5-25. Soft-Start Current vs Temperature ($SS_CTRL = \text{GND}$)




Figure 5-26. Soft-Start Current vs Temperature ($SS_CTRL = V_{IN}$)




Figure 5-27. Enable Threshold vs Temperature






Figure 5-28. Input UVLO Threshold vs Temperature



$V_{IN} = 1.4\text{V}$, $I_{OUT} = 50\text{mA}$ to 500mA to 50mA at $1\text{A}/\mu\text{s}$, $C_{OUT} = 10\mu\text{F}$, $V_{PG} = V_{OUT}$

Figure 5-29. Load Transient Response ($V_{OUT} = 0.8\text{V}$)




$V_{IN} = 5.5\text{V}$, $I_{OUT} = 50\text{mA}$ to 500mA to 50mA at $1\text{A}/\mu\text{s}$, $C_{OUT} = 10\mu\text{F}$, $V_{PG} = V_{OUT}$

Figure 5-30. Load Transient Response ($V_{OUT} = 5.0\text{V}$)

5.6 Typical Characteristics (continued)


at $T_J = 25^\circ\text{C}$, $1.4\text{V} \leq V_{IN} \leq 6.5\text{V}$, $V_{IN} \geq V_{OUT(NOM)} + 0.3\text{V}$, $V_{OUT} = 0.8\text{V}$, $SS_CTRL = \text{GND}$, $I_{OUT} = 5\text{mA}$, $V_{EN} = 1.1\text{V}$, $C_{OUT} = 10\mu\text{F}$, $C_{NR/SS} = C_{FF} = 0\text{nF}$, PG pin pulled up to V_{OUT} with $100\text{k}\Omega$, and $SS_CTRL = \text{GND}$ (unless otherwise noted)



Time (200 $\mu\text{s}/\text{div}$)

$V_{IN} = 1.4\text{V}$ to 6.5V to 1.4V at $2\text{V}/\mu\text{s}$, $V_{OUT} = 0.8\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{NR/SS} = C_{FF} = 10\text{nF}$, $V_{PG} = V_{OUT}$


Figure 5-31. Line Transient



Time (50 $\mu\text{s}/\text{div}$)

$V_{IN} = 1.4\text{V}$, $V_{PG} = V_{OUT}$


Figure 5-32. Start-Up ($SS_CTRL = \text{GND}$, $C_{NR/SS} = 0\text{nF}$)



Time (500 $\mu\text{s}/\text{div}$)

$V_{IN} = 1.4\text{V}$, $V_{PG} = V_{OUT}$


Figure 5-33. Start-Up ($SS_CTRL = \text{GND}$, $C_{NR/SS} = 10\text{nF}$)



Time (50 $\mu\text{s}/\text{div}$)

$V_{IN} = 1.4\text{V}$, $V_{PG} = V_{OUT}$

Figure 5-34. Start-Up ($SS_CTRL = V_{IN}$, $C_{NR/SS} = 10\text{nF}$)



Time (2 ms/div)

$V_{IN} = 1.4\text{V}$, $V_{PG} = V_{OUT}$

Figure 5-35. Start-Up ($SS_CTRL = V_{IN}$, $C_{NR/SS} = 1\mu\text{F}$)


6 Detailed Description

6.1 Overview

The TPS7A90 is a low-noise, high PSRR, low dropout (LDO) regulator capable of sourcing a 500mA load with only 200mV of maximum dropout. The TPS7A90 can operate down to a 1.4V input voltage and a 0.8V output voltage. This combination of low-noise, high PSRR, and low dropout voltage makes the device an appropriate LDO to power a multitude of loads from noise-sensitive communication components in high-speed communications applications to high-end microprocessors or field-programmable gate arrays (FPGAs).

As shown in [Functional Block Diagram](#), the TPS7A90 linear regulator features a low-noise, 0.8V internal reference that can be filtered externally to obtain even lower output noise. The internal protection circuitry (such as the undervoltage lockout) prevents the device from turning on before the input is high enough to establish accurate regulation. Foldback current limiting is also included, allowing the output to source the rated output current when the output voltage is in regulation but reduces the allowable output current during short-circuit conditions. The internal power-good detection circuit allows down-stream supplies to be sequenced and alerts if the output voltage is below a regulation threshold.

6.2 Functional Block Diagram



6.3 Feature Description

6.3.1 Output Enable

The enable pin (EN) for the TPS7A90 is active high. The output voltage is enabled when the enable pin voltage is greater than $V_{IH(EN)}$ and disabled with the enable pin voltage is less than $V_{IL(EN)}$. If independent control of the output voltage is not needed, then connect the enable pin to the input.

The TPS7A90 has an internal pulldown MOSFET that connects a discharge resistor from V_{OUT} to ground when the device is disabled to actively discharge the output voltage.

6.3.2 Dropout Voltage (V_{DO})

Dropout voltage (V_{DO}) is defined as the $V_{IN} - V_{OUT}$ voltage at the rated current (I_{RATED}) of 500mA, where the pass-FET is fully on and in the ohmic region of operation. V_{DO} indirectly specifies a minimum input voltage above the nominal programmed output voltage at which the output voltage is expected to remain in regulation. If the input falls below the nominal output regulation, then the output follows the input.

The $R_{DS(ON)}$ of the pass-FET determines the dropout voltage. Therefore, if the LDO operates below the rated current, then the V_{DO} for that current scales accordingly. Use [Equation 1](#) to calculate the $R_{DS(ON)}$ for the TPS7A90:

$$R_{DS(ON)} = \frac{V_{DO}}{I_{RATED}} \quad (1)$$

6.3.3 Output Voltage Accuracy

Output voltage accuracy specifies minimum and maximum output voltage error, relative to the expected nominal output voltage stated as a percent. The TPS7A90 features an output voltage accuracy of 1% that includes the errors introduced by the internal reference, load regulation, and line regulation variance across the full range of rated load and line operating conditions overtemperature, as [Electrical Characteristics](#) specifies. Output voltage accuracy also accounts for all variations between manufacturing lots.

6.3.4 High Power-Supply Rejection Ratio (PSRR)

PSRR is a measure of how well the LDO control loop rejects noise from the input source to make the dc output voltage as noise-free as possible across the frequency spectrum (usually measured from 10Hz to 10MHz). Even though PSRR is a loss in noise signal amplitude, the PSRR curves in [Section 5.6](#) are shown as positive values in decibels (dB) for convenience. [Equation 2](#) shows the PSRR calculation as a function of frequency where input noise voltage ($V_{IN}(f)$) and output noise voltage ($V_{OUT}(f)$) are the amplitudes of the respective sinusoidal signals.

$$PSRR \text{ (dB)} = 20 \log_{10} \left(\frac{V_{IN}(f)}{V_{OUT}(f)} \right) \quad (2)$$

Noise that couples from the input to the internal reference voltage is a primary contributor to reduced PSRR performance. TI recommends using a noise-reduction capacitor to filter unwanted noise from the input voltage, which creates a low-pass filter with an internal resistor to improve PSRR performance at lower frequencies.

LDOs are often employed not only as a step-down regulators, but also to provide exceptionally clean power rails for noise-sensitive components. This usage is especially true for the TPS7A90, which features a remarkable circuit to boost the PSRR from 200kHz to 1MHz. This boost circuit helps further filter switching noise from switching-regulators that operate in this region; see [Section 5.6](#). To achieve the maximum benefit of this PSRR boost circuit, TI recommends using a capacitor with a minimum impedance in the from 100kHz to 1MHz band.

6.3.5 Low Output Noise

LDO noise is defined as the internally-generated intrinsic noise created by the semiconductor circuits. The TPS7A90 is designed for system applications where minimizing noise on the power-supply rail is critical to system performance. This scenario is the case for phase-locked-loop (PLL)-based clocking circuits where minimum phase noise is all important, or in test and measurement systems where even small power-supply noise fluctuations can distort instantaneous measurement accuracy.

The TPS7A90 includes a low-noise reference establishing minimal output noise in normal operation. Make further improvements by adding a noise-reduction capacitor ($C_{NR/SS}$), a feedforward capacitor (C_{FF}), or a combination of the two. See the [Noise-Reduction and Soft-Start Capacitor \(\$C_{NR/SS}\$ \)](#) and [Feed-Forward Capacitor \(\$C_{FF}\$ \)](#) sections for additional design information.

For more information on noise and noise measurement, see the [How to Measure LDO Noise white paper](#).

6.3.6 Output Soft-Start Control

Soft-start refers to the ramp-up characteristic of the output voltage during LDO turn-on after the EN and UVLO thresholds are exceeded. The noise-reduction capacitor ($C_{NR/SS}$) serves a dual purpose of both governing output noise reduction and programming the soft start ramp during turn-on. Larger values for the noise-reduction capacitors decrease the noise but also result in a slower output turn-on ramp rate.

The TPS7A90 features an SS_CTRL pin. When the SS_CTRL pin is grounded, the charging current for the NR/SS pin is 6.2μA (typical); when this pin connects to IN, the charging current for the NR/SS pin is increased to 100μA (typical). The higher current allows the use of a much larger noise-reduction capacitor and maintains a reasonable startup time. [Figure 6-1](#) shows a simplified block diagram of the soft-start circuit. The switch SW is opened to turn off the $I_{NR/SS}$ current source after V_{FB} reaches approximately 97% of V_{REF} . The final 3% of $V_{NR/SS}$ is charged through the noise-reduction resistor (R_{NR}), which creates an RC delay. R_{NR} is approximately 280kΩ

and applications that require the highest accuracy when using a large value $C_{NR/SS}$ must take this RC delay into account.

If a noise-reduction capacitor is not used on the NR/SS pin, tying the SS_CTRL pin to the IN pin can result in output voltage overshoot of approximately 10%. This overshoot is minimized by either connecting the SS_CTRL pin to GND or using a capacitor on the NR/SS pin.




Figure 6-1. Simplified Soft-Start Circuit

6.3.7 Power-Good Function

The power-good circuit monitors the voltage at the feedback pin to indicate the status of the output voltage. When the feedback pin voltage falls below the PG threshold voltage ($V_{IT(PG)}$), the PG pin open-drain output engages and pulls the PG pin close to GND. When the feedback voltage exceeds the $V_{IT(PG)}$ threshold by an amount greater than $V_{HYS(PG)}$, the PG pin becomes high impedance. By connecting a pullup resistor to an external supply, any downstream device can receive power-good as a logic signal that can be used for sequencing. Make sure that the external pullup supply voltage results in a valid logic signal for the receiving device or devices. TI recommends using a pullup resistor from 10kΩ to 100kΩ. TI also recommends using an external reset device such as the [TPS3890](#) in applications where high accuracy is needed or in applications where microprocessor induced resets are needed.

When using a feed-forward capacitor (C_{FF}), the time constant for the LDO startup is increased whereas the power-good output time constant stays the same, possibly resulting in an invalid status of the power-good output. To avoid this issue and to receive a valid PG output, make sure that the time constant of both the LDO startup and the power-good output are matching, which can be done by adding a capacitor in parallel with the power-good pullup resistor. See also the [Pros and Cons of Using a Feedforward Capacitor with a Low-Dropout Regulator application note](#).

The state of PG is only valid when the device is operating above the minimum input voltage of the device and power-good is asserted regardless of the output voltage state when the input voltage falls below the UVLO threshold minus the UVLO hysteresis. [Figure 6-2](#) shows a simplified block diagram of the power-good circuit. When the input voltage falls below approximately 0.8V, there is not enough gate drive voltage to keep the open-drain, power-good device turned on and the power-good output is pulled high. Connecting the power-good pullup resistor to the output voltage can help minimize this effect.




Figure 6-2. Simplified PG Circuit

6.3.8 Internal Protection Circuitry

6.3.8.1 Undervoltage Lockout (UVLO)

The TPS7A90 has an independent undervoltage lockout (UVLO) circuit that monitors the input voltage, allowing a controlled and consistent turn on and off of the output voltage. To prevent the device from turning off if the input drops during turn on, the UVLO has approximately 290mV of hysteresis.

The UVLO circuit responds quickly to glitches on V_{IN} and disables the output of the device if this rail starts to collapse too quickly. Use an input capacitor that is large enough to slow input transients to less than two volts per microsecond.

6.3.8.2 Internal Current Limit (I_{CL})

The internal current-limit circuit is used to protect the LDO against transient high-load current faults or shorting events. The LDO is not designed to operate in current limit under steady-state conditions. During an overcurrent event where the output voltage is pulled 10% below the regulated output voltage, the LDO sources a constant current as specified in the [Electrical Characteristics](#) table. When the output voltage falls, the amount of output current is reduced to better protect the device. During a hard short-circuit event, the current is reduced to approximately 1.45A. See [Figure 5-12](#) in the [Typical Characteristics](#) section for more information about the current-limit foldback behavior. However, when a current-limit event occurs, the LDO begins to heat up because of the increase in power dissipation. The increase in heat can trigger the integrated thermal shutdown protection circuit.

6.3.8.3 Thermal Protection

The TPS7A90 contains a thermal shutdown protection circuit to turn off the output current when excessive heat is dissipated in the LDO. Thermal shut down occurs when the thermal junction temperature (T_J) of the pass-FET exceeds 160°C (typical). Thermal shutdown hysteresis assures that the LDO again resets (turns on) when the temperature falls to 140°C (typical). The thermal time-constant of the semiconductor die is fairly short, and thus the output turns on and off at a high rate when thermal shutdown is reached until power dissipation is reduced.

The internal protection circuitry of the TPS7A90 is designed to protect against thermal overload conditions. The circuitry is not intended to replace proper heat sinking. Continuously running the TPS7A90 into thermal shutdown degrades device reliability.

For reliable operation, limit junction temperature to a maximum of 125°C. To estimate the thermal margin in a given layout, increase the ambient temperature until the thermal protection shutdown is triggered using worst-case load and highest input voltage conditions. For good reliability, thermal shutdown must occur at least 35°C above the maximum expected ambient temperature condition for the application. This configuration produces a worst-case junction temperature of 125°C at the highest expected ambient temperature and worst-case load.

6.4 Device Functional Modes

[Table 6-1](#) provides a quick comparison between the normal, dropout, and disabled modes of operation.

Table 6-1. Device Functional Modes Comparison

OPERATING MODE	PARAMETER			
	V_{IN}	EN	I_{OUT}	T_J
Normal ⁽¹⁾	$V_{IN} > V_{OUT(nom)} + V_{DO}$	$V_{EN} > V_{IH(EN)}$	$I_{OUT} < I_{CL}$	$T_J < T_{sd}$
Dropout ⁽¹⁾	$V_{IN} < V_{OUT(nom)} + V_{DO}$	$V_{EN} > V_{IH(EN)}$	$I_{OUT} < I_{CL}$	$T_J < T_{sd}$
Disabled ⁽²⁾	$V_{IN} < V_{UVLO}$	$V_{EN} < V_{IL(EN)}$	—	$T_J > T_{sd}$

(1) All table conditions must be met.

(2) The device is disabled when any condition is met.

6.4.1 Normal Operation

The device regulates to the nominal output voltage when all of the following conditions are met:

- The input voltage is greater than the nominal output voltage plus the dropout voltage ($V_{OUT(nom)} + V_{DO}$)

- The enable voltage has previously exceeded the enable rising threshold voltage and has not yet decreased below the enable falling threshold
- The output current is less than the current limit ($I_{OUT} < I_{CL}$)
- The device junction temperature is less than the thermal shutdown temperature ($T_J < T_{sd}$)

6.4.2 Dropout Operation

If the input voltage is lower than the nominal output voltage plus the specified dropout voltage, but all other conditions are met for normal operation, the device operates in dropout. In this mode, the output voltage tracks the input voltage. During this mode, the transient performance of the device becomes significantly degraded because the pass device is in a triode state and no longer controls the current through the LDO. Line or load transients in dropout can result in large output-voltage deviations.

When the device is in a steady dropout state (defined as when the device is in dropout, $V_{IN} < V_{OUT(NOM)} + V_{DO}$, right after being in a normal regulation state, but *not* during startup), the pass-FET is driven as hard as possible. When the input voltage returns to $V_{IN} \geq V_{OUT(NOM)} + V_{DO}$, V_{OUT} can overshoot for a short period of time if the input voltage slew rate is greater than $0.1V/\mu s$.

6.4.3 Disabled

The output of the TPS7A90 can be shutdown by forcing the enable pin below 0.4V. When disabled, the pass device is turned off, internal circuits are shutdown, and the output voltage is actively discharged to ground by an internal resistor from the output to ground.

7 Application and Implementation

Note

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes, as well as validating and testing their design implementation to confirm system functionality.

7.1 Application Information

The TPS7A90 is a linear voltage regulator operating from 1.4V to 6.5V on the input, and regulates voltages from 0.8V to 5.0V within 1% accuracy and a 500mA maximum output current. Efficiency is defined by the ratio of output voltage to input voltage because the TPS7A90 is a linear voltage regulator. To achieve high efficiency, the dropout voltage ($V_{IN} - V_{OUT}$) must be as small as possible, thus requiring a very low dropout LDO. Successfully implementing an LDO in an application depends on the application requirements. This section describes key device features and how to best implement the features to achieve a reliable design.

7.1.1 Adjustable Output

As [Figure 7-1](#) shows, the output voltage of the TPS7A90 can be adjusted from 0.8V to 5.2V by using a resistor divider network.




Figure 7-1. Adjustable Operation

Use [Equation 3](#) to calculate R_1 and R_2 for any output voltage range. This resistive network must provide a current greater than or equal to 5μA for optimum noise performance.

$$R_1 = R_2 \left(\frac{V_{OUT}}{V_{REF}} - 1 \right) \quad (3)$$

where

$$\frac{|V_{REF(max)}|}{R_2} > 5 \mu A \quad (4)$$

If greater voltage accuracy is required, take into account the output voltage offset contribution resulting from the feedback pin current (I_{FB}) and use 0.1%-tolerance resistors.

[Table 7-1](#) lists the resistor combination required to achieve a few of the most common rails using commercially-available, 0.1%-tolerance resistors to maximize nominal voltage accuracy and also abiding to the formula given in [Equation 3](#) and [Equation 4](#).

Table 7-1. Recommended Feedback Resistor Values

$V_{OUT(TARGET)}$ (V)	FEEDBACK RESISTOR VALUES ⁽¹⁾		CALCULATED OUTPUT VOLTAGE (V)
	R_1 (kΩ)	R_2 (kΩ)	
0.8	Short	Open	0.800
1.00	2.55	10.2	1.000
1.20	5.9	11.8	1.200
1.50	9.31	10.7	1.496

Table 7-1. Recommended Feedback Resistor Values (continued)

V _{OUT(TARGET)} (V)	FEEDBACK RESISTOR VALUES ⁽¹⁾		CALCULATED OUTPUT VOLTAGE (V)
	R ₁ (kΩ)	R ₂ (kΩ)	
1.80	1.87	1.5	1.797
1.90	15.8	11.5	1.899
2.50	2.43	1.15	2.490
3.00	3.16	1.15	2.998
3.30	3.57	1.15	3.283
5.00	10.5	2	5.00

(1) R₁ connects from OUT to FB; R₂ connects from FB to GND; see [Figure 7-1](#).

7.1.2 Start-Up

7.1.2.1 Enable (EN) and Undervoltage Lockout (UVLO)

The TPS7A90 only turns on when EN and UVLO are above the respective voltage thresholds. The TPS7A90 has an independent UVLO circuit that monitors the input voltage to allow a controlled and consistent turn on and off. The UVLO has approximately 290mV of hysteresis to prevent the device from turning off if the input drops during turn on. The EN signal allows independent logic-level turn-on and shutdown of the LDO when the input voltage is present. Connecting EN directly to IN is recommended if independent turn-on is not needed.

The TPS7A90 has an internal pulldown MOSFET that connects a discharge resistor from V_{OUT} to ground when the device is disabled to actively discharge the output voltage.

7.1.2.2 Noise-Reduction and Soft-Start Capacitor (C_{NR/SS})

The C_{NR/SS} capacitor serves a dual purpose of both reducing output noise and setting the soft-start ramp during turn-on.

7.1.2.2.1 Noise Reduction

For low-noise applications, the C_{NR/SS} capacitor forms an RC filter for filtering output noise that is otherwise amplified by the control loop. For low-noise applications, a C_{NR/SS} of from 10nF to 10μF is recommended. Larger values for C_{NR/SS} can be used; however, above 1μF there is little benefit in lowering the output voltage noise for frequencies above 10Hz.

7.1.2.2.2 Soft-Start and In-Rush Current

Soft-start refers to the gradual ramp-up characteristic of the output voltage after the EN and UVLO thresholds are exceeded. Reducing how quickly the output voltage increases during startup also reduces the amount of current needed to charge the output capacitor, referred to as in-rush current. In-rush current is defined as the current going into the LDO during start-up. In-rush current consists of the load current, the current used to charge the output capacitor, and the ground pin current (that contributes very little to in-rush current). This current is difficult to measure because the input capacitor must be removed, which is not recommended. However, use [Equation 5](#) to estimate in-rush current:

$$I_{OUT}(t) = \left(\frac{C_{OUT} \times d V_{OUT}(t)}{d t} \right) + \left(\frac{V_{OUT}(t)}{R_{LOAD}} \right) \quad (5)$$

where:

- V_{OUT}(t) is the instantaneous output voltage of the turn-on ramp
- dV_{OUT}(t) / dt is the slope of the V_{OUT} ramp
- R_{LOAD} is the resistive load impedance

The TPS7A90 features a monotonic, voltage-controlled soft-start that is set with an external capacitor (C_{NR/SS}). This soft-start helps reduce in-rush current, minimizing load transients to the input power bus that can cause potential start-up initialization problems when powering FPGAs, digital signal processors (DSPs), or other high current loads.

To achieve a monotonic start-up, the TPS7A90 error amplifier tracks the voltage ramp of the external soft-start capacitor until the voltage exceeds approximately 97% of the internal reference. The final 3% of $V_{NR/SS}$ is charged through the noise-reduction resistor (R_{NR}), creating an RC delay. R_{NR} is approximately 280k Ω and applications that require the highest accuracy when using a large value $C_{NR/SS}$ must take this RC delay into account.

The soft-start ramp time depends on the soft-start charging current ($I_{NR/SS}$), the soft-start capacitance ($C_{NR/SS}$), and the internal reference (V_{REF}). Use [Equation 6](#) to calculate the approximate soft-start ramp time (t_{SS}):

$$t_{SS} = (V_{REF} \times C_{NR/SS}) / I_{NR/SS} \quad (6)$$

The value for $I_{NR/SS}$ is determined by the state of the SS_CTRL pin. When the SS_CTRL pin is connected to GND, the typical value for the $I_{NR/SS}$ current is 6.2 μ A. Connecting the SS_CTRL pin to IN increases the typical soft-start charging current to 100 μ A. The larger charging current for $I_{NR/SS}$ is useful if shorter start-up times are needed (such as when using a large noise-reduction capacitor).

7.1.3 Capacitor Recommendation

The TPS7A90 is designed to be stable using low equivalent series resistance (ESR) ceramic capacitors at the input, output, and noise-reduction pin. Multilayer ceramic capacitors are the industry standard for these types of applications and are recommended, but must be used with good understanding of the limitations. Ceramic capacitors that employ X7R-rated, X5R-rated, and COG-rated dielectric materials provide relatively good capacitive stability across temperature. The use of Y5V-rated capacitors is discouraged precisely because the capacitance varies so widely. In all cases, ceramic capacitors vary a great deal with operating voltage and temperature and the design engineer must be aware of these characteristics. As a general guideline, ceramic capacitors are recommended to be derated by 50%. The input and output capacitors recommended herein account for a capacitance derating of 50%.

7.1.3.1 Input and Output Capacitor Requirements (C_{IN} and C_{OUT})

The TPS7A90 is designed and characterized for operation with ceramic capacitors of 10 μ F or greater at the input and output. Locate the input and output capacitors as near as practical to the input and output pins to minimize the trace inductance from the capacitor to the device.

Attention must be given to the input capacitance to minimize transient input droop during startup and load current steps. Simply using very large ceramic input capacitances can cause unwanted ringing at the output if the input capacitor (in combination with the wire-lead inductance) creates a high-Q peaking effect during transients, which is why short, well-designed interconnect traces to the upstream supply are needed to minimize ringing. Damping of unwanted ringing can be accomplished by using a tantalum capacitor, with a few hundred milliohms of ESR, in parallel with the ceramic input capacitor. The UVLO circuit responds quickly to glitches on V_{IN} and disables the output of the device if this rail starts to collapse too quickly. Use an input capacitor that is large enough to slow input transients to less than two volts per microsecond.

7.1.3.1.1 Load-Step Transient Response

The load-step transient response is the output voltage response by the LDO to a step change in load current. The depth of charge depletion immediately after the load step is directly proportional to the amount of output capacitance. However, although larger output capacitances decrease any voltage dip or peak occurring during a load step, the control-loop bandwidth is also decreased, thereby slowing the response time.

The LDO cannot sink charge, therefore when the output load is removed or greatly reduced, the control loop must turn off the pass-FET and wait for any excess charge to deplete.

7.1.3.2 Feed-Forward Capacitor (C_{FF})

Although a feed-forward capacitor (C_{FF}), from the FB pin to the OUT pin is not required to achieve stability, a 10nF, feed-forward capacitor improves the noise and PSRR performance. When using a higher capacitance C_{FF} , the startup time is longer and the power-good signal can incorrectly indicate that the output voltage has settled. For a detailed description, see the application note [Pros and Cons of Using a Feedforward Capacitor with a Low-Dropout Regulator](#).

7.1.4 Power Dissipation (P_D)

Circuit reliability demands that proper consideration be given to device power dissipation, location of the circuit on the printed circuit board (PCB), and correct sizing of the thermal plane. The PCB area around the regulator must be as free as possible of other heat-generating devices that cause added thermal stresses.

To a first-order approximation, power dissipation in the regulator depends on the input-to-output voltage difference and load conditions. Equation 7 calculates P_D :

$$P_D = (V_{IN} - V_{OUT}) \times I_{OUT} \quad (7)$$

Power dissipation can be minimized, and thus greater efficiency achieved, by proper selection of the system voltage rails. For the lowest power dissipation use the minimum input voltage necessary for proper output regulation.

The primary heat conduction path for the DSK package is through the thermal pad to the PCB. Solder the thermal pad to a copper pad area under the device. This pad area must contain an array of plated vias that conduct heat to additional copper planes for increased heat dissipation.

The maximum power dissipation determines the maximum allowable ambient temperature (T_A) for the device. According to Equation 8, power dissipation and junction temperature are most often related by the junction-to-ambient thermal resistance ($R_{\theta JA}$) of the combined PCB and device package and the temperature of the ambient air (T_A).

$$T_J = T_A + (\theta_{JA} \times P_D) \quad (8)$$

Unfortunately, the thermal resistance ($R_{\theta JA}$) is highly dependent on the heat-spreading capability built into the particular PCB design, and therefore varies according to the total copper area, copper weight, and location of the planes. The $R_{\theta JA}$ recorded in the Section 5.4 table is determined by the JEDEC standard, PCB, and copper-spreading area and is only used as a relative measure of package thermal performance.

7.1.5 Estimating Junction Temperature

The JEDEC standard recommends the use of psi (Ψ) thermal metrics to estimate the junction temperatures of the LDO when in-circuit on a typical PCB board application. These metrics are not strictly speaking thermal resistances, but rather offer practical and relative means of estimating junction temperatures. These psi metrics are determined to be significantly independent of the copper-spreading area. The key thermal metrics (Ψ_{JT} and Ψ_{JB}) are used in accordance with Equation 9 and are given in the Section 5.4 table.

$$\begin{aligned} \Psi_{JT}: T_J &= T_T + \Psi_{JT} \times P_D \\ \Psi_{JB}: T_J &= T_B + \Psi_{JB} \times P_D \end{aligned} \quad (9)$$


where:

- P_D is the power dissipated as explained in Equation 7
- T_T is the temperature at the center-top of the device package
- T_B is the PCB surface temperature measured 1mm from the device package and centered on the package edge

For a more detailed discussion on how to use thermal metrics, see the application note [Semiconductor and IC Package Thermal Metrics](#).

7.2 Typical Application

This section describes the implementation of the TPS7A90 to regulate from a 2V input voltage to a 1.2V output voltage for noise-sensitive loads. Figure 7-2 shows the schematic for this application circuit.



Copyright © 2016, Texas Instruments Incorporated

Figure 7-2. Application Example**7.2.1 Design Requirements**

For the design example shown in [Figure 7-2](#), use the parameters listed in [Table 7-2](#) as the input parameters.

Table 7-2. Design Parameters

PARAMETER	APPLICATION REQUIREMENTS	DESIGN RESULTS
Input voltages (V_{IN})	2V, $\pm 3\%$, provided by the DC-DC converter switching at 750kHz	1.4V to 6.5V
Maximum ambient operating temperature	85°C	108°C junction temperature
Output voltages (V_{OUT})	1.2V, $\pm 1\%$	1.2V, $\pm 1\%$
Output currents (I_{OUT})	500mA (maximum), 10mA (minimum)	500mA (maximum), 5mA (minimum)
RMS noise	$< 6\mu V_{RMS}$, bandwidth = 10Hz to 100kHz	$5.2\mu V_{RMS}$, bandwidth = 10Hz to 100kHz
PSRR at 500kHz	$> 40\text{dB}$	47dB
Start-up time	$< 2\text{ms}$	80µs (typical) 148µs (maximum)

7.2.2 Detailed Design Procedure

Set the output voltage to 1.2V by selecting the correct values for R_1 and R_2 ; see [Equation 3](#).

Input and output capacitors are selected in accordance with [Capacitor Recommendation](#). Ceramic capacitances of 10µF for both input and output help balance the charge needed during start-up when charging the output capacitor, thus reducing the input voltage drop.



To satisfy the required start-up time (t_{SS}) and still maintain low-noise performance, a 0.01µF $C_{NR/SS}$ is selected for with SS_CTRL connected to V_{IN} . [Equation 10](#) calculates this value. Using $I_{NR/SS(MAX)}$ and the smallest $C_{NR/SS}$ capacitance resulting from manufacturing variance (often $\pm 20\%$) provides the fastest start-up time, whereas using $I_{NR/SS(MIN)}$ and the largest $C_{NR/SS}$ capacitance resulting from manufacturing variance provides the slowest start-up time.

$$t_{SS} = (V_{REF} \times C_{NR/SS}) / I_{NR/SS} \quad (10)$$

With a 500mA maximum load, the internal power dissipation is 800mW, corresponding to a 23°C junction temperature rise. With an 85°C maximum ambient temperature, the junction temperature is at 108°C. To minimize noise, use a feed-forward capacitance (C_{FF}) of 10nF.

See [Layout](#) for an example of how to layout the TPS7A90 to achieve best PSRR and noise.

7.2.3 Application Curves



7.3 Power Supply Recommendations

The input of the TPS7A90 is designed to operate from an input voltage range from 1.4V to 6.5V and with an input capacitor of 10μF. The input voltage range must provide adequate headroom for the device to have a regulated output. This input supply must be well regulated. If the input supply is noisy, additional input capacitors can be used to improve the output noise performance.

7.4 Layout

7.4.1 Layout Guidelines

General guidelines for linear regulator designs are to place all circuit components on the same side of the circuit board and as near as practical to the respective LDO pin connections. Place ground return connections to the input and output capacitors, and to the LDO ground pin as close to each other as possible, connected by a wide, component-side, copper surface. The use of vias and long traces to create LDO circuit connections is strongly discouraged and negatively affects system performance.

7.4.1.1 Board Layout

To maximize the ac performance of the TPS7A90, following the layout example shown in [Figure 7-5](#) is recommended. This layout isolates the analog ground (AGND) from the noisy power ground. Components that must connect to the quiet analog ground are the noise-reduction capacitor ($C_{NR/SS}$) and the lower feedback resistor (R_2). These components must have a separate connection back to the thermal pad of the device for peak output noise performance. Connect the GND pin directly to the thermal pad and not to any external plane.

To maximize the output voltage accuracy, the connection from the output voltage back to top output divider resistors (R_1) must be made as close as possible to the load. This method of connecting the feedback trace eliminates the voltage drop from the device output to the load.

To improve thermal performance, use an array of thermal vias to connect the thermal pad to the ground planes. Larger ground planes improve the thermal performance of the device and lowering the operating temperature of the device.

7.4.2 Layout Example




Figure 7-5. TPS7A90 Example Layout

8 Device and Documentation Support

8.1 Device Support

8.1.1 Development Support

8.1.1.1 SPICE Models

Computer simulation of circuit performance using SPICE is often useful when analyzing the performance of analog circuits and systems. A SPICE model for the TPS7A90 is available through the TPS7A90 product folder under simulation models.

8.1.2 Device Nomenclature

Table 8-1. Ordering Information

PRODUCT ⁽¹⁾	DESCRIPTION
TPS7A90XXYYYZ	XX represents the output voltage. 01 is the adjustable output version. YYY is the package designator. Z is the package quantity.

(1) For the most current package and ordering information, see the *Package Option Addendum* at the end of this document, or see the device product folder at www.ti.com.

8.2 Documentation Support

8.2.1 Related Documentation

For related documentation, see the following:

- Texas Instruments, [TPS3890 Low Quiescent Current, 1% Accurate Supervisor with Programmable Delay datasheet](#)
- Texas Instruments, [TPS7A91EVM-831 Evaluation Module user's guide](#)
- Texas Instruments, [How to Measure LDO Noise white paper](#)
- Texas Instruments, [Pros and Cons of Using a Feedforward Capacitor with a Low-Dropout Regulator application note](#)
- Texas Instruments, [Semiconductor and IC Package Thermal Metrics application note](#)

8.3 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. Click on *Notifications* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

8.4 Support Resources

[TI E2E™ support forums](#) are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's [Terms of Use](#).

8.5 Trademarks

TI E2E™ is a trademark of Texas Instruments.

All trademarks are the property of their respective owners.

8.6 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

8.7 Glossary

[TI Glossary](#) This glossary lists and explains terms, acronyms, and definitions.

9 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

Changes from Revision A (June 2020) to Revision B (September 2026) Page

- Updated the numbering format for tables, figures, and cross-references throughout the document..... [1](#)
- Updated all values in the *Thermal Information* section.....[4](#)

Changes from Revision * (June 2017) to Revision A (June 2020) Page

- Changed *Applications* section [1](#)
- Changed $V_{IT(PG)}$ parameter to $V_{IT(PG-)}$, added $V_{IT(PG+)}$ parameter row to *Electrical Characteristics* table.....[5](#)

10 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this datasheet, see also the left-hand navigation.

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package Pins	Package qty Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
TPS7A9001DSKR	Active	Production	SON (DSK) 10	3000 LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	1CEP
TPS7A9001DSKR.A	Active	Production	SON (DSK) 10	3000 LARGE T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	1CEP
TPS7A9001DSKT	Active	Production	SON (DSK) 10	250 SMALL T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	1CEP
TPS7A9001DSKT.A	Active	Production	SON (DSK) 10	250 SMALL T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	1CEP
TPS7A9001DSKTG4	Active	Production	SON (DSK) 10	250 SMALL T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	1CEP
TPS7A9001DSKTG4.A	Active	Production	SON (DSK) 10	250 SMALL T&R	Yes	NIPDAU	Level-2-260C-1 YEAR	-40 to 125	1CEP

⁽¹⁾ **Status:** For more details on status, see our [product life cycle](#).

⁽²⁾ **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

⁽⁴⁾ **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

⁽⁵⁾ **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.


⁽⁶⁾ **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.


TAPE AND REEL INFORMATION



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TPS7A9001DSKR	SON	DSK	10	3000	178.0	8.4	2.75	2.75	0.95	4.0	8.0	Q2
TPS7A9001DSKT	SON	DSK	10	250	178.0	8.4	2.75	2.75	0.95	4.0	8.0	Q2
TPS7A9001DSKTG4	SON	DSK	10	250	178.0	8.4	2.75	2.75	0.95	4.0	8.0	Q2

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal


Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TPS7A9001DSKR	SON	DSK	10	3000	205.0	200.0	33.0
TPS7A9001DSKT	SON	DSK	10	250	205.0	200.0	33.0
TPS7A9001DSKTG4	SON	DSK	10	250	205.0	200.0	33.0

DSK 10

WSON - 0.8 mm max height

2.5 x 2.5 mm, 0.5 mm pitch

PLASTIC SMALL OUTLINE - NO LEAD



Images above are just a representation of the package family, actual package may vary.
Refer to the product data sheet for package details.



DSK0010A

4218903/C 09/2025


- 
- TEXAS
INSTRUMENTS**
www.ti.com

EXAMPLE BOARD LAYOUT


DSK0010A

WSN - 0.8 mm max height

PLASTIC SMALL OUTLINE - NO LEAD



LAND PATTERN EXAMPLE
SCALE:20X



SOLDER MASK DETAILS

4218903/C 09/2025

NOTES: (continued)


4. This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/slue271).
5. Vias are optional depending on application, refer to device data sheet. If some or all are implemented, recommended via locations are shown.

EXAMPLE STENCIL DESIGN

DSK0010A

WSN - 0.8 mm max height

PLASTIC SMALL OUTLINE - NO LEAD



SOLDER PASTE EXAMPLE
BASED ON 0.125 mm THICK STENCIL

EXPOSED PAD 11
84% PRINTED SOLDER COVERAGE BY AREA
SCALE:20X

4218903/C 09/2025

NOTES: (continued)

6. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#), [TI's General Quality Guidelines](#), or other applicable terms available either on [ti.com](#) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2026, Texas Instruments Incorporated

Last updated 10/2025