

TABLE OF CONTENTS

SHEET NO.	SHEET NAME
1	Block diagram
2	Table of Contents
3	Muxing_Block_diagram
4	Pwr_RST_LEDs
5	Power_Input_REG
6	Current Sensors
7	LP8752J_PMIC
8	LP Connector
9	BP_LP_RNR_Options
10	HD_Conn_JTAG_HDR
11	XDS110 Interface_1A
12	XDS110 Interface_1B
13	CAN & VPP_Supply
14	SOP selection
15	Tempsensor
16	FTDI_Interface
17	FTDI_Interface_Power
18	CAN Interface_LEDs
19	Analog_Mux_1A
20	Analog_Mux_1B
21	HD_connector_DCA
22	Hardware

MUX SETTINGS


Switch Refdes	Default position	Position for STAND ALONE mode*	Position for DCA1000 mode	Position for 40Pin LP/BP
S1	OFF (SPI-1)	OFF	OFF	OFF
S2	ON (40pin)	Default position	Default position	ON
S3	ON (FTDI)	ON	Default position	OFF
S4	ON (FTDI/40pin/J16)	ON	OFF	ON
S5 ¹	ON (XDS110)	Default position	Default position	Default position
S6	ON (FTDI)	ON	OFF	OFF
S7	ON (FTDI)	ON	OFF	OFF
S8	OFF (60pin)	Default position	OFF	ON
S9	OFF (60pin)	Default position	OFF	ON
S10	ON (FTDI)	ON	Default position	OFF
S11	ON (FTDI)	ON	Default position	OFF
S12	ON (XDS110)	Default position	Default position	Default position

Table 1 : Switch settings for different sources

*Standalone mode means the combination of Starter kit and MMWAVEICBOOST


(1)S5 has RS232 connections from 40pin/FTDI/60pin/XDS110. Default position will be XDS110.

MUXING BLOCK DIAGRAM



POWER SUPPLY CONNECTOR





VOLTAGE RANGE= 5V TO 36V
MAX. CURRENT = 2A




Note : Replace the capacitor(PN:597D476X9050Z2T)in C22 and C23
if the input voltage exceeds 5V

VIN= 5V : Short P3, Mount R116 and do not short P7
VIN= >5V : Short P3,P7 and Remove R116


RESET AND LEDS
INDICATION LEDS




POWER SUPPLY INPUT 5V TO 3.3V OUTPUT





5V SUPPLY FROM JACK



POWER SUPPLY INPUT(6V-36V) TO 5V OUTPUT








5V SUPPLY FROM THE 40PIN LP/BP CONNECTOR





Texas Instruments and/or its licensors do not warrant the accuracy or completeness of this specification or any information contained therein. Texas Instruments and/or its licensors do not warrant that this design will meet the specifications, will be suitable for your application or fit for any particular purpose, or will operate in an implementation. Texas Instruments and/or its licensors do not warrant that the design is production worthy. You should completely validate and test your design implementation to confirm the system functionality for your application.

Orderable: MMWAVEICBOOST	Designed for: Public Release	Mod. Date: 10/12/2018
TID #: N/A	Project Title: MMWAVEICBOOST	
Number: PROC074	Rev: A	Sheet Title:
SVN Rev: Version control disabled	Assembly Variant: 001	Sheet: 5 of 22
Drawn By:	File: PROC074A_PWR_INPUT_REG.SchDoc	Size: B
Engineer: Chethan Kumar Y.B	Contact: http://www.ti.com/support	http://www.ti.com
		© Texas Instruments 2018


Current Sensors




PMIC (3.3V, 1.2V, 1.8V,1.0V OUTPUTS)



CURRENT SENSE RESISTORS




SNUBBER ON SWITCHING NODES



Texas Instruments and/or its licensors do not warrant the accuracy or completeness of this specification or any information contained therein. Texas Instruments and/or its licensors do not warrant that this design will meet the specifications, will be suitable for your application or fit for any particular purpose, or will operate in an implementation. Texas Instruments and/or its licensors do not warrant that the design is production worthy. You should completely validate and test your design implementation to confirm the system functionality for your application.

Orderable: MMWAVEICBOOST	Designed for: Public Release	Mod. Date: 10/12/2018
TID #: N/A	Project Title: MMWAVEICBOOST	
Number: PROC074	Rev: A	Sheet Title:
SVN Rev: Version control disabled	Assembly Variant: 001	Sheet: 7 of 22
Drawn By:	File: PROC074A_LP8752J_PMIC.SchDoc	Size: B
Engineer: Chethan Kumar Y.B	Contact: http://www.ti.com/support	

BP/LP CONNECTOR



A

B

C

D

A


B

C


D

BP/LP RNR OPTIONS


RNR FOR MCUCLKOUT



RNR FOR SYNC IN




RNR FOR PMIC ENABLE




RNR FOR WARMRST




RNR FOR PMIC CLKOUT



RNR FOR DSS LOGGER




LP/BP SPARE PINS HEADER 1





RNR FOR SYNC OUT




PULL UPs/DOWNs RESISTORS FOR I2C,WARMRST,NERROUT, NERRIN, RS232, SYNC_IN & HOST_IN




HD CONNECTOR FOR LVDS AND JTAG




JTAG DEBUG CONNECTOR



JTAG TRACE DMM INTERFACE HEADER







XDS/14PIN JTAG SELECTION



Texas Instruments and/or its licensors do not warrant the accuracy or completeness of this specification or any information contained therein. Texas Instruments and/or its licensors do not warrant that this design will meet the specifications, will be suitable for your application or fit for any particular purpose, or will operate in an implementation. Texas Instruments and/or its licensors do not warrant that the design is production worthy. You should completely validate and test your design implementation to confirm the system functionality for your application.

Orderable: MMWAVEICBOOST	Designed for: Public Release	Mod. Date: 10/12/2018
TID #: N/A	Project Title: MMWAVEICBOOST	
Number: PROC074	Rev: A	Sheet Title:
SVN Rev: Version control disabled	Assembly Variant: 001	Sheet: 10 of 22
Drawn By:	File: PROC074A_HD_Conn_JTAG_HDR.SchDoc	Size: B
Engineer: Chethan Kumar Y.B	Contact: http://www.ti.com/support	


XDS110(1/2)



Texas Instruments and/or its licensors do not warrant the accuracy or completeness of this specification or any information contained therein. Texas Instruments and/or its licensors do not warrant that this design will meet the specifications, will be suitable for your application or fit for any particular purpose, or will operate in an implementation. Texas Instruments and/or its licensors do not warrant that the design is production worthy. You should completely validate and test your design implementation to confirm the system functionality for your application.

Orderable: MMWAVEICBOOST	Designed for: Public Release	Mod. Date: 10/12/2018
TID #: N/A	Project Title: MMWAVEICBOOST	
Number: PROC074	Rev: A	Sheet Title:
SVN Rev: Version control disabled	Assembly Variant: 001	Sheet: 11 of 22
Drawn By:	File: PROC074A_XDS110_Interface_1A.SchDoc	Size: B
Engineer: Chethan Kumar Y.B	Contact: http://www.ti.com/support	


XDS110(2/2)




Texas Instruments and/or its licensors do not warrant the accuracy or completeness of this specification or any information contained therein. Texas Instruments and/or its licensors do not warrant that this design will meet the specifications, will be suitable for your application or fit for any particular purpose, or will operate in an implementation. Texas Instruments and/or its licensors do not warrant that the design is production worthy. You should completely validate and test your design implementation to confirm the system functionality for your application.

Orderable: MMWAVEICBOOST	Designed for: Public Release	Mod. Date: 10/12/2018
TID #: N/A	Project Title: MMWAVEICBOOST	
Number: PROC074	Rev: A	Sheet Title:
SVN Rev: Version control disabled	Assembly Variant: 001	Sheet: 12 of 22
Drawn By:	File: PROC074A_XDS110_Interface_1B.SchDoc	Size: B
Engineer: Chethan Kumar Y.B	Contact: http://www.ti.com/support	


CAN_FD TRANSCEIVER



CAN/SPI SELECTION




VPP Supply




Texas Instruments and/or its licensors do not warrant the accuracy or completeness of this specification or any information contained therein. Texas Instruments and/or its licensors do not warrant that this design will meet the specifications, will be suitable for your application or fit for any particular purpose, or will operate in an implementation. Texas Instruments and/or its licensors do not warrant that the design is production worthy. You should completely validate and test your design implementation to confirm the system functionality for your application.


Orderable: MMWAVEICBOOST	Designed for: Public Release	Mod. Date: 10/12/2018
TID #: N/A	Project Title: MMWAVEICBOOST	
Number: PROC074	Rev: A	Sheet Title:
SVN Rev: Version control disabled	Assembly Variant: 001	Sheet: 13 of 22
Drawn By: Chethan Kumar Y.B	File: PROC074A_CAN_Interface.SchDoc	Size: B
Engineer: Chethan Kumar Y.B	Contact: http://www.ti.com/support	



ONBOARD TEMP SENSORS




I2C ADDRESS: 100 1001
TEMP SENSOR AWAY FROM PMIC



I2C Address : 100 1000
TEMP SENSOR CLOSE TO PMIC

FTDI INTERFACE




Texas Instruments and/or its licensors do not warrant the accuracy or completeness of this specification or any information contained therein. Texas Instruments and/or its licensors do not warrant that this design will meet the specifications, will be suitable for your application or fit for any particular purpose, or will operate in an implementation. Texas Instruments and/or its licensors do not warrant that the design is production worthy. You should completely validate and test your design implementation to confirm the system functionality for your application.



Orderable: MMWAVEICBOOST	Designed for: Public Release	Mod. Date: 10/12/2018
TID #: N/A	Project Title: MMWAVEICBOOST	
Number: PROC074	Rev: A	Sheet Title:
SVN Rev: Version control disabled	Assembly Variant: 001	Sheet: 16 of 22
Drawn By:	File: PROC074A_FTDI_Interface.SchDoc	Size: B
Engineer: Chethan Kumar Y.B	Contact: http://www.ti.com/support	

FTDI POWER SECTION




3.3V LDO FOR FTDI




THIS 3.3V LDO WILL TURN ON
EITHER FOR IWR6XXX MODULE BOARD
OR CARRIER BOARD IS POWERED UP



FTDI EEPROM




3.3V SUPPLY SELECTION JUMPER




Texas Instruments and/or its licensors do not warrant the accuracy or completeness of this specification or any information contained therein. Texas Instruments and/or its licensors do not warrant that this design will meet the specifications, will be suitable for your application or fit for any particular purpose, or will operate in an implementation. Texas Instruments and/or its licensors do not warrant that the design is production worthy. You should completely validate and test your design implementation to confirm the system functionality for your application.

Orderable: MMWAVEICBOOST	Designed for: Public Release	Mod. Date: 10/12/2018
TID #: N/A	Project Title: MMWAVEICBOOST	
Number: PROC074	Rev: A	Sheet Title:
SVN Rev: Version control disabled	Assembly Variant: 001	Sheet: 17 of 22
Drawn By:	File: PROC074A_FTDI_Interface_PWR.SchDoc	Size: B
Engineer: Chethan Kumar Y.B	Contact: http://www.ti.com/support	


CAN TRANSCEIVER




RESET & SOP STATUS INDICATION



3.3V TO 5V BOOST CONVERTER









5V & 3.3V SUPPLY INDICATION



Texas Instruments and/or its licensors do not warrant the accuracy or completeness of this specification or any information contained therein. Texas Instruments and/or its licensors do not warrant that this design will meet the specifications, will be suitable for your application or fit for any particular purpose, or will operate in an implementation. Texas Instruments and/or its licensors do not warrant that the design is production worthy. You should completely validate and test your design implementation to confirm the system functionality for your application.








ANALOG MUX BETWEEN FTDI , DCA & 40PIN HDR 1/2




EN	IN	NO to COM/ COM to NO	NC to COM/ COM to NC
L	L	OFF	ON
L	H	ON	OFF
H	X	OFF	OFF

Texas Instruments and/or its licensors do not warrant the accuracy or completeness of this specification or any information contained therein. Texas Instruments and/or its licensors do not warrant that this design will meet the specifications, will be suitable for your application or fit for any particular purpose, or will operate in an implementation. Texas Instruments and/or its licensors do not warrant that the design is production worthy. You should completely validate and test your design implementation to confirm the system functionality for your application.



ANALOG MUX BETWEEN FTDI , DCA & 40PIN HDR (2/2)



60PIN HD CONNECTOR FOR DCA1000



MIPI-60 DEBUG TRACE CONNECTOR



Texas Instruments and/or its licensors do not warrant the accuracy or completeness of this specification or any information contained therein. Texas Instruments and/or its licensors do not warrant that this design will meet the specifications, will be suitable for your application or fit for any particular purpose, or will operate in an implementation. Texas Instruments and/or its licensors do not warrant that the design is production worthy. You should completely validate and test your design implementation to confirm the system functionality for your application.

