NOTES:
1) Ref Des' 100 or greater are add-on parts.

Vout = +/-25V @ 10A (250W Max)

Vin = 6V to 16V

25Arms at 6Vin

Von = 9.0V
Voff = 6.0V

fosc = 200kHz
fsw = 100kHz
tdead = 250nS

220KHz SYNC

>15nS, >3V, <7V

Texas Instruments and/or its licensors do not warrant the accuracy or completeness of this specification or any information contained therein. Texas Instruments and/or its licensors do not warrant that this design will meet the specifications, will be suitable for your application or fit for any particular purpose, or will operate in an implementation. Texas Instruments and/or its licensors do not warrant that the design is production worthy. You should completely validate and test your design implementation to confirm the system functionality for your application.

| | | | |
|---|---|---|---|
| Orderable: N/A | | Designed for: Public Release | Mod. Date: 11/2/2017 |
| TID #: | | Project Title: LM25037 Push Pull | |
| Number: PMP11186 | Rev: B | Sheet Title: | |
| SVN Rev: Version control disabled | | Assembly Variant: 001 | Sheet: 1 of 1 |
| Drawn By: | | File: PMP11186 REVB.SchDoc | Size: B |
| Engineer: J Betten | | Contact: http://www.ti.com/support | |

Texas Instruments
http://www.ti.com

© Texas Instruments 2015