

TPS56C215 3.8V to 17V Input, 12A, Synchronous, Step-Down SWIFT™ Converter

1 Features

- Integrated 7.8mΩ and 3.2mΩ MOSFETs
- Supports 12A continuous I_{OUT}
- 4.5V start-up without external 5.0V bias
- 0.6V ±1% reference voltage across full temperature range
- 0.6V to 5.5V output voltage range
- Supports ceramic output capacitors
- D-CAP3™ control mode for fast transient response
- Selectable forced continuous conduction mode (FCCM) for tight output voltage ripple or auto-skipping Eco-mode for high light-load efficiency
- Selectable F_{SW} of 400kHz, 800kHz, and 1.2MHz
- Monotonic start-up into prebiased outputs
- Two adjustable current limit settings with hiccup re-start
- Optional external 5V bias for enhanced efficiency
- Adjustable soft start with a default 1ms soft-start time
- –40°C to 150°C operating junction temperature
- Small 3.5mm × 3.5mm HotRod™ QFN package
- Pin-to-pin compatible with 8A TPS568215
- Create a custom design using TPS56C215 with the WEBENCH® Power Designer

2 Applications

- [Server, cloud-computing, storage](#)
- [Telecom and networking, point-of-load \(POL\)](#)
- [IPCs, factory automation, PLC, test measurement](#)
- [High-end DTV](#)


3 Description

The TPS56C215 is a small monolithic 12A synchronous buck converter with an adaptive on-time D-CAP3 control mode. The device integrates low R_{DS(on)} power MOSFETs that enable high efficiency and offers ease-of-use with minimum external component count for space-conscious power systems. Competitive features include a very accurate reference voltage, fast load transient response, auto-skip mode operation for light load efficiency, adjustable current limit and no requirement for external compensation. A forced continuous conduction mode helps meet tight voltage regulation accuracy requirements for performance DSPs and FPGAs. The TPS56C215 is available in a thermally enhanced, 18-pin, HotRod QFN package and is designed to operate from –40°C to 150°C junction temperature.


Package Information

| PART NUMBER | PACKAGE ⁽¹⁾ | PACKAGE SIZE ⁽²⁾ |
|-------------|------------------------|-----------------------------|
| TPS56C215 | RNN (VQFN-HR, 18) | 3.5mm × 3.5mm |

- (1) For more information, see [Section 10](#).
- (2) The package size (length × width) is a nominal value and includes pins, where applicable.



Typical Application



Efficiency vs Output Current



Table of Contents

| | | | |
|--|-----------|--|-----------|
| 1 Features | 1 | 7 Application and Implementation | 21 |
| 2 Applications | 1 | 7.1 Application Information..... | 21 |
| 3 Description | 1 | 7.2 Typical Application..... | 21 |
| 4 Pin Configuration and Functions | 3 | 7.3 Power Supply Recommendations..... | 25 |
| 5 Specifications | 4 | 7.4 Layout..... | 25 |
| 5.1 Absolute Maximum Ratings..... | 4 | 8 Device and Documentation Support | 29 |
| 5.2 ESD Ratings..... | 4 | 8.1 Device Support..... | 29 |
| 5.3 Recommended Operating Conditions..... | 4 | 8.2 Receiving Notification of Documentation Updates...30 | |
| 5.4 Thermal Information..... | 5 | 8.3 Support Resources..... | 30 |
| 5.5 Electrical Characteristics..... | 5 | 8.4 Trademarks..... | 30 |
| 5.6 Timing Requirements..... | 6 | 8.5 Electrostatic Discharge Caution..... | 30 |
| 5.7 Typical Characteristics..... | 7 | 8.6 Glossary..... | 30 |
| 6 Detailed Description | 13 | 9 Revision History | 31 |
| 6.1 Overview..... | 13 | 10 Mechanical, Packaging, and Orderable | |
| 6.2 Functional Block Diagram..... | 14 | Information | 32 |
| 6.3 Feature Description..... | 14 | 10.1 Package Marking..... | 32 |
| 6.4 Device Functional Modes..... | 20 | | |

4 Pin Configuration and Functions




Figure 4-1. RNN Package, 18-Pin VQFN

Table 4-1. Pin Functions

| PIN | | TYPE ⁽¹⁾ | DESCRIPTION |
|-------|-------------------|---------------------|--|
| NAME | NO. | | |
| BOOT | 1 | I | Supply input for the gate drive voltage of the high-side MOSFET. Connect the bootstrap capacitor between BOOT and SW. |
| VIN | 2,11 | P | Input voltage supply pin for the control circuitry. Connect the input decoupling capacitors between VIN and PGND. |
| PGND | 3, 4, 5, 8, 9, 10 | G | Power GND terminal for the controller circuit and the internal circuitry. Connect to AGND with a short trace. |
| SW | 6, 7 | O | Switch node terminal. Connect the output inductor to this pin. |
| AGND | 12 | G | Ground of internal analog circuitry. Connect AGND to PGND plane with a short trace. |
| FB | 13 | I | Converter feedback input. Connect to the center tap of the resistor divider between output voltage and AGND. |
| SS | 14 | O | Soft-Start time selection pin. Connecting an external capacitor sets the soft-start time and if no external capacitor is connected, the converter starts up in 1 ms. |
| EN | 15 | I | Enable input control, leaving this pin floating enables the converter. This pin can also be used to adjust the input UVLO by connecting to the center tap of the resistor divider between VIN and EN. |
| PGOOD | 16 | O | Open-drain power good indicator, this pin asserted low if output voltage is out of PGOOD threshold, overvoltage, or if the device is under thermal shutdown, EN shutdown or during soft start. |
| VREG5 | 17 | I/O | 4.7-V internal LDO output which can also be driven externally with a 5-V input. This pin supplies voltage to the internal circuitry and gate driver. Bypass this pin with a 4.7- μ F capacitor. |
| MODE | 18 | I | Switching frequency, current limit selection and light load operation mode selection pin. Connect this pin to a resistor divider from VREG5 and AGND for different MODE options shown in Table 6-3 . |

(1) I = input, P = power, G = ground, O = output

5 Specifications

5.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted) ⁽¹⁾

| | | MIN | MAX | UNIT |
|--------------------------------|--------------------------------------|------|------|------|
| Input voltage | V _{IN} | -0.3 | 20 | V |
| | SW | -2 | 19 | |
| | SW (10-ns transient) | -5 | 25 | |
| | V _{IN-SW} | | 22 | |
| | V _{IN-SW} (10-ns transient) | | 25 | |
| | EN | -0.3 | 6.5 | |
| | BOOT –SW | -0.3 | 6.5 | |
| | BOOT –SW (10 ns transient) | -0.3 | 7.5 | |
| | BOOT | -0.3 | 25.5 | |
| | SS, MODE, FB | -0.3 | 6.5 | |
| | VREG5 | -0.3 | 6 | |
| Output voltage | PGOOD | -0.3 | 6.5 | V |
| Output current ⁽²⁾ | I _{OUT} | | 14 | A |
| Operating junction temperature | T _J | -40 | 150 | °C |
| Storage temperature | T _{stg} | -55 | 150 | °C |

- (1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) to be consistent with the TI reliability requirement of 100k Power-On-Hours at 105°C junction temperature, the output current must not exceed 14A continuously under 100% duty operation as to prevent electromigration failure in the solder. Higher junction temperature or longer power-on hours are achievable at lower than 14A continuous output current.

5.2 ESD Ratings

| | | VALUE | UNIT |
|--|--|-------|------|
| V _(ESD) Electrostatic discharge | Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001 ⁽¹⁾ | ±2000 | V |
| | Charged-device model (CDM), per JEDEC specification JESD22-C101 ⁽²⁾ | ±500 | |

- (1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
- (2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

5.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

| | | MIN | NOM | MAX | UNIT |
|--------------------------------|-------------------|------|-----|------|------|
| Input voltage | V _{IN} | 3.8 | | 17 | V |
| | SW | -1.8 | | 17 | V |
| | BOOT | -0.1 | | 23.5 | V |
| | VREG5 | -0.1 | | 5.2 | V |
| Output current | I _{LOAD} | 0 | | 12 | A |
| Operating junction temperature | T _J | -40 | | 150 | °C |

5.4 Thermal Information

| THERMAL METRIC ⁽¹⁾ | | RNN (VQFN-HR) | UNIT |
|-------------------------------|--|---------------|------|
| | | 18 PINS | |
| R _{θJA} | Junction-to-ambient thermal resistance | 29.5 | °C/W |
| R _{θJC(top)} | Junction-to-case (top) thermal resistance | 17.0 | °C/W |
| R _{θJB} | Junction-to-board thermal resistance | 8.6 | °C/W |
| ψ _{JT} | Junction-to-top characterization parameter | 0.4 | °C/W |
| ψ _{JB} | Junction-to-board characterization parameter | 8.6 | °C/W |
| R _{θJC(bot)} | Junction-to-case (bottom) thermal resistance | 0.5 | °C/W |

(1) For more information about traditional and new thermal metrics, see the [Semiconductor and IC Package Thermal Metrics](#) application note.

5.5 Electrical Characteristics

T_J = –40°C to 150°C, V_{IN} = 12V (unless otherwise noted)

| PARAMETER | | CONDITIONS | MIN | TYP | MAX | UNIT |
|-------------------------|-----------------------------------|---|-------|-------|--------|------|
| SUPPLY CURRENT | | | | | | |
| I _{IN} | VIN supply current | T _J = 25°C, V _{EN} = 5 V, non switching | | 146 | | μA |
| I _{VINSDN} | VIN shutdown current | T _J = 25°C, V _{EN} = 0 V | | 9.3 | | μA |
| LOGIC THRESHOLD | | | | | | |
| V _{ENH} | EN H-level threshold voltage | | 1.175 | 1.225 | 1.3 | V |
| V _{ENL} | EN L-level threshold voltage | | 1.025 | 1.104 | 1.15 | V |
| V _{ENHYS} | | | | 0.121 | | V |
| I _{ENp1} | EN pullup current | V _{EN} = 1.0 V | 0.35 | 1.91 | 2.95 | μA |
| I _{ENp2} | | V _{EN} = 1.3 V | 3 | 4.197 | 5.5 | μA |
| FEEDBACK VOLTAGE | | | | | | |
| V _{FB} | FB voltage | T _J = 25°C | 598 | 600 | 602 | mV |
| | | T _J = 0°C to 85°C | 597.5 | 600 | 602.5 | mV |
| | | T _J = –40°C to 85°C | 594 | 600 | 602.5 | mV |
| | | T _J = –40°C to 150°C | 594 | 600 | 606 | mV |
| LDO VOLTAGE | | | | | | |
| V _{REG5} | LDO output voltage | T _J = –40°C to 150°C | 4.58 | 4.7 | 4.83 | V |
| I _{LIM5} | LDO output current limit | T _J = –40°C to 150°C | 100 | 150 | 200 | mA |
| MOSFET | | | | | | |
| R _{DS(on)H} | High side switch resistance | T _J = 25°C, V _{VREG5} = 4.7 V | | 7.8 | | mΩ |
| R _{DS(on)L} | Low side switch resistance | T _J = 25°C, V _{VREG5} = 4.7 V | | 3.2 | | mΩ |
| SOFT START | | | | | | |
| I _{ss} | Soft-start charge current | T _J = –40°C to 150°C | 4.9 | 6 | 7.1 | μA |
| CURRENT LIMIT | | | | | | |
| I _{OCL} | Current Limit (Low side sourcing) | ILIM-1 option, valley current | 9.775 | 11.5 | 13.225 | A |
| | | ILIM option, valley current | 11.73 | 13.8 | 15.87 | A |
| | Current limit (low side negative) | Valley current | | 4 | | A |
| POWER GOOD | | | | | | |
| V _{PGOODTH} | PGOOD threshold | V _{FB} falling (fault) | | 84% | | |
| | | V _{FB} rising (good) | | 93% | | |
| | | V _{FB} rising (fault) | | 116% | | |
| | | V _{FB} falling (good) | | 108% | | |

5.5 Electrical Characteristics (continued)

$T_J = -40^{\circ}\text{C}$ to 150°C , $V_{IN} = 12\text{V}$ (unless otherwise noted)

| PARAMETER | | CONDITIONS | MIN | TYP | MAX | UNIT |
|---|------------------------------|-----------------------------------|-----|-----------------------|-----|--------------------|
| OUTPUT UNDERVOLTAGE AND OVERVOLTAGE PROTECTION | | | | | | |
| V_{OVP} | Output OVP threshold | OVP detect | | $121\% \times V_{FB}$ | | |
| V_{UVP} | Output UVP threshold | Hiccup detect | | $70\% \times V_{FB}$ | | |
| THERMAL SHUTDOWN | | | | | | |
| T_{SDN} | Thermal shutdown threshold | Shutdown temperature | | 160 | | $^{\circ}\text{C}$ |
| | | Hysteresis | | 15 | | $^{\circ}\text{C}$ |
| UVLO | | | | | | |
| UVLO | UVLO threshold | VREG5 rising voltage | | 4.25 | | V |
| | | VREG5 falling voltage | | 3.52 | | V |
| | | VREG5 hysteresis | | 730 | | mV |
| UVLO, VREG5 = 4.7V | UVLO threshold, VREG5 = 4.7V | VIN rising voltage, VREG5 = 4.7V | | 3.32 | | V |
| | | VIN falling voltage, VREG5 = 4.7V | | 3.24 | | V |
| | | VIN hysteresis, VREG5 = 4.7V | | 80 | | mV |

5.6 Timing Requirements

| PARAMETER | | CONDITIONS | MIN | TYP | MAX | UNIT |
|---|--|---|-----|-----|-----|-------|
| ON-TIME TIMER CONTROL | | | | | | |
| t_{ON} | SW on time ⁽¹⁾ | $V_{IN} = 12\text{V}$, $V_{OUT} = 3.3\text{V}$, $F_{SW} = 800\text{kHz}$ | 310 | 340 | 380 | ns |
| $t_{ON\ min}$ | SW Minimum on time | $V_{IN} = 17\text{V}$, $V_{OUT} = 0.6\text{V}$, $F_{SW} = 1200\text{kHz}$ | | 60 | | ns |
| t_{OFF} | SW Minimum off time | 25°C , $V_{FB} = 0.5\text{V}$ | | | 310 | ns |
| SOFT START | | | | | | |
| t_{SS} | Soft-start time | Internal soft-start time | | 1.2 | | ms |
| OUTPUT UNDERVOLTAGE AND OVERVOLTAGE PROTECTION | | | | | | |
| t_{UVPDEL} | Output hiccup delay relative to SS time | UVP detect | | 1 | | cycle |
| t_{UVPEN} | Output hiccup enable delay relative to SS time | UVP detect | | 14 | | cycle |

(1) Specified by design

5.7 Typical Characteristics




Figure 5-1. Quiescent Current vs Temperature




Figure 5-2. Shutdown Current vs Temperature




Figure 5-3. Feedback Voltage vs Temperature




Figure 5-4. Soft-Start Charge Current vs Temperature




Figure 5-5. Enable Pullup Current, V_{EN} = 1.0 V




Figure 5-6. Enable Pullup Current, V_{EN} = 1.3 V

5.7 Typical Characteristics (continued)




Figure 5-7. PGOOD Threshold vs Temperature




Figure 5-8. Current Limit vs Temperature




Figure 5-9. Efficiency, DCM Mode, $f_{sw} = 400 \text{ kHz}$




Figure 5-10. Efficiency, FCCM Mode, $f_{sw} = 400 \text{ kHz}$




Figure 5-11. Efficiency, DCM Mode, $f_{sw} = 800 \text{ kHz}$




Figure 5-12. Efficiency, FCCM Mode, $f_{sw} = 800 \text{ kHz}$

5.7 Typical Characteristics (continued)




Figure 5-13. Efficiency, DCM Mode, $f_{sw} = 1200 \text{ kHz}$




Figure 5-14. Efficiency, FCCM Mode, $f_{sw} = 1200 \text{ kHz}$




Figure 5-15. Efficiency, DCM Mode, $f_{sw} = 400 \text{ kHz}$




Figure 5-16. Efficiency, FCCM Mode, $f_{sw} = 400 \text{ kHz}$




Figure 5-17. Efficiency, DCM Mode, $f_{sw} = 800 \text{ kHz}$




Figure 5-18. Efficiency, FCCM Mode, $f_{sw} = 800 \text{ kHz}$

5.7 Typical Characteristics (continued)




Figure 5-19. Efficiency, DCM Mode, $f_{SW} = 1200 \text{ kHz}$




Figure 5-20. Efficiency, FCCM Mode, $f_{SW} = 1200 \text{ kHz}$




Figure 5-21. Efficiency, Ext-VCC vs Internal-VCC, DCM Mode, $f_{SW} = 800 \text{ kHz}$




Figure 5-22. Load Regulation, $f_{SW} = 800 \text{ kHz}$




Figure 5-23. f_{SW} Load Regulation, Mode = DCM, $f_{SW} = 400 \text{ kHz}$




Figure 5-24. f_{SW} Load Regulation, Mode = DCM, $f_{SW} = 800 \text{ kHz}$

5.7 Typical Characteristics (continued)




Figure 5-25. F_{SW} Load Regulation, Mode = DCM, $F_{SW} = 1200$ kHz




Figure 5-26. F_{SW} Load Regulation, Mode = FCCM, $F_{SW} = 400$ kHz




Figure 5-27. F_{SW} Load Regulation, Mode = FCCM, $F_{SW} = 800$ kHz




Figure 5-28. F_{SW} Load Regulation, Mode = FCCM, $F_{SW} = 1200$ kHz




Figure 5-29. F_{SW} Load Regulation, Mode = FCCM, $F_{SW} = 400$ kHz




Figure 5-30. F_{SW} Load Regulation, Mode = FCCM, $F_{SW} = 800$ kHz

5.7 Typical Characteristics (continued)




Figure 5-31. F_{SW} Load Regulation, Mode = FCCM, $F_{SW} = 1200$ kHz




Figure 5-32. F_{SW} Load Regulation, Mode = DCM, $F_{SW} = 400$ kHz




Figure 5-33. F_{SW} Load Regulation, Mode = DCM, $F_{SW} = 800$ kHz




Figure 5-34. F_{SW} Load Regulation, Mode = DCM, $F_{SW} = 1200$ kHz

6 Detailed Description

6.1 Overview


The TPS56C215 is a high-density, synchronous, step-down buck converter which can operate from 3.8-V to 17-V input voltage (V_{IN}). The device has 7.8-m Ω and 3.2-m Ω integrated MOSFETs that enable high efficiency up to 12 A. The device employs D-CAP3 control mode that provides fast transient response with no external compensation components and an accurate feedback voltage. The control topology provides seamless transition between FCCM operating mode at higher load condition and DCM/Eco-mode operation at lighter load condition. DCM/Eco-mode allows the TPS56C215 to maintain high efficiency at light load. The TPS56C215 is able to adapt to both low equivalent series resistance (ESR) output capacitors such as POSCAP or SP-CAP, and ultra-low ESR ceramic capacitors.

The TPS56C215 has three selectable switching frequencies (F_{SW}) (400 kHz, 800 kHz, and 1200 kHz), which gives the flexibility to optimize the design for higher efficiency or smaller size. There are two selectable current limits. All these options are configured by choosing the right voltage on the MODE pin.

The TPS56C215 has a 4.7-V internal LDO that creates bias for all internal circuitry. There is a feature to overdrive this internal LDO with an external voltage on the VREG5 pin which improves the efficiency of the converter. The undervoltage lockout (UVLO) circuit monitors the VREG5 pin voltage to protect the internal circuitry from low input voltages. The device has an internal pullup current source on the EN pin which can enable the device even with the pin floating.

Soft-start time can be selected by connecting a capacitor to the SS pin. The device is protected from output short, undervoltage, and overtemperature conditions.

6.2 Functional Block Diagram



6.3 Feature Description

6.3.1 PWM Operation and D-CAP3™ Control Mode

The TPS56C215 operates using the adaptive on-time PWM control with a proprietary D-CAP3 control mode which enables low external component count with a fast load transient response while maintaining a good output voltage accuracy. At the beginning of each switching cycle, the high-side MOSFET is turned on for an on-time set by an internal one shot timer. This on-time is set based on the input voltage of the converter, output voltage of the converter, and the pseudo-fixed frequency, hence this type of control topology is called an adaptive on-time control. The one-shot timer resets and turns on again after the feedback voltage (V_{FB}) falls below the internal reference voltage (V_{REF}). An internal ramp is generated which is fed to the FB pin to simulate the output voltage ripple. This enables the use of very low-ESR output capacitors such as multi-layered ceramic caps (MLCC). No external current sense network or loop compensation is required for DCAP3 control topology.

The TPS56C215 includes an error amplifier that makes the output voltage very accurate. This error amplifier is absent in other flavors of D-CAP3. For any control topology that is compensated internally, there is a range of the output filter the control topology can support. The output filter used with the TPS56C215 is a low-pass L-C circuit. This L-C filter has double pole that is described in [Equation 1](#).

$$f_P = \frac{1}{2 \times \pi \times \sqrt{L_{OUT} \times C_{OUT}}} \quad (1)$$

At low frequencies, the overall loop gain is set by the output set-point resistor divider network and the internal gain of the TPS56C215. The low frequency L-C double pole has a 180 degree in-phase. At the output filter frequency, the gain rolls off at a –40-dB per decade rate and the phase drops rapidly. The internal ripple generation network introduces a high-frequency zero that reduces the gain roll off from –40-dB to –20-dB per decade and increases the phase to 90 degree one decade above the zero frequency. The internal ripple injection high frequency zero is changed according to the switching frequency selected as shown in [Table 6-1](#). The inductor and capacitor selected for the output filter must be such that the double pole is located close enough to the high-frequency zero so that the phase boost provided by this high-frequency zero provides adequate phase margin for the stability requirement. The crossover frequency of the overall system must usually be targeted to be less than one-fifth of the switching frequency (F_{SW}).

Table 6-1. Ripple Injection Zero

| SWITCHING FREQUENCY (kHz) | ZERO LOCATION (kHz) |
|---------------------------|---------------------|
| 400 | 17.8 |
| 800 | 27.1 |
| 1200 | 29.8 |

[Table 6-2](#) lists the inductor values and part numbers that are used to plot the efficiency curves in [Section 5.7](#).

Table 6-2. Inductor Values

| V _{OUT} (V) | F _{SW} (kHz) | L _{OUT} (μH) | WÜRTH PART NUMBER ⁽¹⁾ |
|----------------------|-----------------------|-----------------------|----------------------------------|
| 1.2 | 400 | 1.2 | 744325120 |
| | 800 | 0.68 | 744311068 |
| | 1200 | 0.47 | 744314047 |
| 3.3 | 400 | 2.4 | 744325240 |
| | 800 | 1.5 | 7443552150 |
| | 1200 | 1.2 | 744325120 |
| 5.5 | 400 | 3.3 | 744325330 |
| | 800 | 2.4 | 744325240 |
| | 1200 | 1.5 | 7443552150 |

(1) See [Third-Party Products](#) disclaimer.

6.3.2 Eco-mode Control

The TPS56C215 is designed with Eco-mode control to increase efficiency at light loads. This option can be chosen using the MODE pin as shown in [Table 6-3](#). As the output current decreases from heavy load condition, the inductor current is also reduced. If the output current is reduced enough, the valley of the inductor current reaches the zero level, which is the boundary between continuous conduction and discontinuous conduction modes. The low-side MOSFET is turned off when a zero inductor current is detected. As the load current further decreases the converter runs into discontinuous conduction mode. The on-time is kept approximately the same as in continuous conduction mode. The off-time increases as discharging the output with a smaller load current takes more time. The light load current where the transition to Eco-mode operation happens ($I_{OUT(LL)}$) can be calculated from [Equation 2](#).

$$I_{OUT(LL)} = \frac{1}{2 \times L_{OUT} \times F_{SW}} \times \frac{(V_{IN} - V_{OUT}) \times V_{OUT}}{V_{IN}} \quad (2)$$

After identifying the application requirements, design the output inductance (L_{OUT}) so that the inductor peak-to-peak ripple current is approximately between 20% and 30% of the $I_{OUT(max)}$ (peak current in the application). Sizing the inductor properly so that the valley current does not hit the negative low-side current limit is important.

6.3.3 4.7-V LDO

The VREG5 pin is the output of the internal 4.7-V linear regulator that creates the bias for all the internal circuitry and MOSFET gate drivers. The VREG5 pin needs to be bypassed with a 4.7- μ F capacitor. An external voltage that is above the internal output voltage of the LDO can override the internal LDO, switching the internal LDO to the external rail after a higher voltage is detected. This enhances the efficiency of the converter because the quiescent current now runs off this external rail instead of the input power supply. The UVLO circuit monitors the VREG5 pin voltage and disables the output when VREG5 falls below the UVLO threshold. When using an external bias on the VREG5 rail, any power-up and power-down sequencing can be applied but understanding that if there is a discharge path on the VREG5 rail that can pull a current higher than the internal current limit of the LDO (ILIM5) from the VREG5, then the VREG5 LDO turns off thereby shutting down the output of TPS56C215 is important. If such condition does not exist and if the external VREG5 rail is turned off, the VREG5 voltage switches over to the internal LDO voltage which is 4.7 V typically in a few nanoseconds. Figure 6-1 shows this transition of the VREG5 voltage from an external bias of 5.5 V to the internal LDO output of 4.7 V when the external bias to VREG5 is disabled while the output of TPS56C215 remains unchanged.




Figure 6-1. VREG5 Transition

6.3.4 MODE Selection

The TPS56C215 has a MODE pin that can offer 12 different states of operation as a combination of current limit, switching frequency, and light load operation. The device can operate at two different current limits ILIM-1 and ILIM to support an output continuous current of 10 A and 12 A, respectively. The TPS56C215 is designed to compare the valley current of the inductor against the current limit thresholds so understand that the output current is half the ripple current higher than the valley current. For example, with the ILIM current limit selection,

the OCL threshold is 11.73-A minimum, which means that a pk-pk inductor ripple current of 0.54-A minimum is needed to be able to draw 12 A out of the converter without entering an overcurrent condition. The TPS56C215 can operate at three different frequencies of 400 kHz, 800 kHz, and 1200 kHz and also can choose between Eco-mode and FCCM mode. The device reads the voltage on the MODE pin during start-up and latches onto one of the MODE options listed in [Table 6-3](#). The voltage on the MODE pin can be set by connecting this pin to the center tap of a resistor divider connected between VREG5 and AGND. A guideline for the top resistor (R_{M_H}) and the bottom resistor (R_{M_L}) in 1% resistors is shown in [Table 6-3](#). Make sure that the voltage for the MODE pin is derived from the VREG5 rail only because internally this voltage is referenced to detect the MODE option. The MODE pin setting can be reset only by a VIN power cycling.

Table 6-3. MODE Pin Resistor Settings

| R_{M_L} (k Ω) | R_{M_H} (k Ω) | LIGHT LOAD OPERATION | CURRENT LIMIT | FREQUENCY (kHz) |
|--------------------------|--------------------------|----------------------|---------------|-----------------|
| 5.1 | 300 | FCCM | ILIM-1 | 400 |
| 10 | 200 | FCCM | ILIM | 400 |
| 20 | 160 | FCCM | ILIM-1 | 800 |
| 20 | 120 | FCCM | ILIM | 800 |
| 51 | 200 | FCCM | ILIM-1 | 1200 |
| 51 | 180 | FCCM | ILIM | 1200 |
| 51 | 150 | DCM | ILIM-1 | 400 |
| 51 | 120 | DCM | ILIM | 400 |
| 51 | 91 | DCM | ILIM-1 | 800 |
| 51 | 82 | DCM | ILIM | 800 |
| 51 | 62 | DCM | ILIM-1 | 1200 |
| 51 | 51 | DCM | ILIM | 1200 |

[Figure 6-2](#) shows the typical start-up sequence of the device after the EN pin voltage crosses the EN turn-on threshold. After the voltage on VREG5 pin crosses the rising UVLO threshold, reading the first MODE setting takes 100 μ s and approximately 100 μ s from there to finish the last MODE setting. The output voltage starts ramping after the MODE setting reading is completed.




Figure 6-2. Power-Up Sequence

6.3.5 Soft Start and Prebiased Soft Start

The TPS56C215 has an adjustable soft start time that can be set by connecting a capacitor on SS pin. When the EN pin becomes high, the soft-start charge current (I_{SS}) begins charging the external capacitor (C_{SS}) connected between SS and AGND. The device tracks the lower of the internal soft-start voltage or the external soft-start voltage as the reference. The equation for the soft-start time (T_{SS}) is shown in [Equation 3](#):

$$T_{SS(S)} = \frac{C_{SS} \times V_{REF}}{I_{SS}} \quad (3)$$

where

- V_{REF} is 0.6 V and I_{SS} is 6 μ A

If the output capacitor is prebiased at start-up, the device initiates switching and starts ramping up only after the internal reference voltage becomes greater than the feedback voltage V_{FB} . This scheme makes sure that the converters ramp up smoothly into regulation point.

6.3.6 Enable and Adjustable UVLO

The EN pin controls the turn-on and turnoff of the device. When EN pin voltage is above the turn-on threshold which is around 1.2 V, the device starts switching, and when the EN pin voltage falls below the turn-off threshold, which is around 1.1 V, the device stops switching. If the user application requires a different turn-on (V_{START}) and turnoff thresholds (V_{STOP}) respectively, the EN pin can be configured as shown in [Figure 6-3](#) by connecting a resistor divider between VIN and EN. The EN pin has a pullup current I_{p1} that sets the default state of the pin when floating. This current increases to I_{p2} when the EN pin voltage crosses the turn-on threshold. The UVLO thresholds can be set by using [Equation 4](#) and [Equation 5](#).




Figure 6-3. Adjustable VIN Undervoltage Lockout

$$R1 = \frac{V_{START} \left(\frac{V_{ENFALLING}}{V_{ENRISING}} \right) - V_{STOP}}{I_{p1} \left(1 - \frac{V_{ENFALLING}}{V_{ENRISING}} \right) + I_h} \quad (4)$$

$$R2 = \frac{R1 \times V_{ENFALLING}}{V_{STOP} - V_{ENFALLING} + R1 I_{p2}} \quad (5)$$

where

- $I_{p2} = 4.197 \mu\text{A}$
- $I_{p1} = 1.91 \mu\text{A}$
- $I_h = 2.287 \mu\text{A}$
- $V_{ENRISING} = 1.225 \text{ V}$
- $V_{ENFALLING} = 1.104 \text{ V}$

6.3.7 Power Good

The Power Good (PGOOD) pin is an open-drain output. After the FB pin voltage is between 93% and 107% of the internal reference voltage (V_{REF}), the PGOOD is deasserted and floats after a 200- μs deglitch time. TI recommends a pullup resistor of 10 k Ω to pull up to VREG5. The PGOOD pin is pulled low when the FB pin voltage is lower than V_{UVP} or greater than V_{OVP} threshold, in an event of thermal shutdown, or during the soft-start period.


6.3.8 Overcurrent Protection and Undervoltage Protection

The output overcurrent limit (OCL) is implemented using a cycle-by-cycle valley detect control circuit. The switch current is monitored during the OFF state by measuring the low-side FET drain to source voltage. This voltage is proportional to the switch current. During the on-time of the high-side FET switch, the switch current increases at a linear rate determined by input voltage, output voltage, the on-time, and the output inductor value. During the on-time of the low-side FET switch, this current decreases linearly. The average value of the switch current is the load current I_{OUT} . If the measured drain-to-source voltage of the low-side FET is above the voltage proportional to current limit, the low-side FET stays on until the current level becomes lower than the OCL level which reduces the output current available. When the current is limited the output voltage tends to drop because the load demand is higher than what the converter can support. When the output voltage falls below 68% of the target voltage, the UVP comparator detects the fall and shuts down the device after a wait time of $1 \times t_{SS}$. The device re-starts after a hiccup time of $14 \times t_{SS}$. In this type of valley detect control, the load current is higher than the OCL threshold by one half of the peak-to-peak inductor ripple current. When the overcurrent condition is removed, the output voltage returns to the regulated value. If an OCL condition happens during start-up, then the device enters hiccup-mode immediately without a wait time of 1 soft-start cycle.

6.3.9 Transient Response Enhancement

The PSM deglitch feature activates whenever the device transitions from a heavy load in Continuous Conduction Mode (CCM) to a light load in Discontinuous Conduction Mode (DCM). During this transition, the system enters Forced Continuous Conduction Mode (FCCM) for 16 cycles before switching to DCM. This feature is designed to provide fast recovery in load transients during DCM operation.

Figure 6-4 shows 16-cycle and 32-cycle FCCM operation during load release and dynamic COMP pin positioning. Figure 6-5 shows steady-state Auto-skip mode operation with the dynamic COMP pin clamp.



6.3.10 UVLO Protection

Undervoltage lockout protection (UVLO) monitors the internal VREG5 regulator voltage. When the VREG5 voltage is lower than UVLO threshold voltage, the device is shut off. This protection is non-latching.

6.3.11 Thermal Shutdown

The device monitors the internal die temperature. If this temperature exceeds the thermal shutdown threshold value (T_{SDN} typically 160°C), the device shuts off. This protection is a non-latch protection. During start-up, if the device temperature is higher than 160°C , the device does not start switching and does not load the MODE settings. If the device temp goes higher than T_{SDN} threshold after start-up, the device stops switching with SS reset to ground and an internal discharge switch turns on to quickly discharge the output voltage. The device re-starts switching when the temperature goes below the thermal shutdown threshold but the MODE settings are not re-loaded again.

6.3.12 Output Voltage Discharge

The device has a 500- Ω discharge switch that discharges the output V_{OUT} through SW node during any event of fault like output overvoltage, output undervoltage, TSD, if VREG5 voltage below the UVLO and when the EN pin voltage (V_{EN}) is below the turn-on threshold.

6.4 Device Functional Modes

6.4.1 Light Load Operation

When the MODE pin is selected to operate in FCCM mode, the converter operates in continuous conduction mode (FCCM) during light-load conditions. During FCCM, the switching frequency (F_{SW}) is maintained at an almost constant level over the entire load range which is designed for applications requiring tight control of the switching frequency and output voltage ripple at the cost of lower efficiency under light load. If the MODE pin is selected to operate in DCM/Eco-mode, the device enters pulse skip mode after the valley of the inductor ripple current crosses zero. The Eco-mode maintains higher efficiency at light load with a lower switching frequency.

6.4.2 Standby Operation

The TPS56C215 can be placed in standby mode by pulling the EN pin low. The device operates with a shut-down current of 7 μA when in standby condition.

7 Application and Implementation

Note

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes, as well as validating and testing their design implementation to confirm system functionality.

7.1 Application Information

The schematic of [Figure 7-1](#) shows a typical application for TPS56C215. This design converts an input voltage range of 4.5 V to 17 V down to 1.2 V with a maximum output current of 12 A.

7.2 Typical Application




Figure 7-1. Application Schematic

7.2.1 Design Requirements

Table 7-1. Design Parameters

| PARAMETER | CONDITIONS | MIN | TYP | MAX | UNIT |
|--------------------------|-----------------------|-----|---------------|-----|---------------------|
| V _{OUT} | Output voltage | | 1.2 | | V |
| I _{OUT} | Output current | | 12 | | A |
| ΔV _{OUT} | Transient response | | 40 | | mV |
| V _{IN} | Input voltage | 4.5 | 12 | 17 | V |
| V _{OUT(ripple)} | Output voltage ripple | | 20 | | mV _(P-P) |
| | Start input voltage | | Internal UVLO | | V |
| | Stop input voltage | | Internal UVLO | | V |
| F _{SW} | Switching frequency | | 1.2 | | MHz |
| Operating mode | | | DCM | | |
| T _A | Ambient temperature | | 25 | | °C |

7.2.2 Detailed Design Procedure

7.2.2.1 Custom Design With WEBENCH® Tools

[Click here](#) to create a custom design using the TPS56C215 device with the WEBENCH® Power Designer.

1. Start by entering the input voltage (V_{IN}), output voltage (V_{OUT}), and output current (I_{OUT}) requirements.
2. Optimize the design for key parameters such as efficiency, footprint, and cost using the optimizer dial.

- Compare the generated design with other possible solutions from Texas Instruments.

The WEBENCH Power Designer provides a customized schematic along with a list of materials with real-time pricing and component availability. In most cases, these actions are available:

- Run electrical simulations to see important waveforms and circuit performance
- Run thermal simulations to understand board thermal performance
- Export customized schematic and layout into popular CAD formats
- Print PDF reports for the design, and share the design with colleagues

Get more information about WEBENCH tools at www.ti.com/WEBENCH.

7.2.2.2 External Component Selection

7.2.2.2.1 Output Voltage Set Point

To change the output voltage of the application, changing the value of the upper feedback resistor is necessary. By changing this resistor the user can change the output voltage above 0.6 V. See [Equation 6](#).

$$V_{OUT} = 0.6 \times \left(1 + \frac{R_{UPPER}}{R_{LOWER}} \right) \quad (6)$$

7.2.2.2.2 Switching Frequency and MODE Selection

Switching Frequency, current limit, and switching mode (DCM or FCCM) are set by a voltage divider from VREG5 to GND connected to the MODE pin. See [Table 6-3](#) for possible MODE pin configurations. Switching frequency selection is a tradeoff between higher efficiency and smaller system design size. Lower switching frequency yields higher overall efficiency but relatively bigger external components. Higher switching frequencies cause additional switching losses which impact efficiency and thermal performance. For this design, 1.2 MHz is chosen as the switching frequency, the switching mode is DCM and the output current is 12 A.

7.2.2.2.3 Inductor Selection

The inductor ripple current is filtered by the output capacitor. A higher inductor ripple current means the output capacitor must have a ripple current rating higher than the inductor ripple current. See [Table 7-2](#) for recommended inductor values.

The RMS and peak currents through the inductor can be calculated using [Equation 7](#) and [Equation 8](#). Make sure that the inductor is rated to handle these currents.

$$I_{L(rms)} = \sqrt{\left(I_{OUT}^2 + \frac{1}{12} \times \left(\frac{V_{OUT} \times (V_{IN(max)} - V_{OUT})}{V_{IN(max)} \times L_{OUT} \times F_{SW}} \right)^2 \right)} \quad (7)$$

$$I_{L(peak)} = I_{OUT} + \frac{I_{OUT(ripple)}}{2} \quad (8)$$

During transient, short circuit conditions, the inductor current can increase up to the current limit of the device so choosing an inductor with a saturation current higher than the peak current under current limit condition is safe.

7.2.2.2.4 Output Capacitor Selection

After selecting the inductor, the output capacitor needs to be optimized. In DCAP3, the regulator reacts within one cycle to the change in the duty cycle so the good transient performance can be achieved without needing large amounts of output capacitance. The recommended output capacitance range is given in [Table 7-2](#)

Ceramic capacitors have very low ESR, otherwise the maximum ESR of the capacitor must be less than $V_{OUT(ripple)}/I_{OUT(ripple)}$.

Table 7-2. Recommended Component Values

| V _{OUT} (V) | R _{LOWER} (kΩ) | R _{UPPER} (kΩ) | F _{SW} (kHz) | L _{OUT} (μH) | C _{OUT(min)} (μF) | C _{OUT(max)} (μF) | C _{FF} (pF) |
|----------------------|-------------------------|-------------------------|-----------------------|-----------------------|----------------------------|----------------------------|----------------------|
| 0.6 | 10 | 0 | 400 | 0.68 | 300 | 500 | – |
| | | | 800 | 0.47 | 100 | 500 | – |
| | | | 1200 | 0.33 | 88 | 500 | – |
| 1.2 | | 10 | 400 | 1.2 | 100 | 500 | – |
| | | | 800 | 0.68 | 88 | 500 | – |
| | | | 1200 | 0.47 | 88 | 500 | – |
| 3.3 | | 45.3 | 400 | 2.4 | 88 | 500 | 100–220 |
| | | | 800 | 1.5 | 88 | 500 | 100–220 |
| | | | 1200 | 1.2 | 88 | 500 | 100–220 |
| 5.5 | | 82.5 | 400 | 3.3 | 88 | 500 | 100–220 |
| | | | 800 | 2.4 | 88 | 500 | 100–220 |
| | | | 1200 | 1.5 | 88 | 700 | 100–220 |

7.2.2.2.5 Input Capacitor Selection

The minimum input capacitance required is given in [Equation 9](#).

$$C_{IN(min)} = \frac{I_{OUT} \times V_{OUT}}{V_{IN(ripple)} \times V_{IN} \times F_{SW}} \quad (9)$$

TI recommends using a high quality X5R or X7R input decoupling capacitors of 40 μF on the input voltage pin. The voltage rating on the input capacitor must be greater than the maximum input voltage. The capacitor must also have a ripple current rating greater than the maximum input current ripple of the application. The input ripple current is calculated by [Equation 10](#):

$$I_{CIN(rms)} = I_{OUT} \times \sqrt{\frac{V_{OUT}}{V_{IN(min)}} \times \frac{(V_{IN(min)} - V_{OUT})}{V_{IN(min)}}} \quad (10)$$

7.2.3 Application Curves

Figure 7-2 through Figure 7-8 apply to the circuit of Figure 7-1 . $V_{IN} = 12\text{ V}$, $f_{SW} = 800\text{ kHz}$, $T_a = 25^\circ\text{C}$ unless otherwise specified.




Figure 7-2. Efficiency




Figure 7-3. Load Regulation




Figure 7-4. Output Voltage Ripple, $I_{OUT} = 10\text{ mA}$,
Time = $80\ \mu\text{s}/\text{div}$




Figure 7-5. Output Voltage Ripple, $I_{OUT} = 12\text{ A}$,
Time = $1\ \mu\text{s}/\text{div}$




Figure 7-6. Start-Up Relative to EN Rising, Time = $2\text{ ms}/\text{div}$




Figure 7-7. Shutdown Relative to EN Falling, Time = $200\ \mu\text{s}/\text{div}$




Figure 7-8. Transient Response, Load Step = 3 A – 9 A – 3 A, Slew Rate Setting = 2.5 A/ μ S, Time = 100 μ S/div

7.3 Power Supply Recommendations

The TPS56C215 is intended to be powered by a well regulated dc voltage. The input voltage range is 3.8 to 17 V. TPS56C215 is a buck converter. The input supply voltage must be greater than the desired output voltage for proper operation. Input supply current must be appropriate for the desired output current. If the input voltage supply is located far from the TPS56215 circuit, some additional input bulk capacitance is recommended. Typical values are 100 μ F to 470 μ F.

7.4 Layout

7.4.1 Layout Guidelines

- Recommend a four-layer or six-layer PCB for good thermal performance and with maximum ground plane. 3" \times 3", four-layer PCB with 2-oz. copper used as example.
- Recommend having equal caps on each side of the IC. Place them right across VIN as close as possible.
- Inner layer 1 is ground with the PGND to AGND net tie
- Inner layer2 has VIN copper pour that has vias to the top layer VIN. *Place multiple vias under the device near VIN and PGND and near input capacitors* to reduce parasitic inductance and improve thermal performance
- Bottom later is GND with the BOOT trace routing.
- Reference feedback to the quite AGND and routed away from the switch node.
- Make VIN trace wide to reduce the trace impedance.

7.4.2 Layout Example

Figure 7-9 shows the recommended top side layout. Component reference designators are the same as the circuit shown in Figure 7-1. Resistor divider for EN is not used in the circuit of Figure 7-1, but are shown in the layout for reference.




Figure 7-9. Top Side Layout

Figure 7-10 shows the recommended layout for the first internal layer. The figure is comprised of a large PGND plane and a smaller ANGD island. AGND and PGND are connected at a single point to reduce circulating currents.




Figure 7-10. Mid Layer 1 Layout

Figure 7-11 shows the recommended layout for the second internal layer. The figure is comprised of a large PGND plane, a smaller copper fill area to connect the two top side V_{IN} copper areas and a second V_{OUT} copper fill area.




Figure 7-11. Mid Layer 2 Layout

8 Device and Documentation Support

8.1 Device Support

8.1.1 Third-Party Products Disclaimer

TI'S PUBLICATION OF INFORMATION REGARDING THIRD-PARTY PRODUCTS OR SERVICES DOES NOT CONSTITUTE AN ENDORSEMENT REGARDING THE SUITABILITY OF SUCH PRODUCTS OR SERVICES OR A WARRANTY, REPRESENTATION OR ENDORSEMENT OF SUCH PRODUCTS OR SERVICES, EITHER ALONE OR IN COMBINATION WITH ANY TI PRODUCT OR SERVICE.

8.1.2 Development Support

The evaluation module for system validation is shown in [Figure 8-1](#).




Figure 8-1. System Validation EVM Board

8.1.2.1 Custom Design With WEBENCH® Tools

[Click here](#) to create a custom design using the TPS56C215 device with the WEBENCH® Power Designer.

1. Start by entering the input voltage (VIN), output voltage (VOUT), and output current (IOUT) requirements.
2. Optimize the design for key parameters such as efficiency, footprint, and cost using the optimizer dial.
3. Compare the generated design with other possible solutions from Texas Instruments.

The WEBENCH Power Designer provides a customized schematic along with a list of materials with real-time pricing and component availability. In most cases, these actions are available:

- Run electrical simulations to see important waveforms and circuit performance
- Run thermal simulations to understand board thermal performance
- Export customized schematic and layout into popular CAD formats
- Print PDF reports for the design, and share the design with colleagues

Get more information about WEBENCH tools at www.ti.com/WEBENCH.

8.2 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. Click on *Notifications* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

8.3 Support Resources

[TI E2E™ support forums](#) are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's [Terms of Use](#).

8.4 Trademarks

SWIFT™, D-CAP3™, HotRod™, and TI E2E™ are trademarks of Texas Instruments.

WEBENCH® is a registered trademark of Texas Instruments.

All trademarks are the property of their respective owners.

8.5 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

8.6 Glossary

[TI Glossary](#)

This glossary lists and explains terms, acronyms, and definitions.

9 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

| Changes from Revision G (August 2024) to Revision H (June 2025) | Page |
|--|-------------|
| • Changed MOSFET values from 13.5mΩ and 4.5mΩ to 7.8mΩ and 3.2mΩ..... | 1 |
| • Added WEBENCH link in the <i>Features</i> | 1 |
| • Updated Efficiency vs Output Current figure to include the most recent data for the device..... | 1 |
| • Updated $R_{DS(on)H}$ from 13.5 mΩ to 7.8 mΩ , $R_{DS(on)L}$ from 4.5 mΩ to 3.2 mΩ and t_{UVPEN} hiccup time from 7 cycles to 14 cycles..... | 5 |
| • Changed I_{IN} typ value from 600μA to 146μA and deleted I_{IN} max value..... | 5 |
| • Changed $I_{VINS DN}$ typ value from 7μA to 9.3μA..... | 5 |
| • Changed $V_{PGOODTH}$ VFB falling (good) value from 107% to 108%..... | 5 |
| • Changed V_{UVP} value from 68% to 70%..... | 5 |
| • Changed UVLO VREG5 rising voltage value from 4.3V to 4.25V..... | 5 |
| • Changed UVLO VREG5 falling voltage value from 3.57V to 3.52..... | 5 |
| • Changed UVLO, VREG5 = 4.7V VIN falling voltage, VREG5 = 4.7V value from 3.26V to 3.24V..... | 5 |
| • Changed UVLO, VREG5 = 4.7V VIN hysteresis, VREG5 = 4.7V value from 60mV to 80mV..... | 5 |
| • Changed t_{ON} min value from 54ns to 60ns..... | 6 |
| • Changed t_{SS} value from 1.045ms to 1.2ms..... | 6 |
| • Updated Figure 5-9 to Figure 5-34 to include the most recent data for the device..... | 7 |
| • Deleted High-side RDS(on) vs Temperature and Low-side RDS(on) vs Temperature figures..... | 7 |
| • Changes MOSFET values from 13.5-mΩ to 7.8-mΩ and 4.5-mΩ to 3.2-mΩ..... | 13 |
| • Changed "Zero Location" values in Table 6-1 from 7.1 to 17.8, from 14.3 to 27.1, from 21.4 to 29.8..... | 14 |
| • Changed wait time from 1 ms to $1 \times t_{SS}$ and hiccup time from 7ms to $14 \times t_{SS}$ | 19 |
| • Added the Transient Response Enhancement section..... | 20 |
| • Added <i>Custom Design With WEBENCH® Tools</i> section..... | 21 |
| • Updated Application Curves to include the most recent data for the device..... | 24 |
| • Added <i>Custom Design With WEBENCH® Tools</i> section..... | 30 |

| Changes from Revision F (August 2023) to Revision G (August 2024) | Page |
|--|-------------|
| • Changed description "TI's smallest" to "a small" with updated products portfolio. | 1 |
| • Deleted $T_{SDN VREG5}$ spec..... | 5 |
| • Added note "Specified by design" for the SW On Time parameter..... | 6 |
| • Removed Out-of-Bounds Operation section..... | 14 |
| • Updated Thermal Shutdown section..... | 20 |

10 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

10.1 Package Marking




Figure 10-1. Symbolization

PACKAGING INFORMATION

| Orderable part number | Status (1) | Material type (2) | Package Pins | Package qty Carrier | RoHS (3) | Lead finish/ Ball material (4) | MSL rating/ Peak reflow (5) | Op temp (°C) | Part marking (6) |
|-------------------------------|---------------|----------------------|--------------------|-----------------------|-------------|--------------------------------------|-----------------------------------|--------------|---------------------|
| TPS56C215RNNR | Active | Production | VQFN-HR (RNN) 18 | 3000 LARGE T&R | Yes | Call TI Sn | Level-2-260C-1 YEAR | -40 to 125 | 56C215 |
| TPS56C215RNNR.A | Active | Production | VQFN-HR (RNN) 18 | 3000 LARGE T&R | Yes | SN | Level-2-260C-1 YEAR | -40 to 125 | 56C215 |
| TPS56C215RNNT | Active | Production | VQFN-HR (RNN) 18 | 250 SMALL T&R | Yes | Call TI Sn | Level-2-260C-1 YEAR | -40 to 125 | 56C215 |
| TPS56C215RNNT.A | Active | Production | VQFN-HR (RNN) 18 | 250 SMALL T&R | Yes | SN | Level-2-260C-1 YEAR | -40 to 125 | 56C215 |

(1) **Status:** For more details on status, see our [product life cycle](#).

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.


(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| TPS56C215RNNR | VQFN-HR | RNN | 18 | 3000 | 330.0 | 12.4 | 3.75 | 3.75 | 1.15 | 8.0 | 12.0 | Q1 |
| TPS56C215RNNT | VQFN-HR | RNN | 18 | 250 | 180.0 | 12.4 | 3.75 | 3.75 | 1.15 | 8.0 | 12.0 | Q1 |
| TPS56C215RNNT | VQFN-HR | RNN | 18 | 250 | 180.0 | 12.4 | 3.75 | 3.75 | 1.15 | 8.0 | 12.0 | Q1 |

TAPE AND REEL BOX DIMENSIONS


*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|---------------|--------------|-----------------|------|------|-------------|------------|-------------|
| TPS56C215RNNR | VQFN-HR | RNN | 18 | 3000 | 367.0 | 367.0 | 35.0 |
| TPS56C215RNNT | VQFN-HR | RNN | 18 | 250 | 213.0 | 191.0 | 35.0 |
| TPS56C215RNNT | VQFN-HR | RNN | 18 | 250 | 210.0 | 185.0 | 35.0 |



NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.

EXAMPLE BOARD LAYOUT

RNN0018A

VQFN-HR - 1 mm max height

PLASTIC QUAD FLATPACK - NO LEAD



NOTES: (continued)


- This package is designed to be soldered to a thermal pad on the board. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/slua271).
- Solder mask tolerances between and around signal pads can vary based on board fabrication site.

EXAMPLE STENCIL DESIGN

RNN0018A

VQFN-HR - 1 mm max height

PLASTIC QUAD FLATPACK - NO LEAD



NOTES: (continued)

5. For alternate stencil design recommendations, see IPC-7525 or board assembly site preference.

IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#), [TI's General Quality Guidelines](#), or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2026, Texas Instruments Incorporated

Last updated 10/2025